



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE LIST North American prices are ExWorks Ship From Address unless noted otherwise. European and Asian prices are DAP Ship To Address unless noted otherwise. Payment terms unless otherwise noted are 30 days. Price, product design, configuration and specifications subject to change without notice.	



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	FUNCTIONAL INSTRUMENTATION TABLE OF CONTENTS	
	Section A : ANALOG TEST SUBSYSTEMS	
	Section B : BUS TEST INSTRUMENTS	
	Section C : VXI DIGITAL TEST INSTRUMENT & OPTIONS	
	Section D : HIGH SPEED SUB SYSTEM & OPTIONS	
	Section E : DIGITAL HARDWARE OPTIONS	
	Section F : SOFTWARE OPTIONS	
	Section G : removed	
	Section H : OTHER OPTIONS	
	Section I : SERVICE AGREEMENTS	
	Section J : SERVICES & SUPPORT OFFERINGS	
	Section K: TRAINING	
	Section L : CASS SUBSYSTEM AND OPTIONS	
	Section M : COSSI OPTIONS	
	Section N : IFTE PROGRAM	
	Section P: ZT Series Scopes, Digitizers, AFWGs & OPTIONS	
	Section R: VERTA Switching & Options	



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	Warranty notes Standard hardware and software is defined to be that listed in the Price List with Teradyne Part Numbers.	
	TERMS AND CONDITIONS The pricing contained in this catalog is based on Teradyne's standard Terms and Conditions which can be found on our website: https://www.teradyne.com/defense-aerospace-terms-of-sale/	
	WARRANTY These notes applicable to the warranty do not replace any warranty statement but are notes in addition to standard warranty statements. <ol style="list-style-type: none">1. Software warranty is 1 year. The software shipped with the test system has one year of software support included in the purchase price of the test system.2. For non-standard (not in the price list) OEM hardware, Teradyne will provide one year of exact swap support (E-Swap). This one year commences upon shipment or installation, if installed by Teradyne. E-Swap support is the repair and return of the same instrument sent in for repair. For non-standard (not in the price list) OEM software, Teradyne will pass on to the customer the warranty of the manufacturer. This will be the full warranty or whatever is remaining on it at the time of shipment.	
	INSTALLATION <ol style="list-style-type: none">1. Prices for systems and options ordered with systems include installation by Teradyne Global Field Service.2. If the customer wishes Teradyne Field Service to install hardware and software options and upgrades ordered subsequent to system order, installation must be quoted at standard rates. Exceptions to this are options where installation is specifically stated as included.3. For non-standard (not in the Price List) OEM hardware and / or software, installation is not included unless specifically quoted.	



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	Policy Statements	
	1. All customers are required to sign a Teradyne Software License Agreement.	
	2. Shipments are made F.O.B.(Exworks) Factory (North Reading).	
	3. This information is proprietary to Teradyne, and is to be used only for the purpose of preparing quotations or placing orders for the products listed herein.	
	4. If non-standard (not in the Price List) OEM instrumentation and/or software is provided as part of a Spectrum Series system quotation, Teradyne policy is to quote at 33% (x1.33) mark-up over the OEM's published U.S. list price. When the non-standard OEM instrumentation and/or software plus ICA and ITA cable kit price exceeds 30% of the total recurring system price, the price of the non-standard OEM instrumentation and/or software will be marked up an additional 50% (x1.5), for a total markup of 99.5% (*1.995)Integration and handling charges are quoted separately.	
	5. If non-standard (not in Price List) miscellaneous integration materials (e.g. cables, connectors, tools, computer components, Card Cages and mechanical assemblies) are provided as part of a quotation, Teradyne policy is to quote at 150% (x 2.5) mark-up over OEM published U.S. list price. Integration charges are quoted separately.	
	6. For Third Party Services, Teradyne's policy is to quote 66% (x1.66) mark up over OEM published U.S. list prices for all third party services incorporated into any support agreement.	
	7. For all non-Teradyne manufactured instruments purchased after the system is purchased (installed & spares), the price will be marked up an additional 50%. Non-Teradyne manufactured spares purchased with a new system will be marked up an additional 50%.	
	8. For all customer furnished instrumentation (CFE/CFM) there will be a processing, handling, and integration charge equal to 25% of the vendor list price for the item. If more than 2 of the same instrument are provided to Teradyne as CFE/CFM for the same order, and same delivery time, instruments after the first 2 will have the CFE/CFM capped at \$1000 per additional instrument. When the non-standard OEM instrumentation and/or software plus ICA and ITA cable kit price exceeds 30% of the total recurring system price when priced per policy statements 4 & 5, or the CFE/CFM is supplied to Teradyne independent of a system purchase, the price of the customer furnished instruments will be marked up an additional 50% (x1.5), for a total markup of 37.5% (*1.375). Teradyne does not calibrate CFE/CFM instruments as part of the integration.	
	9. For all customer furnished miscellaneous integration materials (CFE/CFM) such as cables, connectors, tools, computer components, Card Cages and mechanical assemblies, there will be a	



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	processing, handling, and integration charge equal to 100% of the vendor list price for the item. If more than 2 of the same item are provided to Teradyne as CFE/CFM for the same order, and same delivery time, items after the first 2 will have the CFE/CFM capped at \$1000 per additional item.	
	10. Third party NRE (Non-Recurring Engineering) required to implement custom solutions will be marked up 100% over Teradyne cost.	
	11. Support Agreements less than 1 year in duration may be subject to a 10% administrative fee.	
	12. For ITA's and associated materials (Adapters, cables, load boards) that are delivered with, or in support of a Teradyne developed TPS, Teradyne policy is to quote at 100% (x2.0) mark-up over vendor list price for the materials, or completed ITA assembly. Design and integration of the ITA is quoted separately	
	13. When Teradyne provides pricing beyond 60 days, pricing will be escalated based on the current financial outlook.	
	14. For support contracts that are based on list price, the list price is determined by taking the list price at the time of the most recent sale or quotation and escalating based on an annual escalator.	
	15. All orders are subject to a minimum order value of \$1,000.	
	16. For Spectrum Series Systems which include Preconfigured RF Options additional 3rd party instrument or software content that is not in the RF option or the Price List is marked up 33% over published U.S. list price for the first \$100,000 of content. When this content exceeds \$100,000, the markup for all additional 3rd party content will be 99.5%. Integration and handling charges are quoted separately.	



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #

DESCRIPTION

LIST PRICE

LIMITED REPRODUCTION RIGHTS

A Teradyne Customer may reproduce this document under the Software Support Agreement solely for internal use by the Customer's employees whose responsibilities include Teradyne equipment. Any copy of this document, or portions thereof, must contain the copyright and proprietary rights notice as stated on the original.

Copyright 2025 Teradyne Inc.
Printed in U.S.A.
Teradyne Incorporated.
700 Riverpark Drive
North Reading, MA 01864

The material in this document is subject to change without notice. Teradyne, Inc. assumes no responsibility for any errors that may appear in this document.

This document contains trade secrets and confidential information, and is furnished pursuant to a license to the user from Teradyne, Incorporated. Use or reproduction of this document is restricted under the terms of the license.

RESTRICTED RIGHTS LEGEND

Use, duplication or disclosure is subject to the proprietary restriction markings on Teradyne's drawings and software documentation per DFARS 252.227-7015.



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section A: ANALOG TEST SUBSYSTEMS		
AI-762-20	AI-762-20 GENERATION 2 HIGH-PERFORMANCE ANALOG INSTRUMENTATION SUBSYSTEM Analog Test Instrumentation: <ul style="list-style-type: none">• High-density VXI C-Size instrument for high-performance operational and parallel test• (8) Multi-Function Analog (MFA) Tester-Per-Pin Channels<ul style="list-style-type: none">• 1ns resolution Timer/Counter (T/C)• 200 MS/s, 14-bit Arbitrary Waveform Generator (AWG)• 50 MS/s, 12-bit Digitizer• 6½ Digital Multimeter (DMM)• 2-Channel 2 GS/s Digital Sampling Oscilloscope (DSO) NOTES: Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One-year warranty on Teradyne manufactured PC boards• 90 days Advanced Replacement Service VXI Chassis: <ul style="list-style-type: none">• Ai-76x hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Ai-76x instruments Development Support: <p>For first time integration of the Ai-760 in new or updated test systems, Teradyne recommends the following integration support items:</p> <ul style="list-style-type: none">• 093-403-00 Ai-760 Developer Cable Kit Software: <ul style="list-style-type: none">• Includes software license to use the Ai-76x on the test system that includes this instrument and on stand alone computers used for program development at the same site as the instrument• If physical media is required order 601-196-00 Ai-760 System Software Media Kit Interfaces: <ul style="list-style-type: none">• It is recommended that the MFA Common Interface Board (CIB) P/N # 608-441-50 be used with the instrument. The CIB provides additional SSMB connections for trigger access.	\$ 91640



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-762-10	<p>AI-762-10 GENERATION 2 HIGH-PERFORMANCE ANALOG INSTRUMENTATION SUBSYSTEM</p> <p>Analog Test Instrumentation:</p> <ul style="list-style-type: none">• High-density VXI C-Size instrument for high-performance operational and parallel test• (8) Multi-Function Analog (MFA) Tester-Per-Pin Channels<ul style="list-style-type: none">• 1ns resolution Timer/Counter (T/C)• 200 MS/s, 14-bit Arbitrary Waveform Generator (AWG)• 50 MS/s, 12-bit Digitizer• 6½ Digital Multimeter (DMM) <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One-year warranty on Teradyne manufactured PC boards• 90 days Advanced Replacement Service <p>VXI Chassis:</p> <ul style="list-style-type: none">• Ai-76x hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Ai-76x instruments <p>Development Support:</p> <p>For first time integration of the Ai-760 in new or updated test systems, Teradyne recommends the following integration support items:</p> <ul style="list-style-type: none">• 093-403-00 Ai-760 Developer Cable Kit <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use the Ai-76x on the test system that includes this instrument and on stand alone computers used for program development at the same site as the instrument• If physical media is required order 601-196-00 Ai-760 System Software Media Kit <p>Interfaces:</p> <ul style="list-style-type: none">• It is recommended that the MFA Common Interface Board (CIB) P/N # 608-441-50 be used with the instrument. The CIB provides additional SSMB connections for trigger access.	\$ 72920



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-762-60	<p>AI-762-60 GENERATION 2 8 CHANNEL MULTI-FUNCTION ANALOG (MFA) INSTRUMENT</p> <p>Analog Test Instrumentation:</p> <ul style="list-style-type: none">• High-density VXI C-Size instrument for high-performance operational and parallel test• (8) Multi-Function Analog (MFA) Tester-Per-Pin Channels<ul style="list-style-type: none">• 1ns resolution Timer/Counter (T/C)• 200 MS/s, 14-bit Arbitrary Waveform Generator (AWG)• 50 MS/s, 12-bit Digitizer <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One-year warranty on Teradyne manufactured PC boards• 90 days Advanced Replacement Service <p>VXI Chassis:</p> <ul style="list-style-type: none">• Ai-76x hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Ai-76x instruments <p>Development Support:</p> <p>For first time integration of the Ai-760 in new or updated test systems, Teradyne recommends the following integration support items:</p> <ul style="list-style-type: none">• 093-403-00 Ai-760 Developer Cable Kit <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use the Ai-76x on the test system that includes this instrument and on stand alone computers used for program development at the same site as the instrument• If physical media is required order 601-196-00 Ai-760 System Software Media Kit <p>Interfaces:</p> <ul style="list-style-type: none">• It is recommended that the MFA Common Interface Board (CIB) P/N # 608-441-50 be used with the instrument. The CIB provides additional SSMB connections for trigger access.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-762-70	<p>AI-762-70 GENERATION 2 16 CHANNEL MULTI-FUNCTION ANALOG (MFA) INSTRUMENT</p> <p>Analog Test Instrumentation:</p> <ul style="list-style-type: none">• High-density VXI C-Size instrument for high-performance operational and parallel test• (16) Multi-Function Analog (MFA) Tester-Per-Pin Channels<ul style="list-style-type: none">• 1ns resolution Timer/Counter (T/C)• 200 MS/s, 14-bit Arbitrary Waveform Generator (AWG)• 50 MS/s, 12-bit Digitizer <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One-year warranty on Teradyne manufactured PC boards• 90 days Advanced Replacement Service <p>VXI Chassis:</p> <ul style="list-style-type: none">• Ai-76x hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Ai-76x instruments <p>Development Support:</p> <p>For first time integration of the Ai-760 in new or updated test systems, Teradyne recommends the following integration support items:</p> <ul style="list-style-type: none">• 093-403-00 Ai-760 Developer Cable Kit <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use the Ai-76x on the test system that includes this instrument and on stand alone computers used for program development at the same site as the instrument• If physical media is required order 601-196-00 Ai-760 System Software Media Kit <p>Interfaces:</p> <ul style="list-style-type: none">• It is recommended that the MFA Common Interface Board (CIB) P/N # 608-441-50 be used with the instrument. The CIB provides additional SSMB connections for trigger access.	\$ 89650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-762-50	AI-762-50 GENERATION 2 HIGH-PERFORMANCE ANALOG INSTRUMENTATION SUBSYSTEM Analog Test Instrumentation: <ul style="list-style-type: none">• High-density VXI C-Size instrument for high-performance operational and parallel test• 2-Channel 2 GS/s Digital Sampling Oscilloscope (DSO) NOTES: Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One-year warranty on Teradyne manufactured PC boards• 90 days Advanced Replacement Service VXI Chassis: <ul style="list-style-type: none">• Ai-76x hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Ai-76x instruments Development Support: <p>For first time integration of the Ai-760 in new or updated test systems, Teradyne recommends the following integration support items:</p> <ul style="list-style-type: none">• 093-403-00 Ai-760 Developer Cable Kit Software: <ul style="list-style-type: none">• Includes software license to use the Ai-76x on the test system that includes this instrument and on stand alone computers used for program development at the same site as the instrument• If physical media is required order 601-196-00 Ai-760 System Software Media Kit	Consult Factory
608-441-50	AI-762(GEN 2) MFA TRIGGER CIB This CIB provides access to MFA channel triggers using industry standard SMB connectors	\$ 1910
609-688-01	AI-762 CALIBRATION CABLE KIT The Ai-762 calibration cable kit includes the following items: <ul style="list-style-type: none">(1) Ai-762 DMM calibration cable interface board(1) Ai-762 DMM cable set(1) Ai-762 MFA calibration cable interface board(1) Ai-762 MFA calibration cable set(1) Ai-762 DSO calibration cable set	\$ 9450
628-525-00	AI-760 MFA ATTENUATOR CIB	\$ 5180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
601-196-00	<p>AI-760 SYSTEM SOFTWARE MEDIA KIT iStudio for Ai-760 Analog Test Instrument</p> <ul style="list-style-type: none">• iStudio Software License• Graphical User Interface Software• Function Panels• Software Media and Documentation on CD-ROM <p>IVI Compliant Instrument Software :</p> <ul style="list-style-type: none">• Instrument Driver License• C and C# Instrument Driver API Software• Self-Test and Calibration Software• Software Simulation• Software Media and Documentation on CD-ROM <p>Note:</p> <ul style="list-style-type: none">• The license to use this software is included with the Ai-760 instruments.• This software may also be used on stand alone computers used in program development at the same site as the instrument	Consult Factory
093-403-00	<p>AI-760 DEVELOPER CABLE KIT Ai-760 connection and adapter cables for use during TPS program development and debug.</p> <p>Contains the following cables and interface accessories:</p> <ul style="list-style-type: none">• (2) Developer DSO Probe Adapter Cable 4" SSMB plug to BNC jack probe adapter cables• (1) Developer DMM Adapter Cable DB15 to 5 banana plugs cable• (5) Developer SSMB Channel Cable 24" RG316/U SSMB plug to SSMB plug connector cables• (5) BNC Channel Cable 24" RG316/U SSMB plug to BNC plug connector cables• (1) Strain relief bracket Aluminum bracket (and attachment screws) and (20) tie wraps to provide cable strain relief for Ai-760 front panel connections	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-705-00	<p>HIGH DENSITY 8 CHANNEL MULTIFUNCTION ANALOG INSTRUMENTATION SUBSYSTEM</p> <p>A High-Density VXI C-Size Instrument for Parallel Analog Test includes 8 channels with voltage ranges from -12 to +12V</p> <p>Each Ai-705-00 channel has 6 independent instruments including</p> <ul style="list-style-type: none">• Function Generator• Arbitrary Waveform Generator• Digitizer• DMM• Limit Detector• Timer Counter <p>VXI plug&play Software for Windows Framework:</p> <ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test and Calibration Software• Software Media and Documentation on CD-ROM <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Ai-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
AI-710-00	<p>HIGH DENSITY 32 CHANNEL MULTIFUNCTION ANALOG INSTRUMENTATION SUBSYSTEM</p> <p>A High-Density VXI C-Size Instrument for Parallel Analog Test includes 32 channels with voltage ranges from -12 to +12V.</p> <p>Each Ai-710-00 channel has 6 independent instruments including</p> <ul style="list-style-type: none">• Function Generator• Arbitrary Waveform Generator• Digitizer• DMM• Limit Detector• Timer Counter <p>VXI plug&play Software for Windows Framework:</p> <ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test and Calibration Software• Software Media and Documentation on CD-ROM <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Ai-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 89430



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section B: BUS TEST INSTRUMENTS		
BI-411-00	4-MODULE EXTENDED BUS TEST INSTRUMENT <ul style="list-style-type: none">• A High-Density VXI C-Size Instrument for Serial Bus Test Emulation• Includes 4 Bus Modules• Supports the Bi-4 Series Basic Bus Set (MIL-STD-1553 A/B, ARINC 429, ARINC 573, RS-232, RS-422, RS-423, RS-485) <p>Each Bi4-Series channel has:</p> <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 112090



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
BI-411-01	<p>4-MODULE EXTENDED BUS TEST INSTRUMENT</p> <ul style="list-style-type: none">• A High-Density VXI C-Size Instrument for Serial Bus Test Emulation• VXI 4.0 Compliant• Includes 4 Bus Modules• Supports the Bi-4 Series Basic Bus Set (MIL-STD-1553 A/B, ARINC 429, ARINC 573, RS-232, RS-422, RS-423, RS-485) <p>Each Bi4-Series channel has:</p> <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software:<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 112090



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
BI-410-00	<p>4 MODULE BUS TEST INSTRUMENT</p> <ul style="list-style-type: none">• A High-Density VXI C-Size Instrument for Serial Bus Test and Emulation includes 4 Bus Modules.• Supports the Bi-4 Series Basic Bus Set (Mil-STD-1533 A/B, ARINC 429, ARINC 573, RS-232, RS-422, RS-423, RS-485) <p>Each Bi4-Series channel has:</p> <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 106730



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
BI-410-01	<p>4 MODULE BUS TEST INSTRUMENT</p> <ul style="list-style-type: none">• A High-Density VXI C-Size Instrument for Serial Bus Test and Emulation includes 4 Bus Modules.• Supports the Bi-4 Series Basic Bus Set (Mil-STD-1533 A/B, ARINC 429, ARINC 573, RS-232, RS-422, RS-423, RS-485)• VXIbus 4.0 compatible covers <p>Each Bi4-Series channel has:</p> <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software:<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification <p>Notes</p> <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 106730



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
BI-410-20	2 MODULE BUS TEST INSTRUMENT <ul style="list-style-type: none">• A High-Density VXI C-Size Instrument for Serial Bus Test and Emulation includes 2 Bus Modules.• Supports the BI-4 Series Basic Bus Set (MIL-STD-1553 A/B, ARINC 429, ARINC 573, RS-232, RS-422, RS-423, RS-485) Each Bi4-Series channel has: <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification Notes <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 68740
BI-420-02	BI4-SERIES 1394B 2 MODULES Each Bi4-Series channel has: <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software:<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification Notes <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
BI-420-04	BI4-SERIES 1394B 4 MODULES Each Bi4-Series channel has: <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software:<ul style="list-style-type: none">• Driver• Soft Front Panel• Function Panel• Self-Test Software Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification Notes <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	Consult Factory
BI-411-73	2-MODULE BUS TEST INSTRUMENT (ARINC573 ONLY) A High-Density VXI C-Size Instrument for Serial Bus Test Emulation <ul style="list-style-type: none">• 2 modules dedicated to support of ARINC-573 Each Bi4-Series channel has: <ul style="list-style-type: none">• Bi-Directional Differential Pin Electronics• VXI plug&play Software• Driver• Soft Front Panel• Function Panel• Self-Test Software Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service• CE Certification Notes <ul style="list-style-type: none">• Includes software license to use Bi-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	\$ 42050
M-996-85	BI-411 MIC AND CAN CIB Cable Interface Board for the Bi-411 that adds capability for the dual-redundant version of the MIC-UBIC bus and the CAN bus protocols. Pass-through capability for 70 ohm shielded twisted pair (MIL-STD-1553) and 50 ohm coax (RS232, 422, 485, ARINC 429). Includes programmable pull-ups/pull-downs and switchable termination.	\$ 20030



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
607-264-00	BI4-SERIES MULTIPLE BUS INTERFACE ADAPTER Cable interface adapter (CIB) for four (4) channel Bi-410 and Bi-411 Bus Test Instruments. This adapter enables fixed cable connections between the Bi-4 Series modules and multiple interface test connectors used for multiple standard serial busses. This CIB eliminates the need for wiring to a switch assembly in order to test the following busses: <ul style="list-style-type: none">• ARINC 429• ARINC 573• TIA/EIA - 232• TIA/EIA - 422• TIA/EIA - 485• MIL-STD-1553• MIL-STD-1773 Note: Customers ordering this item for use in US Navy CASS and CASS compatible test systems must order Teradyne Part Number M-996-55 listed in Price Catalog Section K: CASS Subsystems and Options	\$ 11060
620-311-00	CABLE INTERFACE BOARD TO ITT CANNON CONNECTORS FOR 2-MODULE BI-420-02	Consult Factory
620-311-50	CABLE INTERFACE BOARD TO ITT CANNON CONNECTORS FOR 4-MODULE BI-420-04	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section C: VXI DIGITAL TEST INSTRUMENT & OPTIONS		
DI-050-02	DI-SERIES GENERATION 1 50 MHZ 64-CHANNEL CHANNEL CARD Modular Digital Test Instrument: <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 2.5 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 125 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine NOTES: Hardware Maintenance and Service Support for One Year: <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service VXI Chassis & PC Controller: Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards Requires low-latency connection to controlling PC which requires one of: <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2s Software: <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 DI-SERIES SOFTWARE MEDIA KIT	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-01	<p>DI-SERIES GENERATION 1 50 MHZ 32-CHANNEL CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 2.5 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 125 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-12	<p>DI-SERIES GENERATION 2 50 MHZ 64-CHANNEL CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2s <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 152840



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-11	<p>DI-SERIES GENERATION 2 50 MHZ 32-CHANNEL 30V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 95590



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-22	<p>DI-SERIES GENERATION 2 50 MHZ 64-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 129950



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-21	<p>DI-SERIES GENERATION 2 50 MHZ 32-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 82190



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-30	DI-SERIES GENERATION 1 UTILITY CARD Optional Supplemental DI-Series Support: <ul style="list-style-type: none">• Requires one or more Di-Series Channel Cards• Requires 602-977-00 Di-Series System Software• Includes PS-133-00 Di-Series Diagnostic Software License• Guided Probe Electronics• 32 Utility (High Voltage) Pins• Supplemental Dynamic Control and Timing Signals• Provides full M-918 CRB functionality except Sync Resources and User Clock• Compatible with Di-Series instruments with 2.5ns drive and detect timing resolution (including Di-025-01, Di-025-02, Di-050-01 and Di-050-02) NOTES: <ul style="list-style-type: none">• If Guided Probe capability is required, the Utility Instrument requires one of Di-002-10, Di-002-11 or Di-002-13 Di-Series Guided Probe and Cable Kits.• The Di-050-30 Utility Card should be located in the card cage to the right and adjacent to the associated Di-Series Channel Cards.• Includes PS-133-00 Di-Series Diagnostic Software License and media.	Consult Factory
DI-050-31	DI-SERIES GENERATION 2 UTILITY INSTRUMENT Optional Supplemental DI-Series Support: <ul style="list-style-type: none">• Requires one or more Di-Series Channel Cards• Includes PS-133-00 Di-Series Diagnostic Software License• Guided Probe Electronics• 32 Utility (High Voltage) Pins• Supplemental Dynamic Control and Timing Signals• Provides full M-918 CRB functionality• Compatible with Di-Series instruments with 1 ns drive and detect timing resolution (including Di-025-11, Di-025-12, Di-025-21, Di-025-22, Di-050-11, Di-050-12, Di-050-21 and Di-050-22) NOTES: <ul style="list-style-type: none">• If Guided Probe capability is required, the Utility Instrument requires one of Di-002-10, Di-002-11 or Di-002-13 Di-Series Guided Probe and Cable Kits.• The Di-050-31 Utility Card should be located in the card cage to the right and adjacent to the associated Di-Series Channel Cards.• If physical media is required order 602-977-00 Di-Series Software Media Kit• Includes PS-133-00 Di-Series Diagnostic Software License and media.	\$ 37740



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-02	<p>DI-SERIES GENERATION 1 25 MHZ 64-CHANNEL CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 2.5 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 125 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-01	<p>DI-SERIES GENERATION 1 25 MHZ 32-CHANNEL CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 2.5 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 125 mV on voltage ranges below $\pm 15V$• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-12	<p>DI-SERIES GENERATION 2 25 MHZ 64-CHANNEL 30V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 122320



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-11	<p>DI-SERIES GENERATION 2 25 MHZ 32-CHANNEL 30V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 76440



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-22	<p>DI-SERIES GENERATION 2 25 MHZ 64-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 105080



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-48	<p>DI-SERIES GENERATION 2 25 MHZ 48-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 48 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine• Factory upgradable to full 64-channel capability <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 91520



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-49	<p>DI-SERIES GENERATION 2 25 MHZ 48-CHANNEL 30V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 48 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine• Factory upgradable to full 64-channel capability <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 110970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-48	<p>DI-SERIES GENERATION 2 50 MHZ 48-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 48 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine• Factory upgradable to full 64-channel capability <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 107990



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-49	<p>DI-SERIES GENERATION 2 50 MHZ 48-CHANNEL 30V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 48 bi-directional channels packaged in a single VXI slot.• 50 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 30V$ with up to a 30V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine• Factory upgradable to full 64-channel capability <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 135430



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-21	<p>DI-SERIES GENERATION 2 25 MHZ 32-CHANNEL 15V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 32 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Ranges covering $\pm 15V$ with up to a 20V swing• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% ± 50 mV• Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 64980



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-025-24	<p>DI-SERIES GENERATION 2 25 MHZ 64-CHANNEL -3V TO +6V CHANNEL CARD</p> <p>Modular Digital Test Instrument:</p> <ul style="list-style-type: none">• A high-density VXI C-Size instrument for flexible, high-performance parallel digital test• 64 bi-directional channels packaged in a single VXI slot.• 25 MHz maximum data rate for general-purpose applications• 1 ns timing resolution for drive and detect edges and pattern period• Single range providing drive and detect levels between -3V and +6V• Phases/windows/levels programmable per channel• Drive and detect voltage accuracy of 1% \pm50 mV• Does not support Differential and LVDS capability by pairing of adjacent channels• 8M pattern Deep Serial Memory per channel• Programmable as multiple independent Instruments on 32-channel boundaries• Programmable asynchronous handshake engine• Does not support external analog matrix connections to the channels <p>NOTES:</p> <p>Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit <p>VXI Chassis & PC Controller:</p> <p>Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2	\$ 85560



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-050-63	<p>DI-SERIES GENERATION 2 50 MHZ 32-CHANNEL IFTE(NGATS) CARD</p> <p>Modular Digital Test Instrument: (2) Di-050 modules in a VXI slot each providing:</p> <ul style="list-style-type: none">• 16 full function 50 MHz channels• 8 programmable channels for IFTE control signals• Utility signals for control signals• Factory upgradable to full 64-channels capability <p>NOTES: Hardware Maintenance and Service Support for One Year:</p> <ul style="list-style-type: none">• One Year Warranty on Teradyne Manufactured PC Boards• 90 days Advanced Replacement Service <p>VXI Chassis:& PC Controiller Di-Series hardware requires an integrated high-power VXI chassis such as the Teradyne 600-528-00 (5.7 KW C-Size) which supports up to 12 Di-Series Channel Cards</p> <p>Requires low-latency connection to controlling PC which requires one of:</p> <ul style="list-style-type: none">• Embedded (in chassis) VXI controller PC• Or controller for external PC<ul style="list-style-type: none">• NI MXI-VXI-Express• NI MXI-2 <p>Software:</p> <ul style="list-style-type: none">• Includes software license to use Di-Series System Software on the test system that includes the instrument and on stand alone computers used to for program development at the same site as the instrument.• If physical media is required order 602-977-00 Di-Series Software Media Kit	\$ 103190
615-175-00	<p>DI-SERIES 50 MHZ 64-CHANNEL 15V CHANNEL CARD AND CIB ASSEMBLY</p> <p>Assembly consists of:</p> <ul style="list-style-type: none">• (1) Di-050-22 50 MHz Digital Channel Card• (2) 600-689-51 Cable Interface Boards• VXibus 4.0 compatible enclosing covers <p>Cable interface boards provide access to:</p> <ul style="list-style-type: none">• Di-050-22 test channels• Di-050-22 calibration verification signals• Di-050-22 advanced test capability signals	\$ 133060
615-176-00	<p>DI-SERIES UTILITY INSTRUMENT AND CIB ASSEMBLY</p> <p>Assembly consists of:</p> <ul style="list-style-type: none">• (1) Di-050-31 Utility Instrument• (1) 613-261-50 Cable Interface Board• VXibus 4.0 compatible enclosing covers	\$ 40880



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
668-571-00	M-9 SERIES REPLACEMENT KIT FOR 192 CHANNEL M-917-02 BASED SYSTEM Kit containing the parts to replace an obsolete 192 channel M-917-02 based digital subsystem consisting of : (3) DI-SERIES 25 MHZ 64-CHANNEL CARD w FUNNEL (1) DI-SERIES UTILITY MODULE w FUNNEL (1) DI PROBE AND CABLE (1) Upgrade FPU B Power Supply Module	Consult Factory
626-414-01	DI-SERIES GEN2 25 MHZ 48-CH 15V CHANNEL CARD WITH VPC INTERFACE AND 200V HYBRID RELAY Teradyne 25 MHz 48-Channel Digital Channel Card with -15 volt to +15 volt drive/detect levels, 200V hybrid relay connections, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring.	\$ 107830
638-518-00	DI-SERIES GENERATION 2 50 MHZ 48-CHANNEL 30V CHANNEL CARD (DI-050-49) W/VPC INTERFACE Teradyne 50 MHz 48-Channel Digital Channel Card with -30 volt to +30 volt drive/detect levels, hybrid relay connections, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring.	Consult Factory
638-518-01	DI-SERIES GEN2 50 MHZ 48-CH 30V CHANNEL CARD WITH VPC INTERFACE AND 200V HYBRID FUNNEL Teradyne 50 MHz 48-Channel Digital Channel Card with -30 volt to +30 volt drive/detect levels, 200V hybrid relay connections, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring.	\$ 152310
651-713-00	DI-SERIES GENERATION 2 25 MHZ 48-CHANNEL 30V CHANNEL CARD (DI-025-49) W/VPC INTERFACE Teradyne 25 MHz 48-Channel Digital Channel Card with -30 volt to +30 volt drive/detect levels, hybrid relay connections, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring.	Consult Factory
651-713-01	DI-SERIES GEN2 25 MHZ 48-CH 30V CHANNEL CARD WITH VPC INTERFACE AND 200V HYBRID FUNNEL Teradyne 25 MHz 48-Channel Digital Channel Card with -30 volt to +30 volt drive/detect levels, 200V hybrid relay connections, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring..	\$ 127820
626-417-00	DI-SERIES GENERATION 2 UTILITY INSTRUMENT (DI-050-31) W/VPC INTERFACE Teradyne Utility module Includes PS-133-00 Di-Series Diagnostic Software License, Guided Probe Electronics, 32 Utility (High Voltage) Pins, Supplemental Dynamic Control and Timing Signals, plus VP-90 receiver funnel wiring and self-evaluation fixture wiring.	\$ 45810



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
638-519-00	UPGRADE OF DI-025-49 TO DI-050-49 Upgrade of a Di-025-49 Di-Series 25 MHz 48-Channel Channel Card to the capabilities of a Di-050-49 50 MHz 48-Channel Channel Card. The upgrade increases the available maximum data rate from 25 MHz to 50 MHz while maintaining the +/- 30V voltage range and 30V swing. The Di-025-49 must be returned to Teradyne for upgrading to Di-050-49.	\$ 30590
697-285-00	DI-SERIES GENERATION 2 UTILITY INSTRUMENT (DI-050-31) W/MINI COAX FUNNEL Teradyne Utility module Includes PS-133-00 Di-Series Diagnostic Software License, Guided Probe Electronics, 32 Utility (High Voltage) Pins, Supplemental Dynamic Control and Timing Signals, plus VP-90 receiver mini Coax funnel.	\$ 47400
602-977-00	DI-SERIES SYSTEM SOFTWARE MEDIA KIT Software for on-system support of one or more Di-Series Digital Test Instruments <ul style="list-style-type: none">• iStudio graphical development and debugging environment• Instrument self-test software• Test importers from Teradyne test generation products<ul style="list-style-type: none">• VICTORY Boundary Scan SVF format• LASAR Simulation LSRTAP (IEEE-1445) format• Software Media and Documentation on CD-ROM Multiple Applications Programming Interfaces for instrument control: <ul style="list-style-type: none">• Microsoft .NET Framework interface driver• IVI-C instrument-specific driver• M9-Series VXI-plug&play replacement driver• Teradyne Digital Runtime Environment & L-Series C-shell Applications Programming Interface NOTES: <ul style="list-style-type: none">• The license to use the DI-Series Digital Test Instrument is included with the instrument.• This software may also be used on stand alone computers used in program development at the same site as the instrument	\$ 1330



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
710-084-00	DI-SERIES 336 DIGITAL CHANNEL KIT The 336 digital channel M9-Series to Di-Series 25 MHz, 15V upgrade kit contains combines several catalog items for purchasing convenience consisting of (7) 672-025-58 Di-Series Gen2 25 MHZ 48-Ch 15V Channel Card with VPC Interface and 200V Hybrid Relay (1) 697-285-00 Di-Series Generation 2 Utility Instrument (DI-050-31) w/VPC Interface (1) DI-002-16 DI-SERIES GUIDED PROBE AND CABLE KIT with 48" Ribbon Cable Length (21) 971-644-17 DI-Series to SCPM cable	\$ 804620
710-085-00	DI-SERIES 528 DIGITAL CHANNEL KIT The 528 digital channel M9-Series to Di-Series 25 MHz, 15V upgrade kit contains combines several catalog items for purchasing convenience consisting of (11) 672-025-58 Di-Series Gen2 25 MHZ 48-Ch 15V Channel Card with VPC Interface and 200V Hybrid Relay (1) 697-285-00 Di-Series Generation 2 Utility Instrument (DI-050-31) w/VPC Interface (1) Di-002-16 DI-SERIES GUIDED PROBE AND CABLE KIT with 48" Ribbon Cable Length (33) 971-644-17 DI-Series to SCPM cable	\$ 1235880
672-025-58	DI-SERIES GEN2 25 MHZ 48-CH 15V CHANNEL CARD WITH 200V HYBRID ANALOG FUNNEL Assembly consists of a Di-Series 25MHz 48-Channel 15V Channel card integrated with a Di-Series 48-Channel Coax Funnel with 200V hybrid relays	\$ 106210
672-025-59	DI-SERIES GEN2 25 MHZ 48-CH 30V CHANNEL CARD WITH 200V HYBRID ANALOG FUNNEL Assembly consists of aDi-Series 25MHz 48-Channel 30V Channel card integrated with a Di-Series 48-Channel Coax Funnel with 200V hybrid relays	\$ 125660
672-050-58	DI-SERIES GEN2 50 MHZ 48-CH 15V CHANNEL CARD WITH 200V HYBRID ANALOG FUNNEL Assembly consists of aDi-Series 50MHz 48-Channel 15V Channel card integrated with a Di-Series 48-Channel Coax Funnel with 200V hybrid relays	\$ 122680
672-050-59	DI-SERIES GEN2 50 MHZ 48-CH 30V CHANNEL CARD WITH 200V HYBRID ANALOG FUNNEL Assembly consists of a Di-Series 50MHz 48-Channel 30V Channel card integrated with a Di-Series 48-Channel Coax Funnel with 200V hybrid relays	\$ 150120



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section D : HIGH SPEED SUBSYSTEM & OPTIONS		
611-038-02	<p>HSSUB-1020 HIGH SPEED SUBSYSTEM FOUNDATION WITH EXTERNAL 4U COMPUTER AND GENERATION 2 CHASSIS</p> <p>This Foundation provides the prerequisites for adding Teradyne HSSub instrumentation consisting of one or more Core Instruments, optional I/O Expansion Instruments, and other integrated PXI products. The HSSub-1020 Foundation consists of:</p> <ul style="list-style-type: none">• HSSub controlled by host ATE computer as an LXI instrument, or operated as a standalone, self-contained system• HSSub 18 slot (16 HSSub instrument slots) 3U PXI Express Generation 2 Chassis• 4U External computer containing<ul style="list-style-type: none">o ≥ 2 GHz Intel Xeon server motherboardo 16 GB DDR3 ECC memoryo Window 10 64-bit Operating Systemo (2) 128 GB removable eSATA SSD driveso DVD RWo Rackmount Installation Kit with 20" sliding railo PXI MXI Express Generation 2 controller interface to PXI Express chassiso Ethernet (LXI) connectivity to host ATE computer• HSSub PC-resident TriFlex Integration Software• Teradyne HSSub Test Station Driver for host ATE computer	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
611-038-06	<p>HSSUB-1050 RUGGEDIZED HIGH SPEED SUBSYSTEM ATE-ANCILLARY FOUNDATION</p> <p>This Foundation systems allows for adding Teradyne HSSub instrumentation consisting of Core Instruments, optional I/O Expansion Instruments, and other Teradyne-integrated PXI products. The HSSub-1050 Ruggedized High Sped Subsystem consists of :</p> <ul style="list-style-type: none">• 18-slot 3U PXI Express Generation 2 Chassis• 1U Computer<ul style="list-style-type: none">o >= 2 GHz processoro >= 16 GB memoryo Windows 64-bit Operating Systemo Ethernet connectivity to host ATE computero PXI MXI Express Generation 2 controller interface to PXI Express chassis• Timing Controller Module• HSSub TriFlex Integration Software including communications modules to Alpha/VMS CASS software• Virginia Panel G20 Receiver Frame• Ruggedized container with CASS-compatible mechanical mounting mechanism• Direct Connect Panel" with MIL-38999 connectors for Fibre Channel I/O and additional future critical connections• AC power input monitoring"	Consult Factory
611-038-07	<p>HSSUB-1031 HIGH-SPEED SUBSYSTEM FOUNDATION W/1U PC AND VPC G20</p> <p>This Foundation provides the prerequisites for adding Teradyne HSSub instrumentation consisting of one or more Core Instruments, optional I/O Expansion Instruments, and other integrated PXI products. The HSSub-1031 Foundation consists of HSSub controlled by host ATE computer as an LXI instrument, or operated as a standalone, self-contained system;</p> <ul style="list-style-type: none">• HSSub 18 slot (16 HSSub instrument slots) 3U PXI Express Generation 2 Chassis• 1U External HSSub Windowa Computer• Timing Controller Module• Timing Controller Module Funnel• VPC G20 Receiver with 19" rack mount integration kit• HSSub PC-resident TriFlex Integration Software• Teradyne HSSub Test Station Driver for host ATE computer	Consult Factory
611-038-14	<p>HSSUB-1014 FOUNDATION, NI GEN3, PXIE-1085, PXIE-8880, WIN 10, TM, FOR FUNCTIONAL TEST</p>	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
611-038-15	HSSUB-1015 HIGH-SPEED SUBSYSTEM FOUNDATION (NO EMBEDDED CONTROLLER)	Consult Factory
611-038-08	HSSUN-1032 HIGH SPEED SUBSYSTEM FOUNDATION WITH EXTERNAL 1U COMPUTER AND TERADYNE GENERATION 2 CHASSIS & CONTROLLERS	Consult Factory
611-038-19	HSSUB-1224 HSSUB FOUNDATION WITH P1821 GEN 2 18-SLOT CHASSIS, P821 REMOTE CONTROLLER KIT, 2U EXTERNAL WIN 10 OS COMPUTER, VPC G20 RECEIVER WITH HANDLE AND	\$ 52620
611-038-41	HSSUB-1221 FOUNDATION, P1821, P921, GEN2, WIN 10, TM, FOR FUNCTIONAL TEST	Consult Factory
611-038-42	HSSUB-1231 HIGH SPEED SUBSYSTEM FOUNDATION PXIE GEN3 18-SLOT W/ EMBEDDED WIN10 IOT PC & TIMING MODULE	\$ 52870
611-038-44	HSSUB-1241 STREAMING DATA CAPTURE HSSUB FOUNDATION HSSub Foundation that contains: <ul style="list-style-type: none"> • 691-838-02 ADVANCED SPECTRUM SYSTEM CONTROLLER WINDOWS INDUSTRIAL RACKMOUNT, 2U (x12 Secure Server 2U PC, Windows Pro OS 4TB SSDs) • 660-045-00 P1831 GEN3 PXIe 18-slot Chassis • 660-056-00 P831 GEN3PXIe Remote Controller Kit 	\$ 53920
611-038-49	HSSUB-1126 HSSUB FOUNDATION WITH P0621 GEN2 6-SLOT CHASSIS, P931 WIN 10 OS EMBEDDED CONTROLLER AND RACKMOUNT KIT	\$ 29080
611-038-17	HSSUB-1222 HSUB FOUNDATION KIT WITH 2U WIN10 IOT PC TERADYNE GEN2 CHASSIS AND VPC G20 INTERFACE PLATE The HSSub-1222 Foundation consists of <ul style="list-style-type: none"> • HSSub controlled by host ATE computer as an LXI instrument, or operated as a standalone, self-contained system • 660-057-00 P1821 Teradyne 18 slot (16 HSSub instrument slots) 3U PXI Express Generation 2 Chassis • 660-055-00 P821 PCIe/PXIe Remote Controller Kit with cable • 650-949-40 2U Rackmount Computer with TPM 2.0 chip, Windows 64-bit OS • 618-129-00 HSSub software and documentation • 637-353-00 G20 Interface Plate with integration mechanics 	\$ 46620



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
611-038-96	<p>HSSUB-1220 HIGH SPEED SUBSYSTEM FOUNDATION WITH EXTERNAL 4U COMPUTER AND TERADYNE GENERATION 2 CHASSIS</p> <p>This Foundation provides the prerequisites for adding Teradyne HSSub instrumentation consisting of one or more Core Instruments, optional I/O Expansion Instruments and other integrated PXI products.</p> <p>The HSSub-1220 Foundation consists</p> <ul style="list-style-type: none">• HSSub controlled by host ATE computer as an LXI instrument, or operated as a standalone, self-contained system<ul style="list-style-type: none">o 660-057-00 P1821 Teradyne 18 slot (16 HSSub instrument slots) 3U PXI Express Generation 2 Chassiso 660-055-00 P821 PCIe/PXIe Remote Controller Kit with 5m cableo 616-616-30 4U Rackmount Computer, Windows 64-bit OSo 618-129-00 HSSub software and documentation	\$ 39760
618-807-00	<p>HSSUB LOOPBACK KIT FOR FIBER OPTIC APPLICATIONS</p> <p>Complete cable kit for performing wraparound selftest on Teradyne Fibre Channel Applications that employ two sets of four optical channels and auxiliary Ethernet and eSATA capability. MIL D38999 connectors are used for all interfaces.</p>	Consult Factory
618-807-03	<p>HSSUB-AK DIRECT CONNECT PANEL WRAP PLUGS</p> <ul style="list-style-type: none">• Provides wraparound self-test interconnections for the MIL-DTL-38999 connectors on the Direct Connect Panel of the HSSub-AK• Supported connectors:<ul style="list-style-type: none">• (2) Four-Channel optical connectors with Multi-Gigabit Serial channels• (1) Two-Channel optical Ethernet connector• (2) One-Channel Ethernet ports	Consult Factory
618-807-06	<p>HSSUB-AK I2 AND DIRECT CONNECT WRAP PLUGS</p> <p>Provides wraparound self-test interconnections for the MIL-DTL-38999 connectors on the Direct Connect Panel of the HSSub-AK:</p> <ul style="list-style-type: none">(2) Four-Channel optical connectors with Multi-Gigabit Serial channels(1) Two-Channel optical Ethernet connector(2) One-Channel Ethernet ports <p>Provides wraparound self-test interconnections employing Virginia Panel i2 plugs for each HSSub-AK instrument:</p> <ul style="list-style-type: none">(2) Serial Core Instruments(1) LVTTTL IO Expansion Instrument(1) Timing Module(1) RS232/IRIG-B/Ethernet Flexible IO Expansion Instrument(1) RS485/HOTLink/ECL Flexible IO Expansion Instrument	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
618-673-01	HSS POWER CABLE AC power cable that connects HSSub-AK to CASS, RTCASS or eCASS station power	Consult Factory
618-674-02	HSS TO CASS ETHERNET COMMUNICATION CABLE Ethernet cable that allows HSSub-AK to communicate with CASS station.	Consult Factory
651-183-00	HSS RTCASS ETHERNET COMMUNICATION ADAPTER CABLE Ethernet cable that allows HSSub-AK to communicate with RTCASS station	Consult Factory
660-367-00	HSS ECASS ETHERNET COMMUNICATION ADAPTER CABLE Ethernet cable that allows HSSub-AK to communicate with eCASS station	Consult Factory
618-679-00	EXTERNAL SSD WITH DRIVE CARRIER FOR HSSUB 1U PC	Consult Factory
616-616-40	RACKMOUNT SPECTRUM WINDOWS 10 IOT ENTERPRISE LTSC WITH TPM COMPUTER (4U), X10 MOTHERBOARD	\$ 13200
622-573-30	HSSUB – EXTERNAL 1U WIN10 IOT ENT OS 64-BIT COMPUTER 1U External computer contains: <ul style="list-style-type: none"> • >=2 GHz Intel Xeon server motherboard with TPM2.0 chip • Windows 64-bit Operating System • 16 GB DDR3 ECC memory • 500 GB (minimum) removable eSATA SSD drive • Spare 500 GB (minimum) removable eSATA SSD drive • Blue Ray DVD RW • Rackmount Installation Kit with 20" sliding rail 	Consult Factory
650-949-40	RACKMOUNT SPECTRUM WINDOWS 10 IOT ENTERPRISE LTSC WITH TPM2.0 CHIP COMPUTER (2U), X10 MOTHERBOARD	\$ 13200
666-779-00	WIN10 OS 4U SYSTEM CONTROLLER KIT Win10 4U System Controller, NI PXIe Remote Controllers and Software Pre-load Kit This kit consists of: <ul style="list-style-type: none"> • 616-616-30 Spectrum 4U Windows System Controller • 605-197-46 PCIe-8381 MXI Express PCIe Controller for computer • 605-197-45 PXIe-8381 MXI Express Controller for PXI Chassis • 615-215-02 1 meter Cable for MXI Express Controllers • 618-129-00 HSSub TriFlex Software & Doc Kit • 663-770-00 VERTA Software • 654-577-03 TIOS Project Software, v1.4 	\$ 24020



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
666-779-10	WIN10 IOT ENTERPRISE 4U SYSTEM CONTROLLER, NI PXIE REMOTE CONTROLLER KIT AND TIOS SOFTWARE PRE-LOAD KIT	\$ 25660
626-851-00	PXI EXPRESS GEN 2 16-SLOT CHASSIS KIT The PXI Express Gen 2x8 16-Slot Chassis Kit includes: <ul style="list-style-type: none">* 18 hybrid slots (16 instrument slots)* US power cable* (3) slot blockers* Filler panels* Front-mounting kit	Consult Factory
626-851-01	ELEC-MECH, PXIE-1085 CHASSIS KIT WITHOUT RACK MOUNT, FOR FUNCTIONAL TEST	\$ Consult Factory
667-809-00	NI PXIE-1085 GEN 3 16-SLOT CHASSIS KIT This PXI Express Gen 3x8 18-Slot Chassis Kit includes: <ul style="list-style-type: none">* 16 hybrid instrument slots (16 instrument slots)* US power cable* Slot blockers* Filler panels* Front rack-mounting kit	\$ 56630
667-809-01	NI PXIE-1085 GEN 3 16-SLOT CHASSIS KIT WITHOUT RACK MOUNT This PXI Express Gen 3x8 18-Slot Chassis Kit includes: <ul style="list-style-type: none">* 16 hybrid instrument slots (16 instrument slots)* US power cable* Slot blockers* Filler panels	\$ 58590
605-197-45	MXI EXPRESS CONTROLLER FOR PXI CHASSIS <ul style="list-style-type: none">• PCIe Gen2x8 connectivity	\$ 7530
605-197-46	MXI EXPRESS PCIE CONTROLLER FOR COMPUTER <ul style="list-style-type: none">• PCIe Gen2x8 connectivity	\$ 6880
630-681-01	ELEC-MECH, PXIE-6672 W/G20 EMI, FOR FUNCTIONAL TEST	\$ 16190
630-681-02	PXIE-6672 TIMING MODULE WITH CLOCK IO & G20 EMI FUNNEL	\$ 16270



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
661-648-00	TIMING AND SYNCHRONIZATION MODULE WITH TCXO 780063-01 W/17025 CAL 960457-04	\$ 12410
622-572-00	TIMING MODULE FUNNEL ADAPTER (PLASTIC)	\$ 3330
622-572-03	WIRE VERIFICATION TEST MATERIAL AND INTEGRATION OF THE WIRE VERIFICATION TEST FOR THE 361-778-06 TIMING AND SYNCHRONIZATION CONTROLLER This item contains the self evaluation fixture wiring, and integration of wire verification selftest. NOTE: This item is only available when configured in a new HSSub, or Spectrum HS system containing the 361-778-06 Timing and Synchronization Controller and 622-572-00 Timing Module Funnel.	\$ 1630
660-865-00	WRAP BLOCK FOR TIMING MODULE - MX Includes material, build, design, and documentation for the PXI timing module	\$ 1610
615-215-02	1 METER CABLE FOR MXI EXPRESS CONTROLLERS	\$ 880
356-136-02	X1 MXI-EXPRESS CABLE, 3M	\$ 550
638-048-00	MXI-EXPRESS CABLE, GEN 2 X8, COPPER, 5M LENGTH WITH G20 FUNNEL ASSEMBLY	\$ 1670
660-677-03	X1 MXI-EXPRESS CABLE, 3M	Consult Factory
660-051-00	TERADYNE P0621 PXIE CHASSIS – 6 SLOT, GEN 2, 5 HYBRID SLOTS, WITH RACKMOUNT KIT	\$ 14180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
660-055-00	TERADYNE P821 REMOTE PCIE- PXIE GEN 2 CONTROLLER KIT, 5M CABLE	\$ 7770
660-056-00	TERADYNE P831 REMOTE CONTROLLER PCI EXPRESS GEN 3 KIT WITH 2M CABLE	\$ 9080
703-544-01	TERADYNE P1831 PXIE CHASSIS - 18 SLOT, GEN 3, 6 HYBRID SLOTS WITH SLOT BLOCKERS, RACKMOUNT KIT	\$ 31180
660-939-00	TERADYNE P931 PC - EMBEDDED PCI EXPRESS GEN 3 CONTROLLER, 240GB SSD, WIN10 IOT ENTERPRISE OS	\$ 21880
660-939-01	TERADYNE P931 PC - EMBEDDED PCI EXPRESS GEN 3 CONTROLLER, 240GB SSD, WIN10 PRO OS	\$ 21880
660-112-10	HSSUB AUGMENTATION KIT – CONFIGURATION B HSSub Augmentation Kit consisting of <ul style="list-style-type: none">• 667-809-00 NI PXIe-1085 PXIe Chassis• 637-353-01 VPC Single Tier G20 PXI Receiver with interlock and handle• 605-197-46 NI PCle-8381, x8 Gen 2 MXI-Express for Computer• 605-197-45 NI PXIe-8381, x8 Gen 2 MXI-Express for PXI Chassis• 638-048-00 MXI-Express Cable, Gen 2 x8, Copper, 5m• 630-681-02 PXIe-6672 w/ G20 EMI Funnel• 638-681-91 HSSub-9100 RS485 64-CH FIOXI w/ G20 EMI Funnel, 2-CH 50MHz RS485 Clock IO• 622-295-96 HSSub-9030 RS485/HOTLink/ECL FIOXI w/ G20 EMI Funnel, 1-CH 50MHz RS485 Clock IO, 1-CH 50MHz ECL Clock IO• 656-290-91 HSSub-9110 RS232/HOTLink/ECL FIOXI w/ G20 EMI Funnel, 1-CH 50MHz ECL Clock IO• 609-494-90 HSSub-5020 RT Processor Module w/ G20 EMI Funnel• 618-129-00 HSSub Software and Doc	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
660-112-20	HSSUB AUGMENTATION KIT – CONFIGURATION C HSSub Augmentation Kit consisting of <ul style="list-style-type: none">• 667-809-00 NI PXIe-1085 PXIe Chassis• 637-353-01 VPC Single Tier G20 PXI Receiver with interlock and handle• 605-197-46 NI PCIe-8381, x8 Gen 2 MXI-Express for Computer• 605-197-45 NI PXIe-8381, x8 Gen 2 MXI-Express for PXI Chassis• 638-048-00 MXI-Express Cable, Gen 2 x8, Copper, 5m• 630-681-02 PXIe-6672 w/ G20 EMI Funnel• 638-681-91 HSSub-9100 RS485 64-CH FIOXI w/ G20 EMI Funnel, 2-CH 50MHz RS485 Clock IO• 622-295-96 HSSub-9030 RS485/HOTLink/ECL FIOXI w/ G20 EMI Funnel, 1-CH 50MHz RS485 Clock IO, 1-CH 50MHz ECL Clock IO• 656-290-91 HSSub-9110 RS232/HOTLink/ECL FIOXI w/ G20 EMI Funnel, 1-CH 50MHz ECL Clock IO• 618-129-00 HSSub Software and Doc	\$ 249010
660-112-03	HSSUB LOOPBACK KIT Self-test Loopback Kit for HSSub Augmentation Kit (660-112-00 or 660-112-10) This kit consists of: <ul style="list-style-type: none">• 622-463-13 WVT Module for HSSub RS485 FIOXI (Qty 3)• 622-462-13 WVT Module for HSSub RS232/IRIG-B FIOXI (Qty 1)• 622-464-13 WVT Module for HSSub HOTLink/ECL FIOXI (Qty 2)• 357-603-65 WVT Module for Timing Module (Qty 1)• 662-280-00 Carry Case for Loopback Kit (7 module)	\$ 21200
675-477-00	PASSIVE QSFP TO SFP+ (X4) CABLE ASSEMBLY	\$ 1000
678-354-00	AB17 HSSUB-9100 VP90 QUADRAPADDLE CABLE ASSEMBLY KIT	\$ 12680
679-073-80	HSSUB-6140 8G HYBRID CIB FOR MGT AND LVDS CABLE CONNECTIONS TO OPTICAL IOXI MODULE	\$ 9280
679-074-00	8G HYBRID TO HSSUB-6065 OPTICAL IO INSTRUMENT INTERCONNECT CABLE	\$ 3690
692-154-80	IRIG-B 3-CH CIB FOR 8G HYBRID IOXI Multi-channel IRIG-B cable interface board with mounting hardware for the 8G Hybrid IO Expansion Instrument. Has 3 input channels for amplitude modulated IRIG-B signal I/O.	\$ 8910



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
700-649-03	HSSUB-6140 8G HYBRID IRIG-B G20 ITA LOOPBACK ADAPTER VPC ITA connector wired for Wire Verification Test of HSSub-6140 8G Hybrid IRIG-B Instrument w/Funnel (664-840-92) with G20 ICA connectors. One module is required per instrument.	\$ 1860
700-649-13	HSSUB-6140 8G HYBRID IRIG-B G20 I2 LOOPBACK ADAPTER VPC ITA connector wired for Wire Verification Test of HSSub-6140 8G Hybrid IRIG-B Instrument w/Funnel (664-840-92) with i2 MX ICA connectors. One module is required per instrument..	\$ 2710
701-480-00	HSSUB-6140 8G HYBRID CDI ITA I2 QSFP CONVERTER MODULE	\$ 6490
614-380-80	HSSUB-7010 REMOTE TESTHEAD CONTROLLER FOR FOUNDATION 2-slot PXI Express card that plugs into the HSSub Foundation chassis to control one HSSub-7050 remote IO chassis. Provides both data connection and test sync signals. Includes three meter optical connection cable.	Consult Factory
614-381-80	HSSUB-7050 REMOTE TESTHEAD CHASSIS KIT 4-slot remote chassis that accepts up to four HSSub IO Expansion instruments. Requires HSSub-7010 Remote IO Controller located in the HSSub Foundation chassis.	\$ 31450
614-381-81	HSSUB-7050 REMOTE TESTHEAD CHASSIS KIT WITH COOLING FAN KIT 4-slot remote chassis that accepts up to four HSSub IO Expansion instruments. Requires HSSub-7010 Remote IO Controller located in the HSSub Foundation chassis.	\$ 33180
636-604-00	QSFP TO QSFP 40G CABLE, 5 METER FOR RTH CONTROL CABLE	\$ 1240
660-149-07	CABLE, RTH CONTROL W/ GEN2 OPTICAL I/O FOR TESTER, 7M LENGTH	\$ 25880
660-150-00	RTH CONTROL W/GEN2 OPTICAL I/O CABLE FOR AUTOMATION TRAY (EXPANDED BEAM TO MTP)	\$ 16950
660-759-00	RTH CONTROL CABLE FOR TESTER (QSFP TO LC)	\$ 1010
660-760-00	GEN2 OPTICAL I/O CABLE FOR TESTER (QTY. 4 LC TO LC)	\$ 700
660-761-00	RTH CONTROL CABLE FOR AUTOMATION TRAY (QSFP TO MTP)	\$ 1010
356-136-06	MXI-EXPRESS/EXPRESSCARD MXI CABLE, 7M	\$ 1100
664-836-00	HSSUB SLIMRTH 2-slot remote chassis that accepts up to two HSSub IO Expansion instruments. Requires HSSub-7010 Remote IO Controller located in the HSSub Foundation chassis.	\$ 28050
664-841-00	PM TO 8G HYBRID IO INSTRUMENT CABLE ASSEMBLY	\$ 31970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
668-055-00	SLIMRTH PM KIT HSSub Augmentation Kit consisting of: <ul style="list-style-type: none">• 664-836-00 HSSub-7055 SlimRTH Chassis Kit• (2) 664-840-80 8G Hybrid IO Instrument• (2) 664-841-00 PM to 8G Hybrid IO Instrument Cable Assembly	\$ 149390
609-494-80	HSSUB-5020 RT PROCESSOR MODULE The HSSub-5020 RT Processor Module consists of the following: <ul style="list-style-type: none">• 1-slot wide 3U PXI Express module• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS	Consult Factory
609-494-81	HSSUB-5025 RT PROCESSOR MODULE CE MARKED The HSSub-5025 RT Processor Module consists of the following: <ul style="list-style-type: none">• CE Cerrified 1-slot wide 3U PXI Express module• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS	Consult Factory
605-197-25	VXI-8360T, VXI-MXI-EXPRESS TRIGGER BOARD	\$ 37570
609-494-90	HSSUB-5020 RT PROCESSOR MODULE WITH FUNNEL HSSub-5020 RT Processor Module with Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors	Consult Factory
611-039-00	HSSUB-5010 LVDS CORE INSTRUMENT The HSSub-5010 LVDS Core Instrument consists of the following: <ul style="list-style-type: none">• 2-slot wide 3U PXI Express Runtime Defined Instrument• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS• Reprogrammable Xilinx Virtex-6 Test-Defined FPGA for direct I/O and for general purpose test processing• Real-time processor and Test-Defined FPGA are programmable by the end-user if required• May provide direct I/O to the UUT• 64 data pair LVDS direct I/O support<ul style="list-style-type: none">o Up to 400 Mbps per pair (SDR) or 800 Mbps (DDR)o Organized as four data ports of:<ul style="list-style-type: none">• 16 data pairs (input or output)• One clock pair per port• One utility pair per port	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
611-039-90	<p>HSSUB-5010 LVDS CORE INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>This instrument is a two-slot, fully integrated and tested assembly that includes:</p> <ul style="list-style-type: none">• One 611-039-00 HSSub-5010 LVDS Core Instrument• Virginia Panel G20 Funnel <p>The HSSub-5010 LVDS Core Instrument consists of the following:</p> <ul style="list-style-type: none">• 2-slot wide 3U PXI Express Runtime Defined Instrument• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS• Reprogrammable Xilinx Virtex-6 Test-Defined FPGA for direct I/O and for general purpose test processing• Real-time processor and Test-Defined FPGA are programmable by the end-user if required• May provide direct I/O to the UUT• 64 data pair LVDS direct I/O support<ul style="list-style-type: none">o Up to 400 Mbps per pair (SDR) or 800 Mbps (DDR)o Organized as four data ports of:<ul style="list-style-type: none">• 16 data pairs (input or output)• One clock pair per port• One utility pair per port	Consult Factory
611-039-95	<p>HSSUB-5010 LVDS CORE INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>The HSSub-5010 LVDS Core Instrument with funnel is a two-slot, fully integrated and tested assembly that provides LVDS parallel I/O and consists of the following:</p> <ul style="list-style-type: none">• One 611-039-00 HSSub-5010 LVDS Core Instrument• "One Virginia Panel G20 Funnel with two receiver modules supporting full ITAs and i2 MX ITA connectors	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
613-892-00	<p>HSSUB-5050 SERIAL CORE INSTRUMENT</p> <p>The HSSub-5050 Serial Core Instrument is typically used to test standardized high-speed serial buses and consists of the following:</p> <ul style="list-style-type: none">• 2-slot wide 3U PXI Express Runtime Defined Instrument• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS• Reprogrammable Xilinx Virtex-6 Test-Defined FPGA for direct I/O and for general purpose test processing• Real-time processor and Test-Defined FPGA are programmable by the end-user if required• May provide direct I/O to the UUT• Provides 16 Multi-Gigabit Transceivers (MGT)<ul style="list-style-type: none">o Four groups of four transceiverso Each transceiver includes a receive pair and a transmit pairo Eight transceivers with AC coupling capacitors on all transmit pairs as required for PCI Expresso Eight transceivers with AC coupling capacitors on all receive pairs as required by most buses other than PCI Expresso Each group includes a receive clock and a transmit clocko Supports up to 3.125 Gbps per pair• Provides four LVDS I/O pairs with one clock pair (input or output)	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
613-892-90	<p>HSSUB-5050 SERIAL CORE INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>This instrument is a two-slot, fully integrated and tested 2-slot wide assembly that includes:</p> <ul style="list-style-type: none">• One 613-892-00 HSSub-5050 Serial Core Instrument• One Virginia Panel G20 Funnel with two receiver modules <p>The HSSub-5050 Serial Core Instrument is typically used to test standardized high-speed serial buses and consists of the following:</p> <ul style="list-style-type: none">• 2-slot wide 3U PXI Express Runtime Defined Instrument• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS• Reprogrammable Xilinx Virtex-6 Test-Defined FPGA for direct I/O and for general purpose test processing• Real-time processor and Test-Defined FPGA are programmable by the end-user if required• May provide direct I/O to the UUT <p>Funnel provides access to 12 Multi-Gigabit Transceiver Channels (MGT)</p> <ul style="list-style-type: none">• Each transceiver includes a receive pair and a transmit pair• Supports up to 3.125 Gbps per pair• Four transceiver channels accessible via a connector on top of the funnel for connection to an Optical IO Expansion Instrument• Eight channels in two groups of four channels for wired access via Virginia Panel receiver modules<ul style="list-style-type: none">• Four transceivers with AC coupling capacitors on all transmit pairs as required for PCI Express• Four transceivers with AC coupling capacitors on all receive pairs as required by most buses other than PCI Express• Each group includes a receive clock and a transmit clock• Multi-Gigabit Transceivers accessed on the right-side Virginia Panel Quadrax connector module• Provides four LVDS I/O pairs with one clock pair (input or output)• Provides signals required to connect to 611-181-80 Debug Board on the left-side Virginia Panel	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
613-892-95	<p>HSSUB-5050 SERIAL CORE INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>This instrument is a two-slot, fully integrated and tested 2-slot wide assembly that includes:</p> <ul style="list-style-type: none">• One 613-892-00 HSSub-5050 Serial Core Instrument• One Virginia Panel G20 Funnel with two receiver modules supporting full ITAs and i2 MX ITA connectors <p>The HSSub-5050 Serial Core Instrument is typically used to test standardized high-speed serial buses and consists of the following:</p> <ul style="list-style-type: none">• 2-slot wide 3U PXI Express Runtime Defined Instrument• Four-core Power Architecture real-time processor with Wind River VxWorks RTOS• Reprogrammable Xilinx Virtex-6 Test-Defined FPGA for direct I/O and for general purpose test processing• Real-time processor and Test-Defined FPGA are programmable by the end-user if required• May provide direct I/O to the UUT <p>Funnel provides access to 12 Multi-Gigabit Transceiver Channels (MGT)</p> <ul style="list-style-type: none">• Each transceiver includes a receive pair and a transmit pair• Supports up to 3.125 Gbps per pair• Four optical transceiver channels accessible via provided SFP pluggable module at the top of the Virginia Panel funnel• Eight channels in two groups of four channels for wired access via Virginia Panel receiver modules<ul style="list-style-type: none">• Four transceivers with AC coupling capacitors on all transmit pairs as required for PCI Express• Four transceivers with AC coupling capacitors on all receive pairs as required by most buses other than PCI Express• Each group includes a receive clock and a transmit clock• Multi-Gigabit Transceivers accessed on the right-side Virginia Panel VTAC connector module• Provides four LVDS I/O pairs with one clock pair (input or output)• Provides signals required to connect to 611-181-80 Debug Board on the left-side Virginia Panel	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
618-142-80	HSSUB-6065 4-CHANNEL OPTICAL IO EXPANSION INSTRUMENT The HSub-6065 Optical IO Expansion Instrument accepts wired serial (MGT) I/O channels from an HSSub Serial Instrument and connects them to SFP (Small Form Factor Pluggable) connectors. These connectors accept standard optical or copper transceiver/cable assembly that is typically routed to the unit under test or an intermediate connector. All of the Optical IO Expansion Instrument connectors are accessible from the front panel of the instrument. <ul style="list-style-type: none">• Connectors for four channels (transmit and receive pairs) from a HSSub serial instrument such as the Serial Core Instrument• Four SFP sockets that can accommodate optical, passive copper, or active copper transceiver modules	\$ 4300
618-142-70	4-CHANNEL OPTICAL IO EXPANSION INSTRUMENT AND CABLE ASSEMBLY This Optical IO Expansion Instrument provides: <ul style="list-style-type: none">• One 618-142-80 4-Channel IO Expansion Instrument for mounting behind Direct Connect Panel in 611-038-05 Foundation• Cable assembly that connects instrument to Serial Core Instrument and to the Direct Connect Panel Note: <ul style="list-style-type: none">• Instrument does not use a PXI chassis slot	Consult Factory
618-142-95	HSSUB-6065 2 PORT OPTICAL ETHERNET IO EXPANSION INSTRUMENT WITH G20 FUNNEL	\$ 12640
620-911-00	SERIAL CORE INSTRUMENT TO 4-CHANNEL OPTICAL IO EXPANSION INSTRUMENT CABLE	Consult Factory
612-122-80	HSSUB-6020 LVTTTL IO EXPANSION INSTRUMENT The HSSub-6020 LVTTTL IO Expansion Instrument consists of the following: <ul style="list-style-type: none">• 1-slot PXI Express instrument• Physical I/O and low-level protocol controlled by reprogrammable FPGA• 96 bidirectional LVTTTL channels (configurable as 44 LVDS pairs) Not to be used for new sales opportunities.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
612-122-90	<p>HSSUB-6020 LVTTL IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This instrument is a one-slot, fully integrated and tested assembly that includes:</p> <ul style="list-style-type: none">• One 612-122-80 HSSub-6020 LVTTL IO Expansion Instrument• Virginia Panel G20 Funnel <p>The HSSub-6020 LVTTL IO Expansion Instrument consists of the following:</p> <ul style="list-style-type: none">• 1-slot PXI Express instrument• Physical I/O and low-level protocol controlled by reprogrammable FPGA• 96 bidirectional LVTTL channels (configurable as 44 LVDS pairs) <p>Not to be used for new sales opportunities</p>	Consult Factory
630-666-90	<p>EDIGITAL-6020A EDIGITAL LVTTL INSTRUMENT AND FUNNEL</p> <p>This instrument is a one-slot, fully integrated and tested assembly that includes:</p> <ul style="list-style-type: none">• 1-slot PXI Express Gen 1 x4 instrument• Controlled by HSSub TriFlex software• Compatible with HSSub-6020 LVTTL IO Expansion Instrument• Signal interface and low-level protocol controlled by Test Defined FPGA• Xilinx XC5VLX155T Virtex 5 Test Defined FPGA with 0.5 GB DDR2 memory• 68 bidirectional LVTTL channels (configurable as 34 LVDS pairs)• All LVTTL channels are TTL tolerant• Conventional (non real-time) control from Windows PC• Funnel (non-removable) with Virginia Panel QuadraPaddle receiver module supporting full ITAs and i2 MX ITA connectors<ul style="list-style-type: none">o Compatible with Virginia Panel i2 cable connectionso Compatible with Virginia Panel G20 ITA approach	\$ 17850



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
673-828-90	EDIGITAL-6025A EDIGITAL LVTTTL INSTRUMENT AND FUNNEL CE MARKED This instrument is a one-slot, fully integrated and tested assembly that includes: <ul style="list-style-type: none">• CE Certified• 1-slot PXI Express Gen 1 x4 instrument• Controlled by HSSub TriFlex software• Compatible with HSSub-6020 LVTTTL IO Expansion Instrument• Signal interface and low-level protocol controlled by Test Defined FPGA• Xilinx XC5VLX155T Virtex 5 Test Defined FPGA with 0.5 GB DDR2 memory• 68 bidirectional LVTTTL channels (configurable as 34 LVDS pairs)• All LVTTTL channels are TTL tolerant• Conventional (non real-time) control from Windows PC• Funnel (non-removable) with Virginia Panel QuadraPaddle receiver module supporting full ITAs and i2 MX ITA connectors<ul style="list-style-type: none">o Compatible with Virginia Panel i2 cable connectionso Compatible with Virginia Panel G20 ITA approach	\$ 17850
662-077-80	HSSUB-6025 GEN 2 LVTTTL IO EXPANSION INSTRUMENT This instrument is a one-slot, fully integrated and tested assembly that includes <ul style="list-style-type: none">• CE certified:• 1-slot PXI Express instrument• Physical I/O and low-level protocol controlled by re-programmable FPGA• 96 bidirectional LVTTTL channels (configurable as 44 LVDS pairs)	\$ 12410
662-077-90	HSSUB-6025 GEN 2 LVTTTL IO EXPANSION INSTRUMENT WITH FUNNEL This instrument is a one-slot, fully integrated and tested assembly that includes: <ul style="list-style-type: none">• One 662-077-80 HSSub-6025 Gen 2 LVTTTL IO Expansion Instrument• Virginia Panel G20 Funnel with pinout identical to the obsolete HSSub-6060 IO Expansion Instrument with VPC G20 Funnel	\$ 20070



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
662-077-81	HSSUB-6026 LVTTTL2-XT IO EXPANSION INSTRUMENT This instrument is a one-slot, fully integrated and tested assembly that includes: <ul style="list-style-type: none">• 1-slot PXI Express instrument• Physical I/O and low-level protocol controlled by reprogrammable FPGA• Extended temperature of operation from -25C to 70C• 96 bidirectional LVTTTL channels (configurable as 48 LVDS pairs)	\$ 15070
685-624-80	EDIGITAL-6030 EDIGITAL 50 MHZ 32 CHANNEL DIGITAL IO INSTRUMENT The eDigital-6030 instrument provides parallel digital testing with the following: <ul style="list-style-type: none">*CE certified*1-slot PXI Express instrument*32 Single-ended channels*Voltage ranges -2V to +6V*Phases/windows/levels programmable per channel*Large channel count contact-free asynchronous communication technology (CFAST)*Data rate 50Mb/s (20 ns period)*Per Pin PMU*Test Defined FPGA for reconfigurability*Controlled by HSSub TriFlex Software*eDTE Test Editor for user-friendly GUI API for test generation, execution and troubleshoot	\$ 33040
685-624-90	EDIGITAL-6030 EDIGITAL 50 MHZ 32 CHANNEL DIGITAL IO INSTRUMENT WITH PASS THROUGH FUNNEL eDigital-6030 Instrument with funnel assembly for system integration	\$ 38930
614-383-80	HSSUB-6040 HYBRID IO EXPANSION INSTRUMENT The HSSub-6040 Hybrid IO Expansion Instrument provides a combination of parallel and serial I/O and consists of the following: <ul style="list-style-type: none">• Physical I/O and low-level protocol controlled by reprogrammable FPGA• 8 Multi-Gigabit Transceivers for high-speed serial I/O at up to 2.5 Gbps• One 18-pair LVDS port with data rates up to 400 Mbps Not to be used for new sales opportunities.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
614-383-90	HSSUB-6040 HYBRID IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY The HSSub-6040 Hybrid IO Expansion Instrument with funnel provides a combination of parallel and serial I/O and consists of the following: <ul style="list-style-type: none">• Physical I/O and low-level protocol controlled by reprogrammable FPGA• 8 Multi-Gigabit Transceivers for high-speed serial I/O at up to 2.5 Gbps• One 18-pair LVDS port with data rates up to 400 Mbps• Funnel (non-removable) with Virginia Panel VTAC receiver module supporting full ITAs and i2 MX ITA Not to be used for new sales opportunities.	Consult Factory
623-485-80	HSSUB-6090 1-SLOT ETHERNET IO EXPANSION INSTRUMENT <ul style="list-style-type: none">• Eight 10BASE-T/100BASE-T/1000BASE-T wired Ethernet ports• Two wired ports for optional connection to an Optical IO Expansion Instrument to produce 1000BASE-SX Optical Gigabit Ethernet• Maximum concurrently operating ports:<ul style="list-style-type: none">o Two Optical and six wired portso Eight wired and no Optical ports• Controllable by network stack on any HSSub Windows PC	\$ 12780
623-485-90	HSSUB-6090 1-SLOT ETHERNET IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY <ul style="list-style-type: none">• Eight 10BASE-T/100BASE-T/1000BASE-T wired Ethernet ports• Controllable by network stack on any HSSub Windows PC• Virginia Panel G20 funnel with QuadraPaddle receiver connector	\$ 21000
635-352-80	HSSUB-6091 10G ETHERNET IO EXPANSION INSTRUMENT <ul style="list-style-type: none">• 1-slot PXI Express Gen 3 x8 instrument• Up to four concurrent Ethernet ports accessed by four SFP+ transceivers• Each port may be configured by transceiver selection for:<ul style="list-style-type: none">• 10 GbE Optical 10GBASE-SR, 10GBASE-SW• 1 GbE Optical 1000BASE-SX\• Instrument is provisioned with four SFP+ transceivers• Controlled by standard Windows network stack on HSSub PC	\$ 15580



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
635-352-81	HSSUB-6091 10G ETHERNET IO EXPANSION INSTRUMENT NO SFPS <ul style="list-style-type: none">• 1-slot PXI Express Gen 3 x8 instrument• Up to four concurrent Ethernet ports accessed by four SFP+ transceivers• Each port may be configured by transceiver selection for:<ul style="list-style-type: none">• 10 GbE Optical 10GBASE-SR, 10GBASE-SW• Controlled by standard Windows network stack on HSSub PC Note : SFPs are not included	\$ 14200
635-352-90	HSSUB-6091 10G ETHERNET IO EXPANSION INSTRUMENT WITH FUNNEL <p>HSSub-6091 10G Ethernet instrument with Funnel assembly for Virginia Panel G20 receiver with one 16-position Mini-fiber receiver modules supporting full ITAs and i2 MX ITA connectors</p>	\$ 22790
635-352-91	HSSUB-6091 10G ETHERNET IO EXPANSION INSTRUMENT WITH VTAC FUNNEL <p>HSSub-6091 10G Ethernet instrument with Funnel assembly for Virginia Panel G20 receiver with VTAC high frequency cabled receiver module supporting full ITAs and i2 MX ITA connectors</p>	\$ 20920
634-540-80	HSSUB-6100 12G SERIAL IO EXPANSION INSTRUMENT <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• CE certified• 1-slot PXI Express Gen 3 x8 instrument• Instrument is configured at runtime by means of a Teradyne or user-generated HSSub App• Low-level protocol is implemented in HSSub App-accessible Xilinx Ultrascale Test Defined FPGA• 2 GB of DDR3 memory directly accessible by Test Defined FPGA• Four Xilinx GTX transceivers service four SFP+ transceiver cages• Four Xilinx GTX transceivers service one 4-port QSFP+ transceiver cage• Instrument is provisioned with four SFP+ optical transceivers capable of supporting multiple protocols at rates of 1 - 10 Gbps Note : Depends on HSSub custom BIOS	\$ 23370



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
634-540-81	HSub-6100 12G SERIAL IO EXPANSION INSTRUMENT, SFPS NOT INCLUDED This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• CE certified• 1-slot PXI Express Gen 3 x8 instrument• Instrument is configured at runtime by means of a Teradyne or user-generated HSSub App• Low-level protocol is implemented in HSSub App-accessible Xilinx Ultrascale Test Defined FPGA• 2 GB of DDR3 memory directly accessible by Test Defined FPGA• Four Xilinx GTX transceivers service four SFP+ transceiver cages• Four Xilinx GTX transceivers service one 4-port QSFP+ transceiver cage Note : Depends on HSSub custom BIOS	\$ 21740
634-540-82	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT This IO Expansion Instrument provides: Same features as the 634-540-80 Not dependent on custom BIOS on HSSub controller	\$ 23370
634-540-83	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT, SFPS NOT INCLUDED This IO Expansion Instrument provides: Same features as the 634-540-81 Not dependent on custom BIOS on HSSub controller	\$ 21740
634-540-90	HSSUB-6100 12G SERIAL IO EXPANSION INSTRUMENT WITH FUNNEL HSSub-6100 12G Serial instrument with Funnel assembly for Virginia Panel G20 receiver with one 16-position Mini-fiber receiver modules supporting full ITAs and i2 MX ITA connectors Note : Depends on HSSub custom BIOS	\$ 35720
634-540-92	HSSUB-6100 12G SERIAL IO EXPANSION INSTRUMENT W/G20 OPTICAL FUNNEL Note : Depends on HSSub custom BIOS	\$ 28210
634-540-91	HSSUB-6100 12G SERIAL IO EXPANSION INSTRUMENT WITH VTAC FUNNEL HSSub-6100 12G Serial instrument with Funnel assembly for Virginia Panel G20 receiver with VTAC high frequency cabled receiver module supporting full ITAs and i2 MX ITA connectors Note : Depends on HSSub custom BIOS	\$ 32750



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
634-540-93	HSSUB-6100 12G SERIAL IO EXPANSION INSTRUMENT WITH G20 EXPANDED BEAM OPTICAL FUNNEL HSSub-6100 12G Serial instrument with Funnel assembly for Virginia Panel G20 receiver with expanded Beam optical cabled receiver module supporting full ITAs and i2 MX ITA expanded beam optical connectors. Note : Depends on HSSub custom BIOS	\$ 43980
634-540-96	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT WITH FUNNEL This IO Expansion Instrument provides: Same features as the 634-540-90 Not dependent on custom BIOS on HSSub controller	\$ 35720
634-540-97	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT WITH VTAC FUNNEL This IO Expansion Instrument provides: Same features as the 634-540-91 Not dependent on custom BIOS on HSSub controller	\$ 32570
634-540-98	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT WITH G20 OPTICAL FUNNEL This IO Expansion Instrument provides: Same features as the 634-540-92 Not dependent on custom BIOS on HSSub controller	\$ 28210
634-540-99	HSSUB-6101 12G SERIAL IO EXPANSION GEN 2 INSTRUMENT WITH G20 EXPANDED BEAM OPTICAL FUNNEL This IO Expansion Instrument provides: Same features as the 634-540-93 Not dependent on custom BIOS on HSSub controller	\$ 43980
633-833-80	HSSUB-6120 4-NODE AS5643 MIL-FIREWIRE INSTRUMENT This HSSUB-6120 Instrument provides: <ul style="list-style-type: none">• 1-slot PXI Express Gen 2 x4 instrument• Up to four concurrent IEEE 1394b FireWire nodes each with 3 ports• Independent transformer coupling and isolation relay on each port• Each port may be configured to support 100 Mbps, 200 Mbps, 400 Mbps and 800 Mbps data transfer rates.• Two trigger inputs• Supplied with SAE AS5643 HSSub App for Mil-FireWire mode	\$ 33480



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
676-877-80	HSSUB-6125 4-NODE AS5643 MIL-FIREWIRE CE MARKED INSTRUMENT This HSSUB-6125 Instrument provides: <ul style="list-style-type: none">• CE-Certified• 1-slot PXI Express Gen 2 x4 instrument<ul style="list-style-type: none">• Up to four concurrent IEEE 1394b FireWire nodes each with 3 ports• Independent transformer coupling and isolation relay on each port• Each port may be configured to support 100 Mbps, 200 Mbps, 400 Mbps and 800 Mbps data transfer rates.• Two trigger inputs• Supplied with SAE AS5643 HSSub App for Mil-FireWire mode	\$ 33480
676-877-90	HSSUB-6125 4-NODE AS5643 MIL-FIREWIRE CE MARKED INSTRUMENT WITH EMI G20 FUNNEL This HSSUB-6125 Instrument provides: <ul style="list-style-type: none">• CE-Certified• 1-slot PXI Express Gen 2 x4 instrument<ul style="list-style-type: none">• Up to four concurrent IEEE 1394b FireWire nodes each with 3 ports• Independent transformer coupling and isolation relay on each port• Each port may be configured to support 100 Mbps, 200 Mbps, 400 Mbps and 800 Mbps data transfer rates.• Two trigger inputs• Supplied with SAE AS5643 HSSub App for Mil-FireWire mode• EMI Funnel assembly for Virginia Panel G20 receiver with one VTAC receiver modules supporting full ITAs and i2 MX ITA connectors	\$ 41310



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
700-426-00	MIL-FIREWIRE KIT VDATS MESS-017 Kit contains: (1) 676-877-80 HSSUB-6125 4 Node AS5643 Mil- Firewire CE Instrument (1) 671-383-01 Firewire CIB (1) 707-641-00 Firewire to Quadrapaddle 24" Cable (1) 634-540-80 HSSub 12G Serial Instrument (1) 658-499-99 FC-2 Layer Compatibility App Software (1) 678-899-80 PXI VERTA P3020 Switch Matrix and Optical Power Management Instrument (4) 710-059-03 SFP+ Optical Fiber Channel Transceiver	\$ 146890
633-833-90	HSSUB-6120 4-NODE AS5643 MIL-FIREWIRE INSTRUMENT WITH FUNNEL HSSub-6120 AS5643 Mil-FireWire instrument with Funnel assembly for Virginia Panel G20 receiver with one VTAC receiver modules supporting full ITAs and i2 MX ITA connectors	\$ 41310
687-242-80	HSSUB-6126 4-NODE 1394A FIREWIRE IO EXPANSION INSTRUMENT This instrument provides: <ul style="list-style-type: none">• 1-slot PXI Express Gen 2 x4 instrument• Up to four concurrent IEEE 1394a FireWire nodes each with 3 ports• Isolation relay on each port• Each port may be configured to support 100 Mbps, 200 Mbps, and 400 Mbps data transfer rates.• Two trigger inputs	\$ 33480
664-840-80	HSSUB-6140 8G HYBRID IO EXPANSION INSTRUMENT This instrument is a one-slot, fully integrated and tested assembly that includes: <ul style="list-style-type: none">• CE certified• 1-slot PXI Express Gen 3 x8 instrument• Low-level protocol is implemented in HSSub App-accessible Xilinx Ultrascale Test Defined FPGA• 2 GB of DDR3 memory directly accessible• Physical I/O and low-level protocol controlled by reprogrammable FPGA• 8 Xilinx GTX transceivers (capable of supporting multiple protocols at rates of 1 - 8 Gbps)• 104 bidirectional LVTTTL channels (up to 200 Mb/s)• 26 LVDS pairs (up to 800 Mb/s)	\$ 28860



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
664-840-90	HSSUB-6140 8G HYBRID IO EXPANSION INSTRUMENT WITH G20 FUNNEL ASSEMBLY HSSub-6140 8G Hybrid instrument with funnel assembly for Virginia Panel G20 receiver with VTAC receiver modules which bring out MGT IO and LVDS IO with compatibility to pinmap for 614-383-90 Hybrid IO Expansion Instrument with Funnel Assembly. Support full ITAs and i2 MX ITA connectors.	\$ 39540
664-840-91	HSSUB-6140 8G HYBRID INSTRUMENT W/ G20 FUNNEL VTAC MGT TOP SE BOTTOM HSSub-6140 8G Hybrid instrument with funnel assembly for Virginia Panel G20 receiver with VTAC receiver modules which bring out MGT IO and Single-ended IO with Funnel Assembly. Support full ITAs and i2 MX ITA connectors.	\$ 39540
664-840-92	HSSUB-6140 8G HYBRID IRIG-B INSTRUMENT W/ FUNNEL HSSub-6140 8G Hybrid instrument with IRIG-B CIB and funnel assembly for Virginia Panel G20 receiver with VTAC connectors which has 3 input channels for amplitude modulated IRIG-B signal I/O. Use ITA loopback modules 700-649-03 for full ITAs or 700-649-13 for independent i2 ITA modules.	\$ 39540
664-840-93	HSSUB-6140 8G HYBRID TO HSSUB6020A HYBRID I/O EXPANSION INSTRUMENT WITH G20 FUNNEL ASSEMBLY HSSub-6140 8G Hybrid instrument with funnel assembly for Virginia Panel G20 receiver with Quadrapaddle receiver modules which bring out single ended IO compatibility with pinmap 630-666-90 eDigital-6020A IO Expansion Instrument with Funnel Assembly. Support full ITAs and i2 MX ITA connectors..	\$ 39540
673-317-00	CABLE, G20 FUNNEL 8G HYBRID MGT TOP SE BOTTOM FUNNEL, W/ CONN VPC Funnel assembly for HSSub-6140 8G Hybrid Instrument included with part number 664-890-91.	\$ 8750
673-317-03	CABLE, G20 ITA 8G HYBRID MGT TOP SE BOTTOM, W/ CONN VPC ITA connector wired for Wire Verification HSSub-6140 instrument with Funnel (664-840-91) with i2 MX VTAC ICA connectors for copper IO.	\$ 7520
634-541-80	HSSUB-6310 STREAMING STORAGE MODULE This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none"> • CE certified • 1-slot PXI Express Gen 3 x8 instrument • Provides 2 TB of high speed Flash-based memory • Write operations to 2.1 GB/s • Read operations to 3.5 GB/s • Data can be streamed peer to peer from HSSub instruments using HSSub TriFlex Streaming Services 	\$ 37800



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
357-604-18	G20 MX FUNNEL FOR TIMING AND SYNCHRONIZATION MODULE	\$ 3520
632-682-90	HSSUB-8030 PERIPHERAL BUS INSTRUMENT WITH FUNNEL ASSEMBLY <ul style="list-style-type: none">• 1-slot PXI Express Gen 3 x8 instrument• Includes integrated Virginia Panel G20 funnel module supporting full ITAs and i2 MX ITA connectors• Provides a collection of PC-style bus interfaces packaged in an instrument for direct connection to the UUT• All buses are supported directly by the Windows operating system on the HSSub PC as if they were integrated within the computer• Supported bus types:<ul style="list-style-type: none">• RS232 - two ports with all support signals• Ethernet - four ports of 10 BASE-T, 100 BASE-T, 1000 BASE-T• eSATA - Two ports supporting eSATA 3.0• USB - Four ports of USB 2.0/3.0	\$ 17000
636-285-03	WVT CONNECTOR FOR HSSUB-8030 PBI WITH FUNNEL - G20 VPC ITA connector wired for Wire Verification Test of HSSub-8030 Peripheral Bus Instrument with Funnel	\$ 4370
622-289-00	HSSUB-9010 32 PAIR RS485 FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">• Teradyne Zync Control FPGA and 1 GB memory• Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">• 32 differential RS485 pairs• Each pair programmable as an input or output• Programmable termination• Test Defined FPGA provides low-level control	\$ 29700



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-289-95	HSSUB-9010 32 CHANNEL RS-485 FIOXI WITH FUNNEL This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">• Teradyne Zync Control FPGA and 1 GB memory• Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">• 32 differential RS485 pairs• Each pair programmable as an input or output• Programmable termination• Test Defined FPGA provides low-level control• Funnel assembly for Virginia Panel G20 receiver with QuadraPaddle modules supporting full ITAs and i2 MX ITA connectors	\$ 33480
622-289-90	HSSUB-9010 32 PAIR RS485 FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">• Teradyne Zync Control FPGA and 1 GB memory• Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">• 32 differential RS485 pairs• Each pair programmable as an input or output• Programmable termination• Test Defined FPGA provides low-level control• Funnel assembly for Virginia Panel G20 receiver with QuadraPaddle connector	\$ 34480
622-290-00	HSSUB-9020 ETHERNET FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10/100/1000 Mbps Ethernet portso Controllable by TCP/IP stack on HSSub Windows PC	\$ 29700



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-290-90	HSSUB-9020 ETHERNET FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10/100/1000 Mbps Ethernet portso Controllable by TCP/IP stack on HSSub Windows PC• Funnel assembly for Virginia Panel G20 receiver<ul style="list-style-type: none">o QuadraPaddle connector for eight wired Ethernet portso Connector available for cable to an Optical IO Expansion Instrument for two Optical Ethernet ports	\$ 37910
622-295-00	HSSUB-9030 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o HotLink:<ul style="list-style-type: none">• Four full duplex interfaces• 200-1500 Mbps operationo ECL:<ul style="list-style-type: none">• 12 differential ECL inputs• 12 differential ECL outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable Note :: Depends on HSSub custom BIOS	\$ 38180
622-295-01	HSSUB-9031 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT This Flexible IO Expansion Instrument provides: Same features as the 622-295-00 Not dependent on custom BIOS on HSSub controller	\$ 38180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-295-95	<p>HSSUB-9030 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o HotLink:<ul style="list-style-type: none">• Four full duplex interfaces• 200-1500 Mbps operationo ECL:<ul style="list-style-type: none">• 12 differential ECL inputs• 12 differential ECL outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable• Funnel assembly for Virginia Panel G20 receiver with QuadraPaddle modules supporting full ITAs and i2 MX ITA connectors	\$ 47390

Note :: Depends on HSSub custom BIOS



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-295-96	HSSUB-9030 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT WITH 1-CH RS485 AND 1-CH ECL LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Funnel assembly for Virginia Panel G20 receiver with<ul style="list-style-type: none">o One RS485 level 50MHZ CLOCK IO CIB Assemblyo One ECL level 50MHZ CLOCK IO CIB Assemblyo One QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules Note :: Depends on HSSub custom BIOS	\$ 47390
622-295-97	HSSUB-9031 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: Same features as the 622-295-95 Not dependent on custom BIOS on HSSub controller	\$ 47390
622-295-98	HSSUB-9031 RS485/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH 1-CH RS485 AND 1-CH ECL LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL This Flexible IO Expansion Instrument provides: Same features as the 622-295-96 Not dependent on custom BIOS on HSSub controller	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
624-111-00	<p>HSSUB-9050 ETHERNET/RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Control FPGA with 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10BASE-T/100BASE-T/1000BASE-T wired Ethernet portso Two additional ports for connection to an Optical IO Expansion Instrument to produce 1000BASE-SX Optical Gigabit Etherneto Controllable by TCP/IP stack on HSSub Windows PCo Maximum concurrently operating ports:• Two Optical and Four wired ports• Eight wired and no Optical ports• Physical Interface Module (PIM) in Fusion Socket 1 providing<ul style="list-style-type: none">o Maximum RS232 ports:• 8 ports with full handshaking capability• 32 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PC<ul style="list-style-type: none">o IRIG-B:• One input (analog and digital)• One output (analog and digital)	\$ 40810



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
624-111-90	<p>HSSUB-9050 ETHERNET/RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Control FPGA with 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory....• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10BASE-T/100BASE-T/1000BASE-T wired Ethernet ports accessed at QuadraPaddle receiver connectoro Two additional ports for connection to an Optical IO Expansion Instrument to produce 1000BASE-SX Optical Gigabit Ethernet are accessed via a connector on the top of the Virginia Panel G20 funnelo Controllable by TCP/IP stack on HSSub Windows PCo Maximum concurrently operating Ethernet ports:..<ul style="list-style-type: none">• Six wired and two optical ports..• Eight wired and no optical ports..• Physical Interface Module (PIM) in Fusion Socket 1 providing<ul style="list-style-type: none">o RS232 ports:<ul style="list-style-type: none">• Up to 6 ports with full handshaking capability..• Up to 36 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA..• Supported by Teradyne RS232 HSSub App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver connectors for each of the two Physical Interface Modules	\$ 52400



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
624-111-95	<p>HSSUB-9050 ETHERNET/RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Control FPGA with 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory.• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10BASE-T/100BASE-T/1000BASE-T wired Ethernet ports accessed at QuadraPaddle receiver connectoro Two optical 1000BASE-SX ports accessible via provided SFP pluggable modules at the top of the Virginia Panel G20 funnelo Controllable by TCP/IP stack on HSSub Windows PCo Maximum concurrently operating Ethernet ports:<ul style="list-style-type: none">§ Six wired and two optical ports..§ Eight wired and no optical ports..• Physical Interface Module (PIM) in Fusion Socket 1 providing<ul style="list-style-type: none">o RS232 ports:<ul style="list-style-type: none">§ Up to 6 ports with full handshaking capability§ Up to 36 ports with no handshake capability (TX/RX only)§ UARTs implemented in Test Defined FPGA§ Supported by Teradyne RS232 HSSub App providing control via PCo IRIG-B:<ul style="list-style-type: none">§ One input (analog and digital)§ One output (analog and digital)• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules	\$ 60360
622-469-00	<p>HSSUB-9060 RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Control FPGA with 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 1 providing<ul style="list-style-type: none">o Maximum RS232 ports:<ul style="list-style-type: none">• 8 ports with full handshaking capability• 32 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PC<ul style="list-style-type: none">o IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver connector	\$ 29700



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-469-90	HSSUB-9060 RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Control FPGA with 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 1 providing<ul style="list-style-type: none">o Maximum RS232 ports:<ul style="list-style-type: none">• 8 ports with full handshaking capability• 2 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PC<ul style="list-style-type: none">o IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)	\$ 33810
622-472-00	HSSUB-9070 HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o HotLink:<ul style="list-style-type: none">• Four full duplex interfaces• 200-1500 Mbps operationo ECL:<ul style="list-style-type: none">• 12 differential ECL inputs• 12 differential ECL outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable	\$ 29700



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-472-90	<p>HSSUB-9070 HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o HotLink:<ul style="list-style-type: none">• Four full duplex interfaces• 200-1500 Mbps operationo ECL:<ul style="list-style-type: none">• 12 differential ECL inputs• 12 differential ECL outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable <p>• Funnel assembly for Virginia Panel G20 receiver with QuadraPaddle connector</p>	\$ 33810



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
629-604-00	<p>HSSUB-9080 RS485/RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o Maximum standard RS232 ports:<ul style="list-style-type: none">• 115 kbps max. data rate• 3 ports with full handshaking capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo Maximum fast RS232 or RS423 ports:<ul style="list-style-type: none">• 1 Mbps max. data rate• 3 ports with full handshaking RS232 capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• 100 PPS RS-422 input• 100 PPS RS-422 output	\$ 38180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
629-604-90	<p>HSSUB-9080 RS485/RS232/IRIG-B FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o Maximum standard RS232 ports:<ul style="list-style-type: none">• 115 kbps max. data rate• 3 ports with full handshaking capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo Maximum fast RS232 or RS423 ports:<ul style="list-style-type: none">• 1 Mbps max. data rate• 3 ports with full handshaking RS232 capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• 100 PPS RS-422 input• 100 PPS RS-422 output• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
638-681-00	HSSUB-9100 64 PAIR RS485 FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control Note :: Depends on HSSub custom BIOS	\$ 38180
638-681-01	HSSUB-9101 64 PAIR RS485 FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT This Flexible IO Expansion Instrument provides: Same features as the 638-681-00 Not dependent on custom BIOS on HSSub controller	\$ 38180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
638-681-90	<p>HSSUB-9100 64 PAIR RS485 FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules <p>Note: Depends on HSSub custom BIOS</p>	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
638-681-91	HSSUB-9100 64 PAIR RS485 FLEXIBLE IO EXPANSION INSTRUMENT WITH 2-CH RS485 LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• One QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules Note :: Depends on HSSub custom BIOS	\$ 47390
638-681-97	HSSUB-9101 64 PAIR RS485 FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH FUNNEL This Flexible IO Expansion Instrument provides: Same features as the 638-681-90 Not dependent on custom BIOS on HSSub controller	\$ 47390
638-681-98	HSSUB-9101 64 PAIR RS485 FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH 2-CH RS485 LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL This Flexible IO Expansion Instrument provides: Same features as the 638-681-91 Not dependent on custom BIOS on HSSub controller	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
656-290-00	HSSUB-9110 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Maximum standard RS232 ports:<ul style="list-style-type: none">• 115 kbps max. data rate• 3 ports with full handshaking capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo Maximum fast RS232 or RS423 ports:<ul style="list-style-type: none">• 1 Mbps max. data rate• 3 ports with full handshaking RS232 capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• 100 PPS RS-422 input• 100 PPS RS-422 output• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o HotLink ports:<ul style="list-style-type: none">• Four full duplex interfaces• 200 - 1500 Mbps operationo ECL ports:<ul style="list-style-type: none">• 12 differential inputs• 12 differential outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable Note : Depends on HSSub custom BIOS	\$ 38180
656-290-01	HSSUB-9111 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT This Flexible IO Expansion Instrument provides: Same features as the 656-290-00 Not dependent on custom BIOS on HSSub controller	\$ 38180



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
656-290-90	<p>HSSUB-9110 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Maximum standard RS232 ports:<ul style="list-style-type: none">• 115 kbps max. data rate• 3 ports with full handshaking capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo Maximum fast RS232 or RS423 ports:<ul style="list-style-type: none">• 1 Mbps max. data rate• 3 ports with full handshaking RS232 capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• 100 PPS RS-422 input• 100 PPS RS-422 output• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o HotLink ports:<ul style="list-style-type: none">• Four full duplex interfaces• 200 - 1500 Mbps operationo ECL ports:<ul style="list-style-type: none">• 12 differential inputs• 12 differential outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules <p>Note : Depends on HSSub custom BIOS</p>	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
656-290-91	<p>HSSUB-9110 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION INSTRUMENT WITH 1-CH ECL LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Maximum standard RS232 ports:<ul style="list-style-type: none">• 115 kbps max. data rate• 3 ports with full handshaking capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PC or RT <p>Processor</p> <ul style="list-style-type: none">o Maximum fast RS232 or RS423 ports:<ul style="list-style-type: none">• 1 Mbps max. data rate• 3 ports with full handshaking RS232 capability• 18 ports with no handshake capability (TX/RX only)• UARTs implemented in Test Defined FPGA• Supported by Teradyne RS232 App providing control via PCo IRIG-B:<ul style="list-style-type: none">• One input (analog and digital)• One output (analog and digital)• 100 PPS RS-422 input• 100 PPS RS-422 output• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o HotLink ports:<ul style="list-style-type: none">• Four full duplex interfaces• 200 - 1500 Mbps operationo ECL ports:<ul style="list-style-type: none">• 12 differential inputs• 12 differential outputs• Up to 60 Mbps operation• 50 ohms to -2V termination, selectable• Funnel assembly for Virginia Panel G20 receiver with<ul style="list-style-type: none">o One ECL level 50MHZ CLOCK IO CIB Assemblyo One QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules <p>Note : Depends on HSSub custom BIOS</p>	\$ 47390
656-290-97	<p>HSSUB-9111 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH FUNNEL</p> <p>This Flexible IO Expansion Instrument provides:</p> <p>Same features as the 656-290-90</p> <p>Not dependent on custom BIOS on HSSub controller</p>	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
656-290-98	HSSUB-9111 RS232/IRIG-B/HOTLINK/ECL FLEXIBLE IO EXPANSION GEN 2 INSTRUMENT WITH 1-CH ECL LEVEL 50MHZ CLOCK IO CIB AND G20 EMI FUNNEL This Flexible IO Expansion Instrument provides: Same features as the 656-290-91 Not dependent on custom BIOS on HSSub controller	\$ 47390
670-148-00	HSSUB-9120 ETHERNET/RS485 FLEXIBLE IO EXPANSION INSTRUMENT This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory provides low level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10/100/1000 Mbps Ethernet portso Controllable by HSSub Windows PC• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control	\$ 38180
670-148-95	HSSUB-9120 ETHERNET/RS485 FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory provides low level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o Eight 10/100/1000 Mbps Ethernet portso Controllable by HSSub Windows PC• Physical Interface Module (PIM) in Fusion Socket 1 providing:<ul style="list-style-type: none">o 32 differential RS485 pairso Each pair programmable as an input or outputo Programmable terminationo Test Defined FPGA provides low-level control• Funnel assembly for Virginia Panel G20 receiver with one QuadraPaddle receiver modules supporting full ITAs and i2 MX ITA connectors for each of the two Physical Interface Modules	\$ 47390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
666-175-90	HSSUB-9500 SYNC/TEST FLEXIBLE IO EXPANSION INSTRUMENT WITH FUNNEL ASSEMBLY This Flexible IO Expansion Instrument provides: <ul style="list-style-type: none">• 2-slot Flexible IO Expansion Instrument Fusion Module<ul style="list-style-type: none">o Teradyne Zync Control FPGA and 1 GB memoryo Test Defined Virtex 7 FPGA with 2 GB memory provides low level control• Physical Interface Module (PIM) in Fusion Socket 0 providing:<ul style="list-style-type: none">o (2) 40 MHz clock outputso (5) Discrete PECL inputso (5) Discrete PECL outputso (16) Opto-coupled inputso (14) Opto-coupled outputso (13) TTL inputso (2) TTL outputso (2) Buffered DAC outputso ADC measurement of (5) select signals	\$ 44760
710-059-00	SFP OPTICAL ETHERNET TRANCEIVER	\$ 210
710-059-01	SFP OPTICAL FIBRE CHANNEL TRANCEIVER	\$ 210
652-063-00	SFP TRANSCEIVER, 4.25 GB/S	\$ 250
678-020-00	SOLID OPTICS SFP-1G-LX-MMF-SO SFP TRANSCEIVER	\$ 1000
710-059-03	SFP OPTICAL FIBRE CHANNEL TRANCEIVER	\$ 360
619-414-01	PLUG, LOOPBACK SFP+, Minimum order quantity of 5	\$ 120
357-603-62	WVT CONNECTOR FOR HSSUB SERIAL CORE WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-5050 Serial Core Instrument (613-892-95) with Funnel with i2 MX ICA connectors. Two modules are required per HSSub-5050 instrument.	Consult Factory
622-455-03	WVT MATERIAL FOR SERIAL CORE INSTRUMENT W/ 8I/O	Consult Factory
622-459-03	WVT MATERAIL FOR HSSUB-6065 4 PORT OPTICAL IO EXPANSION INSTRUMENT	\$ 2130
622-462-03	WVT MATERIAL FORHSSUB-9050 ETHERNET/RS232/IRIG-B FIOXI WITH FUNNEL	\$ 1610
622-462-13	WVT MODULE FOR HSSUB RS232/IRIG-B FIOXI WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-9050 FIOXI Instrument (624-111-95) with Funnel with i2 MX ICA connectors. One module is required per HSSub-9050 instrument.	\$ 3060



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
622-463-13	WVT MODULE FOR HSSUB RS485 FIOXI WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-9030 FIOXI Instrument with Funnel (622-295-95) or HSSub-9100 with Funnel (638-681-90) with i2 MX ICA connectors. One module is required per HSSub-9030 instrument. Two modules are required per HSSub-9100 instrument.	\$ 3060
622-464-03	WVT MATERIAL FOR HOTLINK/ECL FIOXI PIM WITH FUNNEL	\$ 1610
622-464-13	WVT MODULE FOR HSSUB HOTLINK FIOXI WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-9030 FIOXI Instrument (611-039-95) with Funnel with i2 MX ICA connectors. One module is required per HSSub-9030 instrument.	\$ 3060
622-466-03	WVT MATERIAL ETHERNET FIOXI PHYSICAL INTERFACE MODULE (PIM)	\$ 1830
622-466-13	WVT MODULE FOR HSSUB ETHERNET FIOXI WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-9050 FIOXI Instrument (624-111-95) with Funnel with i2 MX ICA connectors. One module is required per HSSub-9050 instrument.	\$ 2820
628-302-03	WVT CONNECTOR FOR HSSUB-6090 WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6090 Ethernet Instrument with Funnel	\$ 1720
628-302-13	WVT MATERIAL FOR HSSUB-6090 1-SLOT 8 PORT ETHERNET IO EXPANSION INSTRUMENT This item contains the self evaluation fixture wiring, and integration of wire verification selftest.	\$ 2820
636-285-13	WVT CONNECTOR FOR HSSUB-8030 PBI WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-8030 Peripheral Bus Instrument (632-682-90) with Funnel with i2 MX ICA connectors.	\$ 4800
637-642-13	WVT CONNECTOR FOR HSSUB-6120 MIL-FIREWIRE WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6120 Mil-FireWire Instrument (633-833-90) with Funnel with i2 MX ICA connectors.	\$ 5350
622-467-03	WVT CONNECTOR FOR HSSUB-6040 WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6040 Instrument with Funnel (614-383-90) and HSSub-6140 instrument with Funnel (664-840-90) with i2 MX VTAC ICA connectors for copper IO.	\$ 5430



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
640-041-13	WVT CONNECTOR FOR HSSUB-6020A EDIGITAL WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6020A eDigital Instrument (630-666-90) with Funnel with i2 MX ICA connectors.	\$ 2640
650-957-13	WVT CONNECTOR FOR HSSUB TIMING MODULE WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub Timing Module (630-681-01) with Funnel with i2 MX ICA connectors. .	\$ 3940
652-825-13	CABLE, WVT I2 CON ITA 10G ETHERNET SFP IOXI FUNNEL	\$ 3330
652-826-03	CABLE, WVT G20 ITA 12G SERIAL SFP IOXI FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6100 12G Serial Instrument with Funnel (634-540-90) with i2 MX ICA connectors for optical IO.	\$ 3680
652-826-13	WVT CONNECTOR FOR HSSUB-6100 12G SERIAL WITH FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6100 12G Serial Instrument with Funnel (634-540-90) with i2 MX ICA connectors for optical IO.	\$ 4800
652-826-23	WVT CONNECTOR FOR HSSUB-6100 12G SERIAL WITH FUNNEL VPC ITA connector cabled for Wire Verification Test of HSSub-6100 12G Serial Instrument with Funnel (634-540-93) with i2 MX ICA connectors for optical IO.	\$ 9760
652-825-03	CABLE, WVT G20 ITA 10G ETHERNET SFP IOXI FUNNEL	\$ 2200
660-275-03	CABLE, WVT G20 ITA 10G ETHERNET IOXI VTAC FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-609110G Ethernet Instrument with Funnel (635-352-91) with i2 MX VTAC ICA connectors for copper IO.	\$ 1940
660-275-13	CABLE, WVT I2 CON ITA 10G ETHERNET IOXI VTAC FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-609110G Ethernet Instrument with Funnel (635-352-91) with i2 MX VTAC ICA connectors for copper IO.	\$ 2650
660-276-03	CABLE, WVT G20 ITA 12G SERIAL IOXI VTAC FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6100 12G Serial Instrument with Funnel (634-540-91) with i2 MX VTAC ICA connectors for copper IO.	\$ 2900
660-276-13	CABLE, WVT I2 CON ITA 12G SERIAL IOXI VTAC FUNNEL VPC ITA connector wired for Wire Verification Test of HSSub-6100 12G Serial Instrument with Funnel (634-540-91) with i2 MX VTAC ICA connectors for copper IO.	\$ 3660



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
666-456-00	WVT MODULE FOR HSSUB SYNC/TEST FIOXI WITH FUNNEL ASSEMBLY VPC ITA connector wired for Wire Verification Test of HSSub-9500 FIOXI Instrument (666-175-90) with Funnel with i2 MX ICA connectors. Two modules are required per HSSub-9500 instrument.	\$ 2900
660-758-00	FRONT PANEL LOOPBACK CIB FOR HSSUB-6120 MILFIREWIRE INSTRUMENT	\$ 1440
639-989-00	HSSUB-AK REUSABLE TRANSIT CASE The reusable HSS Transit case is designed to house the HSSub during shipment and storage.	Consult Factory
639-990-00	CASE, TRANSIT PLUG WRAP	Consult Factory
686-645-80	EDIGITAL-6030 FRONT PANEL LOOPBACK ADAPTER eDigital-6030 interface adaptor for loopback testing at the instrument front panel	\$ 3560
686-648-80	EDIGITAL-6030 CALIBRATION ADAPTER (FOR CONFIG WITHOUT FUNNEL) eDigital-6030 calibration adaptor (Cal CIB) for interface with instrument configured without a funnel	\$ 3560
689-681-80	EDIGITAL-6030 BREAKOUT CIB eDigital-6030 Breakout Cable Interface Board (CIB) for use in test development, troubleshooting, Boundry Scan. CIB is installed at the front panel (not with funneled configuration)	\$ 3170
696-148-80	EDIGITAL-6030 CALIBARTION ADAPTER I2 (FOR CONFIG WITH FUNNEL) eDigital-6030 calibration adaptor (Cal CIB) for I2 interface with instrument configured with a funnel	\$ 5910
698-342-03	EDIGITAL-6030 G20 ITA LOOPBACK eDigital-6030 interface adaptor for loopback testing with G20 interface	\$ 3880
698-342-13	EDIGITAL-6030 I2 ITA LOOPBACK eDigital-6030 interface adaptor for loopback testing with I2 interface.	\$ 4590
650-595-30	PM ITA LOOPBACK ASSEMBLY KIT Contains (2) 654-660-13, (2) 654-660-14, 622-467-13	\$ 21560



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
650-595-31	SLIMRTH PM ITA LOOPBACK ASSEMBLY KIT Contains qty 2 654-660-13 Cable i2 ITA Loopback, Qty 1 654-660-14 Cable i2 ITA Loopback, Qty 2 622-467-14 Cable i2 ITA Loopback	\$ 21050
660-499-00	1U 16-PORT FEED-THRU PANEL W/8 DUPLEX LC'S FOR TESTER	\$ 570
661-121-00	COVER ASSEMBLY, 6U TALL, 5.25" DEPTH	\$ 4500
662-595-80	LVTTL2 LOOPBACK ADAPTER HLA	Consult Factory
662-595-81	LVTTL2 LED TRAINING BOARD HLA	Consult Factory
664-472-80	LVTTL2 TO 34 POS RIBBON HEADER HLA	\$ 5220
654-660-21	LVTTL IO INSTRUMENT PM CABLE	Consult Factory
628-302-00	G20 FUNNEL FOR HSSUB-6090 1-SLOT ETHERNET FLEXIBLE IO EXPANSION INSTRUMENT <ul style="list-style-type: none"> • Virginia Panel G20 funnel with QuadraPaddle ICA connector for eight wired ports • For use with 623-485-80 HSSub-6090 1-slot Ethernet IO Expansion Instrument 	\$ 7530
654-660-22	HYBRID IO INSTRUMENT PM CABLE	Consult Factory
657-597-00	HSSUB-9080 ADAPTER CABLE FOR GEN2 TS	\$ 11570
658-690-00	PC MONITOR, KEYBOARD, MOUSE KIT	\$ 1470
663-942-00	CABLE KIT, FIOXI RS485 TO SCSI CIB	\$ 3740
629-625-00	2-CHANNEL OPTICAL IO EXPANSION INSTRUMENT AND CABLE FOR ETHERNET This Optical IO Expansion Instrument provides: <ul style="list-style-type: none"> • One 618-142-80 4-Channel IO Expansion Instrument for mounting behind Direct Connect Panel in 611-038-05 Foundation • Cable assembly that connects instrument to Ethernet Instrument and to the Direct Connect Panel Note: <ul style="list-style-type: none"> • Instrument does not use a PXI chassis slot 	Consult Factory
658-499-99	FC-2 LAYER COMPATABILITY APP SOFTWARE	\$ 3250



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
691-358-99	SPI HSSUB APP SOFTWARE & DOC Configures the HSSub eDigital-6020A Flexible IO Expansion Instrument to support SPI TX/Rx behavior that can transmit and receive on 1 to 4 Interfaces per instrument at speeds up to 10 M. C/C# Application Programming Interface supporting interface initialization, settings and operation modes Interface Speed (All interfaces need to be the same speed): <ul style="list-style-type: none">o Minimum interface speed of 10 MB/s SDR	\$ 9120
676-099-99	ARINC 708 STIMULUS ONLY APP <ul style="list-style-type: none">• Configures the RS485 Flexible IO Expansion Instrument to create a user-defined 1600-bit ARINC 708 stimulus stream<ul style="list-style-type: none">• User-created file specifies the contents of one or more ARINC 708 data frames• User data is repeated continuously until terminated• Includes Windows TPS API on HSSub PC• Includes executable App code that can be invoked from any HSSub TPS on the HSSub PC• Includes hardware design for ARINC 708 buffer and transformer circuit that can be located in the main TPS ID	\$ 6080
663-837-99	2.5G SFPDP STREAMING DATA HSSUB APP Configures the HSSub-6100 12G Serial IO Expansion Instrument and the HSSub-6310 Streaming Storage instrument to support capture and playback Serial Front Panel Data Port streaming data compliant to ANSI/VITA 17.1-2015 <ul style="list-style-type: none">• Real-time peer-to-peer data streaming across PXIe backplane with sustained write speed of 2.1 GB/s and read speed of 3.5 GB/s• Supports 4 lanes of 2.5 Gb/s per 12G instrument with up to 0.5TB storage per lane or 26 minutes of record time• Simultaneous, parallel access to multiple Storage instruments• 3.5 GB/s stored data offload capability via 10G Ethernet IO Expansion Instrument• Full featured C/C# Application Programming Interface supporting store and playback operation modes, time stamping, error checking, signal state and other metadata• GUI application for Windows for test setup, start/stop data recording and playback, data file access, secure file erase and diagnostic utility functions	\$ 9390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
667-637-99	10G SFPDP STREAMING DATA HSSUB APP Configures the HSSub-6100 12G Serial IO Expansion Instrument and the HSSub-6310 Streaming Storage Instrument to support capture and playback Serial Front Panel Data Port streaming data compliant to ANSI/VITA 17.3-2018 <ul style="list-style-type: none">• Real-time peer-to-peer data streaming across PXIe backplane with sustained write speed of 2.1 GB/s and read speed of 3.5 GB/s• Supports 2 lanes of 10G per 12G instrument with up to 1TB storage per lane for 13 Minutes of record time• Simultaneous, parallel access to multiple Storage instruments• 3.5 GB/s stored data offload capability via 10G Ethernet IO Expansion Instrument• Full featured C/C# Application Programming Interface supporting store and playback operation modes, time stamping, error checking, signal state and other metadata• GUI application for Windows for test setup, start/stop data recording and playback, data file access, secure file erase and diagnostic utility functions	\$ 12130
666-674-99	PCI HSSUB APP V1.0 Configures the eDigital-6020A Instrument to support 33MHz PCI Initiator or Target bus behavior <ul style="list-style-type: none">• Provide PCI Bus management functions including Reset, all clocks, bus ownership arbitration, IDSEL select lines, Configuration Space reads and writes, pull-up resistors, and interrupt and error handling• Maps a single dual-port memory of 1024 or fewer 32-bit locations into PCI space and drives out a single PCI interrupt• As Initiator reads and writes from local memory to UUT internal dual 4KB RAM memory• As Target allows external PCI Initiator to reads and writes from local 4KB RAM memory• C/C# Application Programming Interface supporting PCI Initialization and enumeration, operation modes, management functions and read/write to memory	\$ 9390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
666-676-99	I2C HSSUB APP V1.0 Configures the eDigital-6020A Instrument to support generic master or slave i2C bus behavior <ul style="list-style-type: none">• 8 independent bus ports• Up to a 32 message sequence• 2 tristate IOs per bus: SCL and SDA• Bus speeds (8-bit oriented bidirectional)<ul style="list-style-type: none">o Standard(Sm): 100kb/so Fast-Mode(Fm): 400kb/so Fast-Mode Plus(Fm+): 1Mb/so High-Speed Mode(Hs-mode): 3.4Mb/s• Bus speeds (8-bit oriented unidirectional)<ul style="list-style-type: none">o Ultra Fast-Mode(UFm): 5Mb/s• Master Mode<ul style="list-style-type: none">o 1K message FIFO for I2C transmissiono 1KB FIFO of receive/capture datao Source Message Types:<ul style="list-style-type: none">• Source and expect Ack• Source and expect No Ack• Receive with Capture• Receive without Capture• Receive Ignore• Slave Mode<ul style="list-style-type: none">o Configurable for 7 or 10 bit addressing with user assigned addresso Configurable Device IDo Reserved addresses supporto The slave behaves as a memory mapped device with control and status registers and a block of memory<ul style="list-style-type: none">• Scratchpad register• Slave busy status register• A 1KB memory block• C/C# Application Programming Interface supporting bus Initialization, settings and operation modes	\$ 9390
667-178-99	BI420 COMPATIBILITY HSSUB APP Configures the HSSub-6120 Mil-FireWire Instrument for compatibility to BI420 functionality and TPS programming interface.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
668-454-99	<p>GENERIC HOTLINK HSSUB APP</p> <p>Configures the HSSub-9070 Flexible IO Expansion Instrument to support HOTLink TX/Rx behavior that can transmit and receive HOTLink bytes on 1 to 4 Interfaces per FIOXI PIM. C/C# Application Programming Interface supporting interface initialization, settings and operation modes</p> <p>Hardware Supported:</p> <ul style="list-style-type: none">• HSSub-9070, standalone• HSSub-9030, runs concurrently with RS485 UART App• HSSub-9110, runs concurrently with RS232 UART App <p>Interface Speed (All interfaces need to be the same speed):</p> <ul style="list-style-type: none">• Minimum interfaces speed of 195 MBaud or 156 MB/s• 1 Interface at a Max speed of 1400 Mbaud or 1120 Mb/s• 2 Interfaces at a Max speed of 700 MBaud or 560 Mb/s• 4 Interfaces at a Max speed of 350 MBaud or 280 Mb/s	\$ 3150



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
670-147-99	<p>RS422/ECL SYNCHRONOUS PRBS HSSUB APP</p> <p>Configures the HSSub-9030 or HSSub-9100 or HSSub-9110 Flexible IO Expansion instrument for RS422 or ECL synchronous PRBS source and receive capability</p> <ul style="list-style-type: none">• Pseudorandom Patterns: PRBS-9, PRBS-15• Full-Duplex Data Bit Rates, Synchronous SDR (single data rate) timing mode:<ul style="list-style-type: none">o Low Range (RS422): 50 to 25,000,000 b/s data with 50 to 25,000,000 Hz clocko Low Range (ECL): 50 to 30,000,000 b/s data with 50 to 30,000,000 Hz clocko High Range (RS422 and ECL): 50 to 50,000,000 b/s data with 50 to 50,000,000 Hz clock• Programmable Direction Clock In/Clock Out• Measures Clock In, Clock Out Frequency• Reports Bit Error Rate• Full featured C/C# Application Programming Interface with documentation supporting initialization, settings and operation modes• HSSub-9030 RS485/ECL FIOX supported IO configurations:<ul style="list-style-type: none">o 4-channel, full-duplex, Synchronous, RS-422 functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Independent clock out)Or<ul style="list-style-type: none">o 8-channel, full-duplex, Synchronous, RS-422 functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Dependent clock out)Or<ul style="list-style-type: none">o 4-channel, full-duplex, Synchronous, ECL functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Independent clock out)Or<ul style="list-style-type: none">o 6-channel, full-duplex, Synchronous, ECL functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Dependent clock out)o All Channels support Low Range Timing Modes<ul style="list-style-type: none">• Quantity of 8 RS422• Quantity of 6 ECLo A subset of 1 RS422 channel supports High Range Timing Modeo A subset of 1 ECL channel supports High Range Timing Mode• HSSub-9100 RS485 FIOXI supported IO configurations:<ul style="list-style-type: none">o 8-channel, full-duplex, Synchronous, RS-422 functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Independent clock out)Or<ul style="list-style-type: none">o 16-channel, full-duplex, Synchronous, RS-422 functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Dependent clock out)o Quantity of 16 RS422 channels support Low Range Timing Modeso A subset of 2 RS422 channels support High Range Timing Mode• HSSub-9110 RS232/ECL FIOXI supported IO configurations:	\$ 5920



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	<ul style="list-style-type: none"> o 4-channel, full-duplex, Synchronous, ECL functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Independent clock out) Or o 6-channel, full-duplex, Synchronous, ECL functionality with PRBS Generator-Detector capability (Tx data, Rx data, Clock in, Dependent clock out) o Quantity of 6 ECL channels support Low Range Timing Modes o A subset of 1 ECL channel supports High Range Timing Mode 	
670-298-99	SMPTE 292 HSSUB APP Configures the HSSub-5050 Serial Core Instrument for SMPTE 292 Video Capture and Generation. Configures eight channels of a Serial Core Instrument to support SMPTE-292 Video I/O. Supports I/O with one of eight SMPTE-292 streams at a time Includes reference hardware design for SMPTE-292 Line Buffer circuit. Full featured C/C# Application Programming Interface with documentation supporting initialization, setup, and operation modes.	\$ 6680
678-331-99	FOTR SERIAL 8B/10B ENCODED DATA PACKET STREAM HSSUB APP The 8b/10b Encoded Data HSSub App configures 8G Hybrid IOXI and HSSub-6065 Optical IO Expansion Instrument with commercial SFP transceivers. The App provides two 8b/10b encoded serial data links, using MGT I/O operating at a bit rate of 400 Mb/s and a Baud rate of 500 Mbaud. Full duplex transmit and receive capability is supported on both data links. Files on the local PC can be loaded into the 8G Hybrid hardware for 8b/10b encoding and asynchronous transmission. Data can also be captured asynchronously and 10b/8b decoded via the 8G Hybrid hardware and saved as files on the local PC. Includes full featured C/C# Application Programming Interface with documentation supporting initialization, setup, and operation modes..	Consult Factory
CIPHER-ETH-HOST	AIT ETHERNET NETWORK TRAFFIC ANALYZER SOFTWARE	\$ 2670
Cipher-Host	FIBRE CHANNEL, ETHERNET, FIREWIRE PROTOCOL ANALYZER APPLICATION Single Seat, Perpetual License	\$ 7140
F-SIM-DCE	AIT ETHERNET FLIGHT SIMULYZER DCE AND FRAME BUILDER APPLICATIONS SOFTWARE	\$ 11260



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
HS-SIM	HIGH SPEED (FIBRE CHANNEL, ETHERNET, FIREWIRE) DATA SIMULATION APPLICATION Single Seat, Perpetual License	\$ 12905



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section E: DIGITAL HARDWARE OPTIONS		
600-528-00	TERADYNE HIGH PERFORMANCE 5.7 KW C SIZED VXI CHASSIS KIT The High-performance 5.7 KW C Sized VXI Chassis will accommodate 11 M9-Series cards plus an M-918 CRB, 12 Di-Series cards, 12 Ai-76X cards, or any mix of these cards. Teradyne recommends this chassis for use with Teradyne Digital, and Analog Instruments. NOTES: This chassis has a 3' power cable with a 30 Amp NEMA L6-30P plug (30 A locking plug) and a 7' 601-706-03 30 A Locking to 20 A Locking Plug Adapter/Extender If a bladed connector is required at the end of the extender, purchase the following item: 601-717-00 30 A Locking to 20 A Bladed Plug Adapter/Extender	\$ 41440
617-910-00	MEDIUM POWER 2.6 KW C SIZED VXI CHASSIS	\$ 30010
627-943-00	MEDIUM POWER 1.7 KW 6 SLOT C-SIZED HORIZONTAL EXPANSION CHASSIS This 6 slot VXI chassis is capable of powering 4 Di-Series Channel cards, or 3 Ai-760-Series Analog Test Instruments	\$ 28730
686-568-00	TERADYNE HIGH PERFORMANCE 3U, 4-SLOT C SIZED VXI CHASSIS This item is only available with configured in a Spectrum or High Speed Subsystem	\$ 22080
627-772-50	TERADYNE HIGH POWER FRONT MAINTAINABLE 10U VXI 4.0 COMPLIANT CHASSIS The high power 3.8 KW C Sized VXI Chassis provides cooling and power for demanding applications. Teradyne recommends this chassis for high performance instrumentation where front side VXI chassis maintenance is required. This chassis is fully compliant with the VXI 4.0 specification..	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
627-773-50	TERADYNE MEDIUM POWER FRONT MAINTAINABLE 8U VXI 4.0 COMPLIANT CHASSIS The medium power 1.7 KW C Sized VXI Chassis provides cooling and power for typical applications. Teradyne recommends this chassis for standard instrumentation where front side VXI chassis maintenance is required. This chassis is fully compliant with the VXI 4.0 specification.	Consult Factory
610-982-00	HIGH PERFORMANCE 4.0 KW C SIZED VXI COMPLIANT CHASSIS This chassis is a direct replacement for the M-940-02 chassis, which can accommodate up to 528 M920 channels (11 M-927s). Note: <ul style="list-style-type: none">For applications that do not require a Form, Fit, and Function equivalent to the M-940-02 chassis, Teradyne recommends using the 600-528-00 5.7 KW Chassis	Consult Factory
611-103-00	4.0 KW CHASSIS UPGRADE KIT This power supply upgrade kit contains the 405-389-01, and 405-391-01 power supplies, plus a label for the VXI Chassis, which changes the assembly PN (Part Number) of the VXI chassis from 854-991-11 (chassis with old design supplies) to 610-984-00 (chassis with new design supplies).	Consult Factory
405-389-01	SPARE UPPER POWER SUPPLY FOR 4.0 KW CHASSIS This power supply is the upper power supply used in the 610-982-00 and 610-983-00 chassis. This supply is also a direct replacement for the 405-389-00 upper power supply used in the 854-991-11 chassis. Note: If upgrading an old design VXI chassis , 611-103-00 Upgrade Kit should be ordered instead of individual supplies.	Consult Factory
405-391-01	SPARE LOWER POWER SUPPLY FOR 4.0 KW CHASSIS This power supply is the lower power supply used in the 610-982-00 and 610-983-00 chassis. This supply is also a direct replacement for the 405-391-00 upper power supply used in the 854-991-11 chassis. Note: If upgrading an old design VXI chassis , 611-103-00 Upgrade Kit should be ordered instead of individual supplies.	Consult Factory
969-175-00	FAN TRAY ASSEMBLY	Consult Factory
969-184-00	CONTROL BOARD	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
DI-002-00	DI-SERIES GUIDED PROBE AND CABLE KIT (PANEL MOUNT) Requires Diagnostic Software Package (P/N PS-133-00) Not recommended for new designs	Consult Factory
DI-002-01	DI-SERIES GUIDED PROBE AND CABLE KIT (FLUSH MOUNT) Requires Diagnostic Software Package (P/N PS-133-00) Not recommended for new designs	Consult Factory
DI-002-03	DI-SERIES GUIDED PROBE AND EXTENDED LENGTH CABLE KIT Requires Diagnostic Software Package (P/N PS-133-00) Not recommended for new designs	Consult Factory
DI-002-10	DI-SERIES GUIDED PROBE AND CABLE KIT (PANEL MOUNT) Requires Diagnostic Software Package (P/N PS-133-00)	\$ 3030
DI-002-11	DI-SERIES GUIDED PROBE AND CABLE KIT (FLUSH MOUNT) Requires Diagnostic Software Package (P/N PS-133-00)	Consult Factory
DI-002-13	DI-SERIES GUIDED PROBE AND EXTENDED LENGTH CABLE KIT Requires Diagnostic Software Package (P/N PS-133-00)	\$ 3080
DI-002-14	DI-SERIES GUIDED PROBE AND CABLE KIT Requires Diagnostic Software Package (P/N PS-133-00)	\$ 2190
DI-002-16	DI-SERIES GUIDED PROBE AND CABLE KIT WITH 48" RIBBON CABLE LENGTH Requires Diagnostic Software Package (P/N PS-133-00)	\$ 1990
DI-002-17	DI-SERIES GUIDED PROBE AND EXTENDED LENGTH CABLE KIT Requires Diagnostic Software Package (P/N PS-133-00)	Consult Factory
604-152-50	DI-SERIES PROBE BUFFER CARD Not Recommended for new designs	Consult Factory
604-152-51	DI-SERIES PROBE BUFFER CARD	\$ 1180
621-429-50	DI-SERIES PROBE BUFFER CARD	\$ 1050
M-930-00	DIAGNOSTIC PROBE AND INTERFACE BOARD (PANEL MOUNT) NOTES: <ul style="list-style-type: none">• Requires Diagnostic Software Package (P/N PS-033-00).• If the flush mount model is required, use (P/N M-930-02) instead.	Consult Factory
M-930-02	DIAGNOSTIC PROBE AND INTERFACE BOARD (FLUSH MOUNT) NOTES: <ul style="list-style-type: none">• Requires Diagnostic Software Package (P/N PS-033-00).• If the panel mount model is required, use (P/N M-930-00) instead.	Consult Factory
M-930-03	TETS DIAGNOSTIC PROBE AND INTERFACE BOARD (FLUSH MOUNT) NOTES: <ul style="list-style-type: none">• Requires Diagnostic Software Package (P/N PS-033-00).• If the panel mount model is required, use (P/N M-930-00) instead.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
417-555-00	SPARE DIGITAL PROBE Digital Probe for use with: <ul style="list-style-type: none">• M-930-0x M9 probe and interface board• DI-002-0x DI probe and interface board Note : This is the same as the Field Replaceable part number 853-068-00/853-068-0C	\$ 1030
853-068-00	PROBEMASTER PROBE	Consult Factory
417-555-03	SPARE TETS PROBE BOARD (CT-934)	Consult Factory
859-930-02	PROBE INTERFACE CARD	Consult Factory
859-930-00	PROBE INTERFACE CARD	Consult Factory
M-950-01	M9-SERIES CENTRAL RESOURCE BRD FUNNEL ADAPTER Virginia Panel Fixture Receiver Adapters for Analog VXI Instrumentation. Funnel adapter for Teradyne M-918 Central Resource Board. Fixture receiver adapters are pre-fabricated wiring harness assemblies that connect instrumentation I/O to the test system receiver. Configure one adapter per VXI instrument.	Consult Factory
M-950-02	M9-SERIES 64 CHANNEL FUNNEL ADAPTER Virginia Panel Fixture Receiver Adapters for Analog VXI Instrumentation. Funnel adapter for the Teradyne M-917 64 Channel Channel card. Fixture receiver adapters are pre-fabricated wiring harness assemblies that connect instrumentation I/O to the test system receiver. Configure one adapter per VXI instrument.	Consult Factory
M-950-03	M9-SERIES 48 CHANNEL FUNNEL ADAPTER Virginia Panel Fixture Receiver Adapters for Analog VXI Instrumentation. Funnel adapter for the Teradyne M-927, M-925 and M-921 48 Channel Channel Cards. Fixture receiver adapters are pre-fabricated wiring harness assemblies that connect instrumentation I/O to the test system receiver. Configure one adapter per VXI instrument.	Consult Factory
626-419-00	DI-SERIES 48 CHANNEL MINI COAX FUNNEL ASSEMBLY This funnel assembly contains the Cable Interface Boards (CIBS) and cabling to present signals at the same location as the 48 channel M9-Series channel card. This funnel assembly should be used when M9-Series compatibility is a requirement.	\$ 8980



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
626-421-00	DI-SERIES UTILITY INSTRUMENT MINI COAX FUNNEL ASSEMBLY This funnel assembly contains the Cable Interface Boards (CIBS) and cabling to present signals at the same location as the M9-Series Central Resource Board (CRB). This funnel assembly should be used when M9-Series compatibility is a requirement.t.	\$ 10580
854-994-78	WIRE VERIFICATION TEST (WVT) BLOCK FOR USE WITH DI-SERIES UTILITY INSTRUMENT Teradyne standard WVT test block used by checkers. This test block is compatible with the 626-421-00 mini coax funnel assembly. This part is also included in the S9-U00-FM Di-Series Utility Instrument system integration kit.	Consult Factory
854-994-80	WIRE VERIFICATION TEST (WVT) BLOCK FOR USE WITH 48-CHANNEL DIGITAL TEST INSTRUMENTS Teradyne standard WVT test block used by checkers. This test block is compatible with the 626-419-00 mini coax funnel assembly. This part is also included in the 626-414-00 48 channel Di-Series channel card kit and the S9-D03-FM 48 channel Di-Series system integration kit.	Consult Factory
289-020-00	DI-SERIES UTILITY MODULE TO M9 CABLE CIB	\$ 2330
600-124-50	DI-SERIES UTILITY MODULE TO M9 CABLE CIB	\$ 2040
609-272-00	DI-SERIES TO M917 RIBBON CABLE 64-CHANNEL CIB	\$ 10690
600-689-50	DI-SERIES TO M9 CABLE CIB	\$ 1090
600-689-51	DI-SERIES TO RIBBON CABLE CIB WITH MODULE SIGNALS <ul style="list-style-type: none">• One CIB required for each 32-channel Di-Series Module• Ribbon cable connectors are compatible with M-925 and M-927 channel cables• Compatible with all Di-Series channel cards• Includes additional connector providing module control signals and Calibration Verification signals.	\$ 1140
611-652-50	DI-SERIES CALIBRATION VERIFICATION CIB FOR CHANNEL MODULE	\$ 1450
611-702-50	DI-SERIES CALIBRATION VERIFICATION CIB FOR UTILITY MODULE	\$ 1830



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
613-261-50	DI-SERIES UTILITY INSTRUMENT ENHANCED CIB • Compatible with Di-050-30 (Generation 1) and Di-050-31 (Generation 2) Utility Modules	\$ 2510
613-458-50	DI-SERIES UTILITY MODULE TO M9-SERIES CIB (CABLE INTERFACE BOARD)	\$ 2430
619-565-50	DI 48 CHANNEL CARD TO CABLES LEFT	\$ 1730
619-566-50	DI 48 CH TO CABLES RIGHT	\$ 1560
289-019-0B	DI-SERIES PROBE INTERFACE CIB	\$ 2230
640-038-00	INSTRUMENT CALIBRATION OPTION WITH CALIBRATION DATA For new instrument sales only for select Teradyne Instruments. This option provides calibration data in addition to the calibration certificate and certificate of conformance supplied with all instruments. Requires the purchase of a Teradyne instrument that supports Z540 calibration. Note: For instruments that have a Z540 compliant calibration. If the instruments does not have a Z540 certification the will be a factory calibration with post calibration data only.	\$ 1590
854-994-58	M9 PROBE CABLE	Consult Factory
610-584-51	UPGRADE OF DI-050-22 TO DI-050-12 Upgrade of a Di-050-22 Di-Series 50 MHz 64-Channel Channel Card to the capabilities of a Di-050-12 50 MHz 64-Channel Channel Card. The upgrade increases the available maximum voltage capability from +/- 15V and a 20V swing to +/- 30V and a 30V swing. The Di-050-22 must be returned to Teradyne for upgrading to Di-050-12. Instruments are assumed to be in good working condition (passing full selftest). Does not include repair for failing instruments or calibration data.	\$ 28620
854-993-92	AI-710 RIBBON CABLE 60 INCH	\$ 550



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section F: SOFTWARE OPTIONS		
PS-042-00	<p>TPS CONVERTER STUDIO TRANSLATION SOFTWARE LICENSE</p> <p>Site License for TPS Converter Studio includes 3 weeks of applications time (P/Ns PS-042-00 & 777-464-42 x 3).</p> <p>Translator for L-Series (Program Guide 1.0 VX/3.2 or greater and AX2.02 or greater) :</p> <ul style="list-style-type: none">• Pre-processor to read L-Series text files• Post-processor to ANSI C language• CSHELL L-Series Applications Programming Interface• Site license for both translator and CShell (1 mile radius) <p>Documentation:</p> <ul style="list-style-type: none">• User Documentation• L-Series Language Module Function Reference• Translation Tips <p>Software Support Agreement for one year including:</p> <ul style="list-style-type: none">• Software and documentation updates• Access to Teradyne Support Center• Customer Bulletins	\$ 68500
PS-033-00	<p>M9-SERIES DIAGNOSTIC SOFTWARE LICENSE</p> <p>The M9-Series Diagnostic Software includes Guided Probe Diagnostic and Fault Dictionary Diagnostic software, LSRTAP Importer, SVF reader, and BSID software packages.</p> <p>NOTES:</p> <ul style="list-style-type: none">• All software is shipped on CD ROM media. All SPECTRUM 9000-Series Test Systems and Programming Packages come with the M9-Series Diagnostic Software and the M9-Series VXIplug&play driver.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section H : OTHER OPTIONS		
671-241-00	CABLE, FIREWIRE D38999 QUADRAX TO PCB QUADRAX, J18B	\$ 7960
671-241-01	CABLE, FIREWIRE D38999 QUADRAX TO PCB QUADRAX, J18A	\$ 7960
671-241-03	FIREWIRE D38999 QUADRAX SHORTING PLUG FOR J18A	\$ 8960
671-241-04	FIREWIRE D38999 QUADRAX SHORTING PLUG FOR J18B	\$ 8960
671-383-00	HSSUB-6120 FIREWIRE QUADRAX CIB FOR MEK CABLES, J18A AND J18B	\$ 9560
671-383-01	HSSUB-6120 FIREWIRE QUADRAX CIB	\$ 10430
289-025-00	1553 COUPLING ADAPTER	\$ 1150
601-548-00	MIL-STD CUSTOM PACKAGING Mil-Std custom packaging is available upon request at an additional charge. This charge depends on type of packaging requested. Customers requiring custom packaging should provide their sales engineer with the packaging specifications so that the cost for these requirements may be determined. Packing is priced based on standard 3rd party service pricing policy with a \$500 minimum.	Consult Factory
613-044-50	1773 INTERFACE BOARD	Consult Factory
613-275-00	1773 INTERFACE BOARD MOUNTING BRACKET	Consult Factory
613-566-00	DI & UTILITY CAL & ADVANCED CAPABILITY CABLE There is a miniumum order quantity of 10 pieces for this cable	\$ 12870
613-984-00	3 X AI710 CALIBRATION CABLE ASSEMBLY	\$ 800
615-330-00	50 OHM 64COND TO 2-34COND CABLE	\$ 1080
616-597-00	50OHM 34CON 32"LONG CABLE	\$ 620
616-598-00	CBL ASSY 50OHM 34CON 24"LONG	\$ 2800
616-599-00	DI PROBE RIBBON CBL, 67 IN	\$ 940
619-902-48	SMB TO MINI-COAX DSO CABLE (4 FT)	Consult Factory
637-353-00	KIT, VPC G20 RECEIVER FRAME WITH SPECTRUM INTEGRATION	\$ 16220



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
651-285-00	SWITCH MATRIX INTERCONNECT CABLING AND MACPANEL RECEIVER KIT Includes; • 8 of L-COM FBR01007007020-002m LC Cables Tester to Switch • 1 of Samtec QSFPO-40G-3.0-01-03 QSFP+ to 4 LC 64 of Mac Panel OC161162073275 LC XBEAM, Receiver Cables • 2 of Mac Panel 564441 Receiver Block, Fiber Optic,32 Position	Consult Factory
663-970-10	CABLE, VERTA-3010 QUAD SFP TO QUADRAX 31 IN LENGTH	\$ 5720
663-970-20	CABLE, VERTA-3010 QUAD SFP TO QUADRAX 20 IN LENGTH	\$ 4610
663-971-10	CABLE, VERTA-3010 EXPANDED BEAM FIBER OPTIC TO DUPLEX LC 31 IN LENGTH	\$ 11280
663-971-20	CABLE, VERTA-3010 EXPANDED BEAM FIBER OPTIC TO DUPLEX LC 20 IN LENGTH	\$ 16380
663-972-10	CABLE, VERTA-5010 EXPANDED BEAM FIBER OPTIC TO DUPLEX LC 36 IN LENGTH	\$ 11120
671-241-10	CABLE, AS5643 FIREWIRE D38999 QUADRAX TO PCB QUADRAX 1394B 18.5 IN, W/ CONN	\$ 7960
671-241-11	CABLE, AS5643 FIREWIRE D38999 QUADRAX TO PCB QUADRAX 1394B 18 IN, W/ CONN	\$ 7960
696-476-00	1394B QUADRAX TO VTAC ICON CONNECTOR CABLE	\$ 13810
707-641-00	FIREWIRE QUADRAX TO ICON QUADRAPADDLE CABLE, 24 IN	\$ 15430
651-286-00	SWITCH MATRIX FVT ITA KIT Includes; • 2 of Mac Panel 564442/ OC 165 165 073 012 Loopback ITA Blocks	Consult Factory
651-313-00	AI-762-20 NGATS LRIP SYSTEM UPGRADE KIT The Ai-762-20 NGATS LRIP Station Upgrade Kit includes cables to integrate the DMM and MFA of the Ai-762-20 into the LRIP Switching Subsystem and an MFA ATTENUATOR CIB (P/N 628-525-00) for the Ai-762-20.	Consult Factory
664-940-00	NGATS SPARES KIT The NGATS Spares Kit includes: (1) AI-710-00 (1) AI-762-20 (1) BI-411-00 (1) DI-050-31 (1) DI-050-63	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
664-940-01	NGATS SPARES KIT PACKAGE The NGATS Spares Kit Package includes : (10) Ai-762-20 (7) Bi-411-00 (10) DI-050-31 (5) Di-050-63	Consult Factory
662-203-03	CABLE, LVDS D38999 HERCULES J1 SHORTING PLUG	\$ 6170
662-203-04	CABLE, LVDS D38999 HERCULES J2 SHORTING PLUG	\$ 6360
662-374-00	CABLE, LVTTTL TO D38999 HERCULES	\$ 15690
662-374-03	CABLE, LVTTTL #1 D38999 HERCULES SHORTING PLUG	\$ 7110
859-991-00	CIB BTI COSSI	Consult Factory
977-288-06	SSMB TO SMB CABLE (4 FT)	Consult Factory
977-288-07	SSMB TO SMB CABLE (5 FT)	Consult Factory
987-602-01	BT-025 BOARD COVER	\$ 140
602-613-00	CSI CABLE TIE-DOWN KIT FOR VXI INSTRUMENTS Strain relief bracket for use with Teradyne's Ai-Series, Bi-Series, and Di-Series test instrumentation. Kit contains the following items: (1) Strain relief bracket (4) attachment screws (24) plastic tie wraps	Consult Factory
CU-500-00	SHIPPING & FREIGHT CHARGES	Consult Factory
CU-500-10	SETUP AND TOOLING CHARGED	Consult Factory
NRE-000-10	DESIGN ENGINEERING LABOR FOR INSTRUMENTATION Price is per hour	\$ 420



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
NRE-000-15	TRAVEL EXPENSES FOR FACTORY BASED PERSONNEL NOTES: <ul style="list-style-type: none">• The travel time will be charged at the current hourly rate.• If air travel is required additional air fare and per diem charges will apply. For travel in the US and Canada, per diem charges will be \$1000.00/each for the first and last day of travel.<ul style="list-style-type: none">• \$1000.00 if travel to/from occur within one day.• \$2000.00 if two days involve travel• This includes first and last day of expenses and air fare with 7 days notice.• International travel will be charged at actual rates• A Flat Rate of \$350.00/day will be charged for per diem for the days spent after first and before the last day of travel.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section I: SERVICE AGREEMENTS		
777-407-00	<p>ADVANCED REPLACEMENT AGREEMENT (ARA) - INSTRUMENTATION AND SUB-SYSTEMS</p> <p>The Advanced Replacement Agreement is a fixed price agreement available in the first year of ownership and beyond. This agreement provides customers with advanced repair and replacement services for Teradyne parts for a fixed annual rate.</p> <p>Annual Coverage [per system] Includes:</p> <ul style="list-style-type: none">• SDS (Same Day Ship Shipment)• BPS (Basic Parts Service - 5 Day TAT)• MPS (Mature Parts Service 20 Day TAT)• EWAP (Exact Swap Service 60 Day TAT) <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p> <p>* Ship services will be best available, same day if possible. ** For further definition of deliverables, please refer to the ATD Service & Support Supplement Doc.</p> <p>NOTES:</p> <ol style="list-style-type: none">1) Advanced part shipments for Teradyne manufactured equipment should be used only if a replacement part is not available on-site.2) Failures caused by environmental conditions, misuse of the product, or programming errors are not covered under the ARA or PRA.3) For SDS orders, the customer must return the defective part within five days of receipt of the replacement part.4) Throughout the term of the ARA or PRA, Teradyne will perform account management to monitor part replenishment orders. As a partnership, Teradyne will work with the customer to develop a corrective action plan that brings these activities to their expected levels. However, if the customer does not fulfill their part of the corrective action plan and parts and labor usage continues at a high rate, Teradyne reserves the right to terminate this agreement.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-PRA-LO	<p>PARTS REPAIR AGREEMENT (PRA) - FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEMS</p> <p>The Parts Repair Agreement (PRA) is a fixed price agreement. It is an annual agreement that includes the return and repair service (R&R) whereby the customer returns a defective part to a Teradyne Stocking Center and a form, fit and function replacement part is shipped to the customer within 20 business days of Teradyne's receipt of the defective part.</p> <p>**Annual Coverage [per system] Includes:</p> <ul style="list-style-type: none">• *MPS (Mature Parts Service 20 Day TAT)• ESWP (Exact Swap Parts Service 60 Day TAT) <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p> <p>* Ship services will be best available, same day if possible. ** For further definition of deliverables, please refer to the ATD Service & Support Supplement Doc.</p> <p>NOTES:</p> <ol style="list-style-type: none">1) Advanced part shipments for Teradyne manufactured equipment should be used only if a replacement part is not available on-site.2) Failures caused by environmental conditions, misuse of the product, or programming errors are not covered under the ARA or PRA.3) If it does become necessary to expedite a part, the repair portion is covered under the agreement and the advanced replacement service charge is invoiced separately.4) Throughout the term of the ARA or PRA, Teradyne will perform account management to monitor part replenishment orders. As a partnership, Teradyne will work with the customer to develop a corrective action plan that brings these activities to their expected levels. However, if the customer does not fulfill their part of the corrective action plan and parts and labor usage continues at a high rate, Teradyne reserves the right to terminate this agreement.5) This PRA does not cover any non-standard (custom) instruments that are part of the system. A separate custom quotation is required for those items.6) For parts beyond formal support period, commercially reasonable efforts will be used to attempt repair. If the part is determined to be Beyond Economic Repair it will be returned to the customer unrepai7) Parts that are out of support are not covered under this agreement. They will be returned to the customer unrepai	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-391-44	<p>COMPREHENSIVE SUPPORT AGREEMENT (CSA) - FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEMS</p> <p>The Comprehensive Support Agreement is a variable contract with a value based upon historical and estimated annual usage. This agreement provides discounts and preference associated with contract customer status yet provides price flexibility based on a given customers usage.</p> <p>Invoices are issued quarterly and include a 7% discount on replaceable parts and labor. Labor billing is based on prevailing hourly rates. At any point during the life of the contract, usage exceeding the contract value will require an amended PO to cover the additional costs. If at the end of the contract period there are remaining funds available, then these funds may be used to purchase additional support items, or to extend the term of the contract.</p> <p>Flexible benefits include:</p> <ul style="list-style-type: none">• 7% Discount on replaceable parts• Quarterly billing• Applies to emergency on-site and calibration services• All Parts Services available for that part, including *SDS (Same Day Ship Service) <p>*Ship services will be best available, same day if possible.</p> <p>***Software Support sold separately</p> <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p>	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-ESR-LO	<p>EXACT SWAP AND REPLACEMENT AGREEMENT (ESRA) FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEMS</p> <p>The parts Exact Swap and Replacement Agreement (ESRA) is a fixed price agreement . For Teradyne manufactured instruments the agreement includes return and repair service (MPS), whereby the customer returns a defective part to a Teradyne Stocking Center and a form, fit and function replacement part is shipped to the customer within 20 business days of Teradyne's receipt of the defective part. If it does become necessary to expedite a part, the repair portion is covered under the agreement and the advanced replacement service charge is invoiced separately. For Teradyne pricelist OEM Hardware the agreement includes exact swap replacement (ESWP), whereby the customer receives back the same instrument sent in for repair.</p> <p>Coverage [per system] Includes:</p> <ul style="list-style-type: none">• MPS (Mature Parts Service)*• ESWP (Exact Swap) <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p> <p>*For Teradyne pricelist instruments only.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Ship services will be best available.	<p>\$ 3.5 % of List Price</p>



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-831-22	<p>CUSTOM SOFTWARE SUPPORT AGREEMENT (SSA) - FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEMS</p> <p>The Software Support Agreement (SSA) is a comprehensive support plan to help you optimize your test and inspection programs through a combination of rapid telephone support, 24 / 7 web support, and periodic software releases.</p> <p>The Custom Software Agreement is an a-la-carte service intended for customers who have requirements outside of our standard Software Support Agreement.</p> <p>**Annual Coverage (per system) Includes:</p> <ul style="list-style-type: none">• Response time <2 hours (telephone)• Phone support/1-800-TERADYNE or local regional support office (Europe and Asia) available during normal business hours.• *eKnowledge access• Software Releases• Free Software License Key Transfers• Remote Diagnostics (if available) <p>* With the purchase of an SSA you will be eligible for an eKnowledge account. eKnowledge is Teradyne's 24/7 support website. For more information about eKnowledge, or to obtain an account, visit our support website at: http://www.teradyne.com/atd/support/eknowledge.html</p> <p>** For further definition of deliverables, please refer to the ATD Service & Support Supplement Doc.</p> <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p> <p>NOTES:</p> <ul style="list-style-type: none">• Must renew before expiration date to avoid reinstatement fee.	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section J : SERVICES & SUPPORT OFFERINGS		
777-305-19	FIELD SERVICE LABOR - INSTRUMENTS Hourly price for on-site labor. NOTES: <ul style="list-style-type: none">• Quote based on estimated costs, customer will be invoiced based on actual charges.• Any Replacement parts will require additional funding.• Please reference the System Serial number to be serviced on any purchase order	\$ 420
777-310-19	FIELD SERVICE TRAVEL - INSTRUMENTS NOTES: <ul style="list-style-type: none">• The travel time will be charged at the current hourly rate.• If air travel is required additional air fare and per diem charges will apply. For travel in the US and Canada, per diem charges will be \$1000.00/each for the first and last day of travel.<ul style="list-style-type: none">• \$1000.00 if travel to/from occur within one day.• \$2000.00 if two days involve travel• This includes first and last day of expenses and air fare with 7 days notice.• International travel will be charged at actual rates• A Flat Rate of \$350.00/day will be charged for per diem for the days spent after first and before the last day of travel.	Consult Factory
777-320-19	APPLICATIONS LABOR - INSTRUMENTS Hourly price for on-site labor.	\$ 400
777-463-44	APPLICATIONS ASSISTANCE ONE DAY (AA/1) - FUNCTIONAL TEST INSTRUMENTATION One-day Applications Assistance offers on-site applications assistance in one-day increments for system operation, program creation, and debugging. This offering gives our customers the ability to have Teradyne Engineers assist with all stages of the test process including evaluation of a new or existing test process and operation, consultation on test techniques, and application of new test equipment or methods. NOTES: <ul style="list-style-type: none">• Travel charges not included.	\$ 3110



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-325-19	APPLICATIONS ASSISTANCE FIVE DAYS (AA/5) - FUNCTIONAL TEST INSTRUMENTATION <p>Five day Applications Assistance offers on-site applications assistance in five-day increments. This offering gives our customers the ability to have Teradyne Engineers assist with all stages of the test process including evaluation of a new or existing test process and operation, consultation on test techniques, and application of new test equipment or methods. Customers can request service on a one-time basis, contract for long-term assistance with multiple on-site visits, or define a specific project for completion by Teradyne.</p> NOTES: <ul style="list-style-type: none">• Travel charges for one trip per week is included.	\$ 16380
777-315-19	APPLICATIONS TRAVEL - INSTRUMENTS NOTES: <ul style="list-style-type: none">• The travel time will be charged at the current hourly rate.• A Flat Rate of \$350.00/day will be charged for per diem for travel requiring an overnight stay• If air travel is required additional air fare and per diem charges will apply. For travel in the US and Canada, per diem charges will be \$1000.00/each for the first and last day of travel.<ul style="list-style-type: none">• \$1000.00 if travel to/from occur within one day.• \$2000.00 if two days involve travel• This includes first and last day of per diem expenses and assumes air fare with 7 days notice.• International travel will be charged at actual rates	Consult Factory
777-345-80	APPLICATIONS LABOR - HIGH SPEED SUBSYSTEM - HOURLY Hourly price for on-site labor.	\$ 400
777-463-80	APPLICATIONS ASSISTANCE ONE DAY (AA/1) - HIGH SPEED SUBSYSTEM <p>One-day Applications Assistance offers on-site applications assistance in one-day increments for system operation, program creation, and debugging. This offering gives our customers the ability to have Teradyne Engineers assist with all stages of the test process including evaluation of a new or existing test process and operation, consultation on test techniques, and application of new test equipment or methods.</p> NOTES: <ul style="list-style-type: none">• Travel charges not included.	\$ 3110



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-464-80	<p>APPLICATIONS ASSISTANCE FIVE DAYS (AA/5) - HIGH SPEED SUBSYSTEM</p> <p>Five day Applications Assistance offers on-site applications assistance in five-day increments. This offering gives our customers the ability to have Teradyne Engineers assist with all stages of the test process including evaluation of a new or existing test process and operation, consultation on test techniques, and application of new test equipment or methods. Customers can request service on a one-time basis, contract for long-term assistance with multiple on-site visits, or define a specific project for completion by Teradyne.</p> <ul style="list-style-type: none">• Pricing includes travel&per diem charges within the US., For Overseas classes travel will be billed at actual rates	\$ 16380



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-482-20	<p>PRODUCT AND SOFTWARE SUPPORT AGREEMENT (PSSA/2) - HSSUB</p> <p>This is a one-year all-inclusive Product & Software Support Agreement (PSSA) that combines hardware and software support intended for customers who wish to maintain Teradyne's test equipment themselves, and use our technical support services as needed. It combines a Hotline & Software Support Agreement (HSSA) with 24 x 7 telephone and web-based support, fast parts replacement and repair services, as well as next day response for on-site support. See details below.</p> <p>**Annual Coverage [per system] Includes:</p> <ul style="list-style-type: none">• Phone Support/1 877 TERADYNE or local regional support office (Europe and Asia) available during normal business hours• On-site Field Service Support• Emergency Visits / Remedial Repair• Advanced Part Repair Services as available• Software Releases• *eKnowledge access <p>* With the purchase of a PSSA customers will be eligible for an eKnowledge account. eKnowledge is Teradyne's 24/7 support website. For more information about eKnowledge, or to obtain an account, visit our support website at: http://www.teradyne.com/atd/support/eknowledge.html</p> <p>. ** For further definition of deliverables, please refer to the ATD Service & Support Supplement Doc.</p> <p>COVERAGE PERIOD: DD-MMM-YYYY through DD-MMM-YYYY FOR S/N: TBD</p> <p>Notes :</p> <ul style="list-style-type: none">• Annual Instrument Calibration is not included• For parts beyond formal support period, commercially reasonable efforts will be used to attempt repair. If the part is determined to be Beyond Economic Repair it will be returned to the customer unrepared• Parts that are out of support are not covered under this agreement.	\$ Five % of List



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section K: TRAINING		
777-160-31	TRAINING IN HOUSE - AI-710 SERIES WORKSHOP Course Description: In this workshop you will learn the architecture of the Ai7-Series product, capability and the basic skills needed to begin using the subsystem in analog functional test development. The workshop uses the C-API functions that are provided with the instrument driver to program the instrument. Course Content (Emphasis on the following subject areas) Ai-7 Series product architecture and software, including: <ul style="list-style-type: none">• Overview• Operation and verification• Trigger subsystem• Sourcing stimulus<ul style="list-style-type: none">• DC Voltage• Pulse Current• Arbitrary Waveforms• Measurements<ul style="list-style-type: none">• DC Voltage• DC Current• Frequency and Time interval• Limit Detect• Digitizing• Interrupts and Interrupt handling Course Duration: 3 days Prerequisite(s): C/C++ Programming NOTES: <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 2760



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-175-31	<p>TRAINING IN HOUSE - HSSUB TPS TRAINING</p> <p>Course Description: The HSSub TPS Training provides the student with introductory information necessary for developing, debugging and executing a subTPS on the HSSub. The course emphasis is concepts and architecture of the High Speed Subsystem. These concepts are then applied by creating programs written in C++. The course will use the High Speed Subsystem with HSSub-5010, HSSub-eDigital 6020A or FIOXI instrument with an RS232 or RS422/RS485 PIM for lab purposes. The concepts learned apply to other Core and/or IO Expansion instruments.</p> <p>Course Content (Emphasis on the following subject areas) High Speed Subsystem Test Architecture, program development and integration:</p> <ul style="list-style-type: none">• Introduction to HSSub Architecture• Hardware Overview• Software Overview• HSSub Basic Programming• HSSub App and Driver Usage <p>Course Duration: 3 days</p> <p>Prerequisite(s): General Programming Concepts C/C++ Programming Digital Applications Familiar with Visual Studio C/C++</p> <p>NOTES:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 2760



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-176-31	<p>TRAINING IN HOUSE - HSSUB APP TRAINING</p> <p>Course Description: The High Speed Subsystem Application Development Training provides the student with introductory information necessary for developing custom High Speed Subsystem Applications (HSSub Apps).</p> <p>The course will cover a high-level overview of the architecture of the HSSub instrument, identifying differences between Core and IO Expansion instruments and describing Test Defined FPGA (TDF) features. The included FPGA development tools will be explained and demonstrated.</p> <p>The Application Interface overview will cover the basic components of an HSSub App, the development process and demonstration of an HSSub App with the LED Training Kit. The Application Interface section will also cover high level concepts including data transfer and hardware interrupts. The concepts here will be applied by using and modifying the LED Training Kit Application Interface code written in C.</p> <p>Course Content (Emphasis on the following subject areas) Advanced HSSub TPS development focused on HSSub App development</p> <ul style="list-style-type: none">• Architecture Overview• HSSub TDF Introduction• HSSub TDF Advanced Topics• HSSub App Interface Introduction• HSSub App Interface Advanced Topics <p>Course Duration: 3 days</p> <p>Prerequisite(s): Must have already taken the HSSub TPS Training Advanced programming concepts C/C++ Programming Digital Applications Familiar with Visual Studio C/C++ Familiar with a Hardware Description Language (VHDL or Verilog) if future FPGA support or development activities are planned</p> <p>NOTES:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 2760



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-177-31	<p>TRAINING IN HOUSE - HSSUB MAINTENANCE TRAINING</p> <p>Course Description: HSSub Hardware Management, Maintenance and Troubleshooting provides the student with the information necessary to setup, configure and manage the HSSub Test System. The different components of the HSSub Test System are examined and troubleshooting techniques are taught to identify and isolate failures. Procedures are outlined for maintaining the operation of the test system.</p> <p>Course Content (Emphasis on the following subject areas) High Speed Subsystem Test Architecture, program development and integration</p> <ul style="list-style-type: none">• Identify hardware components of HSSub Test System• Identify and isolate failures with the HSSub• Run self-test procedures• Properly maintain HSSub Test System <p>Course Duration: 1 day</p> <p>Prerequisite(s): Hardware experience maintaining and troubleshooting complex electronic equipment.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities• Minimum class size 3 students	\$ 1380



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-160-33	<p>TRAINING IN HOUSE - AI-76X SERIES WORKSHOP</p> <p>Course Description: This course introduces the Ai-76x Series of analog test instrument. Emphasis is placed on typical source and measure applications using the DMM, the DSO, and MFA modules, implemented using the Analog Test Editor (a graphical user interface) and also using the C-API (Application Programming Interface). The MFA (Multi-function Analog) module includes Timer/Counter, Waveform Generator (standard and arbitrary) and Digitizer. The course is instructor-led with associated hands-on lab exercises.</p> <p>Course Content (Emphasis on the following subject areas) Ai-76x Series architecture and software programming, including:</p> <ul style="list-style-type: none">• General Introduction<ul style="list-style-type: none">• Hardware Architecture• Software Architecture• IVI Drivers• Ai-760 Help Reference and Examples• IVI configuration using MAX• C-API Programming<ul style="list-style-type: none">• Digital Multimeter (DMM)• Digital Sampling Oscilloscope (DSO)• Multifunction Analog (MFA)<ul style="list-style-type: none">• MFA Standard/Predefined Waveform Generation• MFA Arbitrary Waveform Generation• MFA Timer/Counter• MFA Digitizer• The graphical user interface (Analog Test Editor) <p>Course Duration: 5 days</p> <p>Prerequisite(s): C/C++ Programming</p> <p>NOTES:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 4600



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-170-31	<p>TRAINING IN HOUSE - BI-4 WORKSHOP</p> <p>Course Description: This course introduces the Bi-4 Series family of bus test instruments. Emphasis is placed on programming the Bi-4 Series to transmit and receive data and perform bus testing, including error injection and detection, caching, and fetching status and data. The two protocols focused on in this training are RS232 and 1553.</p> <p>Course Content (Emphasis on the following subject areas): BTI Programming and Integration, including:</p> <ul style="list-style-type: none">• Hardware Architecture overview• Software API Overview• Transmitting data (RS232 protocol)• Receiving data (RS232 protocol)• Bus testing• 1553 Protocol <p>Course Duration: 3 days</p> <p>Prerequisite(s): General programming concepts C/C++ C Programming</p> <p>NOTES:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 2760



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-180-31	<p>TRAINING IN HOUSE - DI-SERIES PROGRAMMING CLASS</p> <p>Course Description:</p> <p>The Di-Series Consolidated Programming training provides the student with the information necessary for developing, debugging and executing a digital test program using iStudio Digital Test Editor and exporting the debugged program to ANSI C. In addition, the information necessary for developing, debugging and executing a digital test program using IVI-C application program interface (API) functions is also covered.</p> <p>The course emphasis is on teaching fundamental digital testing concepts such as static and dynamic patterns, pattern sets, op-codes, formats, timing, phases and windows. These concepts are then applied by creating a PASS/FAIL test program that will test the functionality of a training board. The course then advances to using the IVI-C API functions to develop the same program with the additional information on retrieving and presenting failure information.</p> <p>The course will use a Di-Series DTI for lab purposes. The concepts learned apply to other Di-Series Digital Test Instruments.</p> <p>Course Content (Emphasis on the following subject areas)</p> <p>iStudio Digital Test Editor</p> <ul style="list-style-type: none">• Developing a digital test program• Fundamental concepts of Digital Testing• Constructing an iStudio project• Exporting the debugged program to ANSI C• Executing a digital test program to functionally test a UUT• IVI-C application program interface (API) functions• Developing a digital test program• Debugging a digital test program using C/C++ <p>Course Duration:</p> <ul style="list-style-type: none">• 5 days <p>Prerequisite(s):</p> <ul style="list-style-type: none">• General programming concepts• Digital applications• C/C++ Programming <p>Notes:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 4600



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-180-41	<p>TRAINING IN HOUSE - DI-SERIES DIAGNOSTICS PROGRAMMING CLASS</p> <p>Course Description: The CSI Diagnostics with Di-Series training provides the student with the a procedure for converting, using the LSRTAP to CShell Converter, a LASARTM developed digital test with diagnostics and post processed to IEEE 1445 standard (LSRTAP) to run on the Di-Series DTI. The course covers the software tools used in converting, executing and debugging the LASAR generated Go/Nogo test, verifying the diagnostic data and integration into TestStudio. The course will use a Di-Series DTI for lab purposes. The concepts learned apply to other Di-Series Digital Test Instruments.</p> <p>Course Content (Emphasis on the following subject areas): CSi Diagnostics software tools and architecture, including:</p> <ul style="list-style-type: none">• Introduction to CShell• Introduction to Digital Runtime• LSRTAP to CShell Converter• Fault Dictionary Diagnostics• Guided Probe Diagnostics• TestStudio Integration <p>Class Duration: 3 days</p> <p>Prerequisite(s):</p> <ul style="list-style-type: none">• Must have taken the Di-Series Consolidated Programming course• Familiar with Di-Series DTI and test development tools• Familiar with Visual Studio C/C++• Familiar with TestStudio• Familiar with LASAR <p>Notes:</p> <ul style="list-style-type: none">• Price is per student• Courses conducted at Teradyne facilities	\$ 2760



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-160-32	<p>ON SITE TRAINING - AI-71X WORKSHOP CLASS - MAXIMUM 6 STUDENTS</p> <p>Course Description: In this workshop you will learn the architecture of the Ai7-Series product, capability and the basic skills needed to begin using the subsystem in analog functional test development. The workshop uses the C-API functions that are provided with the instrument driver to program the instrument.</p> <p>Course Content (Emphasis on the following subject areas) Ai-7 Series product architecture and software, including:</p> <ul style="list-style-type: none">• Overview• Operation and verification• Trigger subsystem• Sourcing stimulus<ul style="list-style-type: none">• DC Voltage• Pulse Current• Arbitrary Waveforms• Measurements<ul style="list-style-type: none">• DC Voltage• DC Current• Frequency and Time interval• Limit Detect• Digitizing• Interrupts and Interrupt handling <p>Course Duration: 3 days</p> <p>Prerequisite(s): C/C++ Programming</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 13650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-160-34	<p>ON SITE TRAINING - AI-76X WORKSHOP CLASS - MAXIMUM 6 STUDENTS</p> <p>Course Description: This course introduces the Ai-76x Series of analog test instrument. Emphasis is placed on typical source and measure applications using the DMM, the DSO, and MFA modules, implemented using the Analog Test Editor (a graphical user interface) and also using the C-API (Application Programming Interface). The MFA (Multi-function Analog) module includes Timer/Counter, Waveform Generator (standard and arbitrary) and Digitizer. The course is instructor-led with associated hands-on lab exercises..</p> <p>Course Content (Emphasis on the following subject areas) Ai-76x Series architecture and software programming, including:</p> <ul style="list-style-type: none">• General Introduction<ul style="list-style-type: none">• Hardware Architecture• Software Architecture• IVI Drivers• Ai-760 Help Reference and Examples• IVI configuration using MAX• C-API Programming<ul style="list-style-type: none">• Digital Multimeter (DMM)• Digital Sampling Oscilloscope (DSO)• Multifunction Analog (MFA)<ul style="list-style-type: none">• MFA Standard/Predefined Waveform Generation• MFA Arbitrary Waveform Generation• MFA Timer/Counter• MFA Digitizer• The graphical user interface (Analog Test Editor) <p>Course Duration: 5 days</p> <p>Prerequisite(s): C/C++ Programming</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 22830



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-175-32	<p>ON SITE TRAINING - HSSUB TPS TRAINING - MAXIMUM 6 STUDENTS</p> <p>Course Description: The HSSub TPS Training provides the student with introductory information necessary for developing, debugging and executing a subTPS on the HSSub. The course emphasis is concepts and architecture of the High Speed Subsystem. These concepts are then applied by creating programs written in C++. The course will use the High Speed Subsystem with HSSub-5010, HSSub-eDigital 6020A or FIOXI instrument with an RS232 or RS422/RS485 PIM for lab purposes. The concepts learned apply to other Core and/or IO Expansion instruments.</p> <p>Course Content (Emphasis on the following subject areas) High Speed Subsystem Test Architecture, program development and integration:</p> <ul style="list-style-type: none">• Architecture Overview• Hardware Overview• Software Overview• HSSub Basic Programming• HSSub App and Driver Usage <p>Course Duration: 3 days</p> <p>Prerequisite(s): C/C++ Programming Digital Applications Familiarity with Visual Studio C/C++</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 13650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-175-33	<p>TRAINING IN HOUSE - HSSUB RTSCRIPT PROGRAMMING</p> <p>Course Description: The HSSub RTScript Programming Course provides the student with the information necessary for developing, debugging and executing RTScript programs. In addition, the student will learn how to use the RTScript editor and be able to describe what RTScript is and how it works. The course identifies HSSub App development scenarios where the use of RTScript is appropriate for Real-Time development instead of the TriFlex Real-Time driver APIs and VxWorks. The course will use an HSSub-eDigital 6020A or HSSub-6020 along with the LED training kit, part of the Test Development Kit (TDK), for lab purposes. The concepts learned apply to other HSSub instruments with application specific firmware. The target audience for this course is an HSSub customer looking for RTScript programming experience as part of HSSub App development. The training exercises use Visual C++ along with the RTScript editor and the RTScript language.</p> <p>Course Content (Emphasis on the following subject areas): HSSub RTScript Programming Training includes:</p> <ul style="list-style-type: none">• RTScript Basics• RTScript Extension with the Application Framework• RTScript Error Handling and DMA <p>Course Duration: 2 days</p> <p>Prerequisite(s): Courses: 1. HSSub TPS Programming Course 2. HSSub App Development Course Experience with: 1. Digital applications 2. General programming concepts 3. Familiarity with C/C++</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Training is conducted using the most current level of software and the standard training material.• Consult the training manager for special requirements for lab exercises.	\$ 1970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-175-40	<p>ON SITE TRAINING - REMOTE TEST HEAD TRAINING AND SUPPORT - MAXIMUM 6 STUDENTS</p> <p>Course Description: This class covers the Spectrum HSSub Remote Test Head (RTH) with a focus on the SlimRTH and the HSSub-6140 8G Hybrid instrument.</p> <p>In addition to the on-site training class Teradyne will provide one week of on-site support (PN 777-325-19) for RTH Test implementation.. This applications time must be used within 90 days of the completion of the training.</p> <p>Course Content (Emphasis on the following subject areas)</p> <ul style="list-style-type: none">• Overview• Hardware• Software• Front Panel Pinouts• Differences between (6020 & 6040) and 6140• Remote Test Head (RTH)• Checkers• Loopback Testing• Boundary Scan using HSSub-6140• FPGA migration from LVTTL & Hybrid to HSSub-6140 <p>Course Duration: 3 days</p> <p>Prerequisite(s): C/C++ Programming</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Pricing includes travel & per diem charges for Teradyne Applications Engineer for one wee of on-site Test implementation support..• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab exercises require a working SlimRTH and HSSub	\$ 30010



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-176-32	<p>ON SITE TRAINING - HSSUB APP TRAINING - MAXIMUM 6 STUDENTS</p> <p>Course Description: The High Speed Subsystem Application Development Training provides the student with introductory information necessary for developing custom High Speed Subsystem Applications (HSSub Apps).</p> <p>The course will cover a high-level overview of the architecture of the HSSub instrument, identifying differences between Core and IO Expansion instruments and describing Test Defined FPGA (TDF) features. The included FPGA development tools will be explained and demonstrated.</p> <p>The Application Interface overview will cover the basic components of an HSSub App, the development process and demonstration of an HSSub App with the LED Training Kit. The Application Interface section will also cover high level concepts including data transfer and hardware interrupts. The concepts here will be applied by using and modifying the LED Training Kit Application Interface code written in C.</p> <p>Course Content (Emphasis on the following subject areas) Advanced HSSub TPS development focused on HSSub App development:</p> <ul style="list-style-type: none">• Architecture Overview• HSSub TDF Introduction• HSSub TDF Advanced Topics• HSSub App Interface Introduction• HSSub App Interface Advanced Topics <p>Course Duration: 3 days</p> <p>Prerequisite(s):</p> <ul style="list-style-type: none">• Must have already taken the HSSub TPS Training• C/C++ Programming• Digital Applications• Advanced programming concepts• Familiar with Visual Studio C/C++• Familiar with a Hardware Description Language (VHDL or Verilog) if future FPGA support or development activities are planned <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab exercises have certain system configuration requirements. Consult the training	\$ 13650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	manager for special requirements.	
777-177-32	ON SITE TRAINING - HSSUB MAINTENANCE TRAINING - MAXIMUM 6 STUDENTS Course Description: HSSub Hardware Management, Maintenance and Troubleshooting provides the student with the information necessary to setup, configure and manage the HSSub Test System. The different components of the HSSub Test System are examined and troubleshooting techniques are taught to identify and isolate failures. Procedures are outlined for maintaining the operation of the test system.. Course Content (Emphasis on the following subject areas) High Speed Subsystem hardware maintenance and troubleshooting: <ul style="list-style-type: none">• Identify hardware components of HSSub Test System• Identify and isolate failures with the HSSub• Run self-test procedures• Properly maintain HSSub Test System Course Duration: 1 day Prerequisite(s): <ul style="list-style-type: none">• Hardware experience maintaining and troubleshooting complex electronic equipment. Notes: <ul style="list-style-type: none">• Six Students maximum• Customer provides HSSub system and selftest adaptor.• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 6470



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-178-32	<p>ON SITE TRAINING - HSSUB-AK TPS TRAINING - MAXIMUM 6 STUDENTS</p> <p>Course Description: The course emphasis is on TPS techniques and developing HSSub-AK used in the CASS Family of Testers</p> <p>Course Content (Emphasis on the following subject areas)</p> <p>Basic understanding of an HSS</p> <ul style="list-style-type: none">• System Layout• Instrumentation Content with Specifications• Documentation• Software Overview (Tri-Flex software, HSSub Apps, Tools, System Manager Client, eDigital, Boundary Scan Runtime,, Debug methods and tools <p>TPS Development process and description of the FEP</p> <p>SubTPS development</p> <ul style="list-style-type: none">• Review Test Development Kit• Creating a SubTPS• Debug Methods and Tools• Review Ethernet API• Review RS API - RS-232/422/485• Review IRIG-B API• Review FC-RDMA API• Review FC-AV API• Review SMPTE 292 API• Review eDigital API• Review Boundary Scan API <p>Course Duration: 5 days</p> <p>Prerequisite(s): C/C++ Programming Digital Applications Advanced programming concepts Familiarity with Visual Studio C/C++</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements including MS Visual Studio license installed and access to CASS station and HSSub-AK system	\$ 13650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #

DESCRIPTION

LIST PRICE



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-179-32	<p>ON SITE TRAINING - HSSUB-AK APP TRAINING - MAXIMUM 6 STUDENTS</p> <p>Course Description: The course emphasis is on HSS APP Development techniques and developing HSSub-AK used in the CASS Family of Testers</p> <p>Course Content (Emphasis on the following subject areas)</p> <p>Basic understanding of an HSS</p> <ul style="list-style-type: none">• System Layout• Instrumentation Content with Specifications• Documentation• Software Overview (Tri-Flex software, HSSub Apps, Tools, System Manager Client, eDigital, Boundary Scan Runtime) <p>HSSub App development</p> <ul style="list-style-type: none">• How to use Test Development Kit• Creating HSSub Apps• Debug methods and tools <p>FPGA development -</p> <ul style="list-style-type: none">• Converting existing VHDL code to run on eDigital FPGA• How to use FPGA Developer's assistant• Mandatory vs Recommended Code• Review Current Examples <p>Real-time Development -</p> <ul style="list-style-type: none">• Introduction to RTScript <p>Course Duration: 5 days</p> <p>Prerequisite(s): C/C++ Programming Digital Applications Advanced programming concepts Familiarity with Visual Studio C/C++ Familiarity with a Hardware Description Language (VHDL or Verilog)</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements including MS Visual Studio and Xilinx ISE installed and access to CASS station and HSSub-AK system	\$ 22830



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-160-35	ON SITE TRAINING - AI-71X WORKSHOP CLASS - ADDITIONAL STUDENT This is the incremental cost of adding a student to an AI-71x class configured for 6 students. NOTES: <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 2390
777-160-36	ON SITE TRAINING - AI-76X WORKSHOP CLASS - ADDITIONAL STUDENT This is the incremental cost of adding a student to an Ai-76x class configured for 6 students. NOTES: <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 3970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-170-32	<p>ON SITE TRAINING - BI4 WORKSHOP - MAXIMUM 6 STUDENTS</p> <p>Course Description: This course introduces the Bi-4 Series family of bus test instruments. Emphasis is placed on programming the Bi4 Series to transmit and receive data and perform bus testing, including error injection and detection, caching, and fetching status and data. The two protocols focused on in this training are RS232 and 1553.</p> <p>Course Content (Emphasis on the following subject areas:) BTI Programming and Integration, including:</p> <ul style="list-style-type: none">• Hardware Architecture overview• Software API Overview• Transmitting data (RS232 protocol)• Receiving data (RS232 protocol)• Bus testing• 1553 Protocol <p>Course Duration: 5 days</p> <p>Prerequisite(s): C/C++ Programming</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 22830
777-170-35	<p>ON SITE TRAINING - BI4 WORKSHOP - ADDITIONAL STUDENT</p> <p>This is the incremental cost of adding a student to a class configured for 6 students.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 3970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-103-44	<p>ON SITE TRAINING - M9 PROGRAMMING INTRODUCTION TRAINING-MAXIMUM 6 STUDENTS</p> <p>Course Description: The M9-Series Programming Introduction Course provides the student with the information necessary for developing, debugging and executing a digital test program using this VXI based functional test instrument. The course emphasis is on teaching fundamental digital testing concepts such as static and dynamic patterns, bursts, op-codes, formats, timing, phases and windows. These concepts are then applied by creating a PASS/FAIL test program that will test the functionality of a training board. Using the Soft Front Panel the student will be able to quickly and easily develop both static and dynamic functional tests. The course will use the M910 DTI for lab purposes. The concepts learned apply to other M9-Series Digital Test Instruments.</p> <p>Course Content (Emphasis on the following subject areas): M9-Series architecture and programming, including:</p> <ul style="list-style-type: none">• Basic Digital Testing Concepts• Hardware Overview• Software Overview• Creating a digital test program• API Functions <p>Course Duration: 3 days</p> <p>Prerequisite(s): General programming concepts C/C++ PC Programming</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 13650
777-104-44	<p>ON SITE TRAINING - M9 INTRODUCTION TRAINING-ADDITIONAL STUDENT</p> <p>This is the incremental cost of adding a student to a class configured for 6 students.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 2390



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-102-44	<p>ON SITE TRAINING - M9 ADVANCED PROGRAMMING TRAINING-MAXIMUM 6 STUDENTS</p> <p>Course Description: The M9-Series Advanced Programming with API Functions course provides detailed API function instruction. API, or Application Programmatic Interface, functions are low-level functions that can be used to program every aspect of the Digital Test Instrument (DTI). This course is normally reserved for System Integrators or users that intend to program the DTI using low-level function calls. The students will learn about the API functions through the development of a static and dynamic program. Instruction is provided in C but the concepts learned can easily be applied to other programming environments.</p> <p>Course Content (Emphasis on the following subject areas): M9-Series architecture and programming, including:</p> <ul style="list-style-type: none">• Review of Testing Concepts• Static Testing with API• Dynamic Testing with API <p>Class Duration: 2 days</p> <p>Prerequisite(s): General programming concepts C/C++ PC Programming Must have already taken the M9-Series Programming Introduction course</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 8970
777-105-44	<p>ON SITE TRAINING - M9 ADVANCED TRAINING-ADDITIONAL STUDENT</p> <p>This is the incremental cost of adding a student to a class configured for 6 students.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 1650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-108-44	<p>ON SITE TRAINING - M9 DIAGNOSTICS - MAXIMUM 6 STUDENTS</p> <p>Course Description: The M9-Series Diagnostics Course provides the student with the information necessary for developing diagnostic information on the M9-Series DTI. The student will use this diagnostic data to diagnose faults on a training board. Fault Dictionary and Guided Probe tools and concepts will be covered through lecture and hands-on lab experience.</p> <p>Course Content (Emphasis on the following subject areas): M9-Series Diagnostics software and tools, including:</p> <ul style="list-style-type: none">• Fault Dictionary Diagnostics• Guided Probe Diagnostics• Diagnostics using a DLL (optional)• Boundary Scan (optional) <p>Course duration: 2 days</p> <p>Prerequisite(s) General programming concepts C/C++ PC Programming Must have already taken the M9-Series Programming Introduction course</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 8970
777-108-45	<p>ON SITE TRAINING - M9 DIAGNOSTICS - ADDITIONAL STUDENT</p> <p>This is the incremental cost of adding a student to a class configured for 6 students.</p> <p>NOTES:</p> <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 1650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-180-32	<p>ON SITE TRAINING - DI-SERIES PROGRAMMING CLASS (MAXIMUM 6 STUDENTS)</p> <p>Course Description: The Di-Series Consolidated Programming training provides the student with the information necessary for developing, debugging and executing a digital test program using iStudio Digital Test Editor and exporting the debugged program to ANSI C. In addition, the information necessary for developing, debugging and executing a digital test program using IVI-C application program interface (API) functions is also covered.</p> <p>The course emphasis is on teaching fundamental digital testing concepts such as static and dynamic patterns, pattern sets, op-codes, formats, timing, phases and windows. These concepts are then applied by creating a PASS/FAIL test program that will test the functionality of a training board. The course then advances to using the IVI-C API functions to develop the same program with the additional information on retrieving and presenting failure information.</p> <p>The course will use a Di-Series DTI for lab purposes. The concepts learned apply to other Di-Series Digital Test Instruments.</p> <p>.</p> <p>Course Content (Emphasis on the following subject areas) iStudio Digital Test Editor</p> <ul style="list-style-type: none">• Developing a digital test program• Fundamental concepts of Digital Testing• Constructing an iStudio project• Exporting the debugged program to ANSI C• Executing a digital test program to functionally test a UUT• IVI-C application program interface (API) functions• Developing a digital test program• Debugging a digital test program using Visual C++ <p>Course Duration:</p> <ul style="list-style-type: none">• 5 days <p>Prerequisite(s):</p> <ul style="list-style-type: none">• General programming concepts• Digital applications• C/C++ Programming <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system	\$ 22830



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
	configuration requirements. Consult the training manager for special requirements.	
777-180-35	ON SITE TRAINING - DI-SERIES PROGRAMMING CLASS - ADDITIONAL STUDENT This is the incremental cost of adding a student to a class configured for 6 students. NOTES: <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 3970



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-180-42	<p>ON SITE TRAINING - DI-SERIES DIAGNOSTICS PROGRAMMING CLASS (MAXIMUM 6 STUDENTS)</p> <p>Course Description: The CSI Diagnostics with Di-Series training provides the student with the a procedure for converting, using the LSRTAP to CShell Converter, a LASARTM developed digital test with diagnostics and post processed to IEEE 1445 standard (LSRTAP) to run on the Di-Series DTI. The course covers the software tools used in converting, executing and debugging the LASAR generated Go/Nogo test, verifying the diagnostic data and integration into TestStudio. The course will use a Di-Series DTI for lab purposes. The concepts learned apply to other Di-Series Digital Test Instruments.</p> <p>Course Content (Emphasis on the following subject areas): CSi Diagnostics software tools and architecture, including:</p> <ul style="list-style-type: none">• Introduction to CShell• Introduction to Digital Runtime• LSRTAP to CShell Converter• Fault Dictionary Diagnostics• Guided Probe Diagnostics• TestStudio Integration <p>Class Duration: 3 days</p> <p>Prerequisite(s): Must have taken the Di-Series Consolidated Programming course Familiar with Di-Series DTI and test development tools Familiar with Visual Studio C/C++ Familiar with TestStudio Familiar with LASAR</p> <p>Notes:</p> <ul style="list-style-type: none">• Six Students maximum• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates• Training is conducted using the most current level of software and the standard training material.• Training fixture and lab excercises have certain system configuration requirements. Consult the training manager for special requirements.	\$ 13650



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
777-180-45	ON SITE TRAINING - DI_SERIES DIAGNOSTICS - ADDITIONAL STUDENT This is the incremental cost of adding a student to a class configured for 6 students. NOTES: <ul style="list-style-type: none">• Additional students to a maximum of 8. Above 8 students it requires an additional instructor	\$ 1650
777-525-19	ON SITE TRAINING - APPLICATION CLASS Application Training: This training provides the student with the basic information for developing, debugging and executing a digital and analog test program using this VXI based functional test instrument. The course will review fundamental digital testing concepts such as static and dynamic patterns, bursts, op-codes, formats, timing, phases and windows. Will also introduce the student how to integrate analog test using TestStudio™ This course provides the student with a software and hardware overview plus the basic knowledge to: <ul style="list-style-type: none">• Develop and implement a UUT test plan in TestStudio™• Integrate and debug analog functional test (s) of the test plan• Integrate and debug digital functional test of the test plan• Implement programmatic test sequence control• Integration using TestStudio and Labwindow CVI Course duration: Variable Prerequisite(s): <ul style="list-style-type: none">• Familiarity with LabWindow/CVI, Worked on ATE for at least 3 years• Pricing includes travel&per diem charges for instructor and documentation for each student for classes within the US., For Overseas classes travel will be billed at actual rates	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section L : CASS SUBSYSTEM AND OPTIONS		
616-487-00	BI 1553 TO RACK INTERCONNECT CABLE reference 4027AS0730-01	\$ 14180
616-488-00	BI 429/1773 TO RACK INTERCONNECT CABLE reference 4027AS0732-01	\$ 11760
617-870-03	CABLE, DUPLEX LC TO HSDN 62.5U VERT, OPTICAL FIBER	Consult Factory
617-871-03	CABLE, DUPLEX LC TO HSVN 62.5U VERT, OPTICAL FIBER	\$ 11760
617-876-01	CABLE, HSDN SHORTING PLUG 100U AK, OPTICAL FIBER	Consult Factory
617-876-51	CABLE, HSDN SHORTING PLUG 100U WITHIN PORT AK, OPTICAL FIBER	Consult Factory
617-877-01	CABLE, HSVN SHORTING PLUG 100U AK, OPTICAL FIBER	Consult Factory
617-877-51	CABLE, HSVN SHORTING PLUG 100U WITHIN PORT AK, OPTICAL FIBER	Consult Factory
618-676-01	CABLE, ADAPTER ENET TEST, Minimum order quantity of 5	\$ 170
619-180-02	CABLE, AK AC POWER IN, W/ CONN	Consult Factory
619-290-02	CABLE, AK CHASSIS & CASE GROUND, W/ CONN, Minimum order quantity of 10	Consult Factory
619-992-02	CABLE, ETHERNET TEST ADAPTER EXTENSION AK, TELECOM, WITH CONN, Minimum order quantity of 10	\$ 80
626-265-01	CABLE, DUPLEX LC TO ETHERNET, OPTICAL FIBER	\$ 10070
627-683-01	CABLE, ETHERNET SHORTING PLUG 100U, OPTICAL FIBER	\$ 6260
859-914-00	CENTRAL RESOURCE BOARD (CRB) This part has limited availability.	Consult Factory
987-641-01	1553/J3 CABLE reference 4027AS0731-01	\$ 1030
M-911-00	50MHZ CHANNEL CARD ASSY This part has limited availability.	Consult Factory

The M9 Series instruments have passed their last time buy period and are not recommended for new designs. Since quantities are limited, confirmation of M9 availability will only occur upon order acceptance



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
616-236-00	CASS VXI DTU CHASSIS J2 STATUS CABLE	Consult Factory
859-826-00	VIRGINIA PANEL INTERCONNECT BOARD	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section M : RTCASS/COSSI OPTIONS		
987-060-00	RTCASS VXI CHASSIS ASSEMBLY	Consult Factory
987-177-00	RTCASS VXI CHASSIS LOW POWER OPT A	Consult Factory
987-177-01	RTCASS VXI CHASSIS LP OPTION B	Consult Factory
607-264-01	BI4-SERIES MULTIPLE BUS INTERFACE ADAPTER Cable interface adapter (CIB) for two (2) channel Bi-410 and Bi-411 Bus Test Instruments. This adapter enables fixed cable connections between the Bi-4 Series modules and multiple interface test connectors used for multiple standard serial busses. This CIB eliminates the need for wiring to a switch assembly in order to test the following busses: <ul style="list-style-type: none">• ARINC 429• ARINC 573• TIA/EIA - 232• TIA/EIA - 422• TIA/EIA - 485• MIL-STD-1553• MIL-STD-1773 Note: Customers ordering this item for use in US Navy CASS and CASS compatible test systems must order Teradyne Part Number M-996-55	\$ 7250
M-996-55	BTI 4 CHANNEL CIB KIT FOR CASS/CASS COMPATIBLE SYSTEMS Cable interface adapter (CIB) for four (4) channel Bi-410 and Bi-411 Bus Test Instruments. This adapter enables fixed cable connections between the Bi-4 Series modules and multiple interface test connectors used for multiple standard serial busses. This CIB eliminates the need for wiring to a switch assembly in order to test the following busses: <ul style="list-style-type: none">• ARINC 429• ARINC 573• TIA/EIA - 232• TIA/EIA - 422• TIA/EIA - 485• MIL-STD-1553• MIL-STD-1773 Note: This item is only for customers making purchases for supply to the US Navy for the CASS and CASS compatible test systems. Other customers must order Teradyne Part Number 607-264-00 listed in Price Catalog Section B: Bus Test Instruments	\$ 11060
854-998-86	BI-410 CABLE ASSEMBLY	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
M-992-65	CASS AI7 J4 INTFC KIT · (1) 854-993-93 RACK 4 DISTRIBUTION TUBE · (1) 859-976-00 J4 ADAPTER ASSEMBLY · (6) 854-993-92 RIBBON CABL	Consult Factory
854-993-93	RACK 4 DISTRIBUTION TUBE	Consult Factory
859-976-00	CIB ATI COSSI	Consult Factory
854-999-67	3XAI710 CALIBRATION CBL, COSSI	Consult Factory
987-086-00	J4 CABLE ASSEMBLY FOR COSSI	Consult Factory
987-087-00	J6 CABLE ASSEMBLY FOR COSSI	Consult Factory
987-088-00	J7 CABLE ASSEMBLY FOR COSSI	Consult Factory
859-977-00	AI-710-00 CABLE TO ICA ADAPTER BOARD Cable Interface Board (CIB) for connecting Ai-710-00 interface cables to CASS compatible ICAs that use the Virginia Panel 80 Series mass interconnect system.	Consult Factory
289-013-00	RTCASS TO M9 CRB CIB	Consult Factory
854-982-70	3XA170 CAL CABLE,RTCASS	Consult Factory
854-982-71	AI710 30" RIBBON CBL,RTCASS #1 1W16	Consult Factory
854-983-82	AI710 30" RIBBON CBL,RTCASS #2 1W17	Consult Factory
854-983-83	AI710 30" RIBBON CBL,RTCASS #3 1W18	Consult Factory
854-983-84	AI710 30" RIBBON CBL,RTCASS #4 1W19	Consult Factory
854-983-85	AI710 30" RIBBON CBL,RTCASS #5 1W20	Consult Factory
854-983-86	AI710 30" RIBBON CBL,RTCASS #6 1W21	Consult Factory
854-983-87	HPC PROBE CABLE, RTCASS	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
987-087-01	J6 RTCASS CABLE	Consult Factory
987-236-00	RTCASS GPI J12 CABLE ASSY	Consult Factory
987-237-00	RTCASS GPI J13 CABLE ASSY	Consult Factory
987-238-00	RTCASS GPI J14 CABLE ASSY	Consult Factory
987-239-00	RTCASS GPI J15 CABLE ASSY	Consult Factory
987-240-00	RTCASS GPI J16 CABLE ASSY	Consult Factory
987-241-00	RTCASS GPI J17 CABLE ASSY	Consult Factory
987-242-00	RTCASS GPI J11 CABLE ASSY	Consult Factory
987-243-00	RTCASS GPI J1 & J3 CABLE ASSY	Consult Factory
987-244-00	RTCASS GPI J2 CABLE ASSY	Consult Factory
987-245-00	RTCASS GPI J5 CABLE ASSY	Consult Factory
987-247-00	RTCASS GPI 2A5 ACPS CABLE ASSY	Consult Factory
987-663-00	CBL,J1-J3 AUX TO SMP5003	Consult Factory
987-088-01	J7 RTCASS CABLE	Consult Factory
987-338-00	CBL, ASSY COMMPNL TO CPU, 802.3	Consult Factory
987-419-00	RTCASS VXI CHASSIS POWER SUPPLY	Consult Factory
987-420-00	RTCASS VXI CHASSIS POWER SUPPLY	Consult Factory
987-424-00	RTCASS VXI CHASSIS FAN ASSEMBLY	Consult Factory
987-425-00	RTCASS VXI CHASSIS FAN ASSEMBLY	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
987-426-00	RTCASS VXI CHASSIS POWER SUPPLY	Consult Factory
987-427-00	RTCASS VXI CHASSIS POWER SUPPLY	Consult Factory
987-428-00	RTCASS DTU METER CAL CBL	Consult Factory
987-444-00	PULL TAB,TOP DTI CABLE	Consult Factory
987-445-00	PULL TAB, BOTTOM DTI CABLE	Consult Factory
987-502-00	CBL, CASS TO M9 CRB CIB POWER	Consult Factory
631-363-00	DI-SERIES CIB KIT FOR EO AND HP This kit includes a CIB mounted on a faceplate that can be installed in a VXI chassis to allow easy upgrade with additional DI-Series cards	\$ 2380
987-641-00	CABLE ASSY, RTCASS 1553/J3	Consult Factory



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section P: ZT Series Scopes, Digitizers, AFWGs & OPTIONS		
ZT4211-01LXI	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 2 CH, 256 MS LXI FORMAT	\$ 14400
ZT4211-01PXI	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 2 CH, 256 MS PXI FORMAT	\$ 12520
ZT4211-01VXI	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 2 CH, 256 MS VXI FORMAT	\$ 14980
ZT4211-ESTSVXI	ZT4210 OSCILLOSCOPE COUNTER/TIMER/DIGITIZER VXI FORMAT Product Management approval required	Consult Factory
ZT4211-TCPXIE	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 2 CH, 256 MS PXIE FORMAT WITH TIMER COUNTER FUNCTIONALITY	Consult Factory
ZT4212-01LXI	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 4 CH, 512 MS LXI FORMAT	\$ 23700
ZT4212-01VXI	ZT4210 OSCILLOSCOPE 1 GS/S, 300 MHZ, 8 BITS, 4 CH, 512 MS VXI FORMAT	\$ 24450
ZT4421LXI	ZT4420 OSCILLOSCOPE 1 GS/S, 300 MHZ, 12 BITS, 2 CH, 256 MS LXI FORMAT	\$ 16210
ZT4421PXI	ZT4420 OSCILLOSCOPE 1 GS/S, 300 MHZ, 12 BITS, 2 CH, 256 MS PXI FORMAT	\$ 14090
ZT4421VXI	ZT4420 OSCILLOSCOPE 1 GS/S, 300 MHZ, 12 BITS, 2 CH, 256 MS VXI FORMAT	\$ 16520
ZT4441DFENVPXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 2 CH, 128 MS, DIFFERENTIAL INPUTS, CONFORMAL COATED PXI FORMAT	\$ 21120
ZT4441DFPXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 2 CH, 128 MS, DIFFERENTIAL INPUTS PXI FORMAT	\$ 17820
ZT4441LXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 2 CH, 256 MS LXI FORMAT	\$ 17880
ZT4441PXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 2 CH, 256 MS PXI FORMAT	\$ 15740
ZT4441VXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 2 CH, 256 MS VXI FORMAT	\$ 18240
ZT4442LXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 4 CH, 512 MS LXI FORMAT	\$ 29390
ZT4442VXI	ZT4440 OSCILLOSCOPE 800 MS/S, 300 MHZ, 14 BITS, 4 CH, 512 MS VXI FORMAT	\$ 29980
ZT4611LXI	ZT4610 OSCILLOSCOPE 4 GS/S, 1 GHZ, 8 BITS, 2 CH, 512 MS LXI FORMAT	\$ 20060



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
ZT4611PXI	ZT4610 OSCILLOSCOPE 4 GS/S, 1 GHZ, 8 BITS, 2 CH, 512 MS PXI FORMAT	\$ 18750
ZT4611VXI	ZT4610 OSCILLOSCOPE 4 GS/S, 1 GHZ, 8 BITS, 2 CH, 512 MS VXI FORMAT	\$ 20710
ZT4612LXI	ZT4610 OSCILLOSCOPE 4 GS/S, 1 GHZ, 8 BITS, 4 CH, 128 MS LXI FORMAT	\$ 34750
ZT4612VXI	ZT4610 OSCILLOSCOPE 4 GS/S, 1 GHZ, 8 BITS, 4 CH, 512 MS VXI FORMAT	\$ 35200
ZT4628LXI	ZT4620 OSCILLOSCOPE 2 GS/S, 500 MHZ, 8 BITS, 2 CH, 512 MS LXI FORMAT	\$ 21830
ZT4628PXI	ZT4620 OSCILLOSCOPE 2 GS/S, 500 MHZ, 8 BITS, 2 CH, 512 MS PXI FORMAT	\$ 19740
ZT4628PXIE	ZT4620 OSCILLOSCOPE 2 GS/S, 500 MHZ, 8 BITS, 2 CH, 512 MS PXIE FORMAT	\$ 19740
ZT4628VXI	ZT4620 OSCILLOSCOPE 2 GS/S, 500 MHZ, 8 BITS, 2 CH, 512 MS VXI FORMAT	\$ 22290
ZT4628VXI-JSF	ZT4620 OSCILLOSCOPE 2 GS/S, 500 MHZ, 8 BITS, 2 CH, 512 MS, ADVANCED EXTERNAL TRIGGERING VXI FORMAT	\$ 27010
ZT4629LXI	ZT4620 OSCILLOSCOPE 1 GS/S, 500 MHZ, 8 BITS, 4 CH, 1 GS LXI FORMAT	\$ 37620
ZT4629VXI	ZT4620 OSCILLOSCOPE 1 GS/S, 500 MHZ, 8 BITS, 4 CH, 1 GS VXI FORMAT	\$ 38400
ZT5211-01LXI	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 2 CH, 32 MS LXI FORMAT	\$ 12070
ZT5211-01PXI	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 2 CH, 32 MS PXI FORMAT	\$ 10030
ZT5211-01PXIE	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 2 CH, 32 MS PXIE FORMAT	\$ 10030
ZT5211-01PXIENV	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 2 CH, 32 MS CONFORMAL COATEDPXI FORMAT	\$ 12760
ZT5211-01VXI	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 2 CH, 32 MS VXI FORMAT	\$ 11950
ZT5212-01LXI	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 4 CH, 32 MS LXI FORMAT	\$ 21550
ZT5212-01VXI	ZT5210 WAVEFORM GENERATOR 200 MS/S, 50 MHZ, 14 BITS, 4 CH, 32 MS VXI FORMAT	\$ 21370
ZT6150	1U RACK MOUNT KIT FOR ONE LXI INSTRUMENT	\$ 860



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
ZT6151	1U RACK MOUNT KIT FOR TWO LXI INSTRUMENTS	\$ 1280
ZT824VXI	ZT824 PRODUCT RUBIDIUM FREQUENCY STANDARD VXI FORMAT The default configuration is 5 Sine outputs and 3 TTL outputs. Options available : Part Number Output Configuration ZT824VXI 5 Sine Outputs, 3 TTL Outputs ZT824VXI-80 8 Sine Outputs ZT824VXI-71 7 Sine Outputs, 1 TTL Output ZT824VXI-62 6 Sine Outputs, 2 TTL Outputs ZT824VXI-44 4 Sine Outputs, 4 TTL Outputs ZT824VXI-35 3 Sine Outputs, 5 TTL Outputs ZT824VXI-26 2 Sine Outputs, 6 TTL Outputs ZT824VXI-17 1 Sine Output, 7 TTL Outputs ZT824VXI-08 8 TTL Outputs	\$ 26020



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
Section R: VERTA Optical Subsystems		
651-591-00	VERTA-404 VERTA FOUNDATION Verta Foundation with : <ul style="list-style-type: none">• High speed full cross point switch matrix with one-to-one and one-to-many non-blocking physical layer switching architecture• Protocol independent• Supports up 64 x 64 lanes of input and output high speed signals• Supports speeds from 10Mb/s to 4Gb/s• Controlled through LXI communications interface (RJ45 10/100 Mb/s Ethernet)• 4-slot, 19-inch rackmount enclosure	\$ 44010
653-097-00	VERTA-1004 VERTA FOUNDATION Verta Foundation with : <ul style="list-style-type: none">• High speed full cross point switch matrix with one-to-one and one-to-many non-blocking physical layer switching architecture• Protocol independent• Supports up 64 x 64 lanes of input and output high speed signals• Supports speeds from 10Mb/s to 10Gb/s• Controlled through LXI communications interface (RJ45 10/100 Mb/s Ethernet)• 4-slot, 19-inch rackmount enclosure	\$ 47140
650-992-00	VERTA-1007 VERTA FOUNDATION Verta Foundation with: <ul style="list-style-type: none">• High speed full cross point switch matrix with one-to-one and one-to-many non-blocking physical layer switching architecture• Protocol independent• Supports up 112 x 112 lanes of input and output high speed signals• Supports speeds from 10Mb/s to 10Gb/s• Controlled through LXI communications interface (RJ45 10/100 Mb/s Ethernet)• 7-slot, 19-inch rackmount enclosure	\$ 51850
687-304-00	VERTA CHASSIS RACK INTEGRATION	\$ 1640



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
650-993-00	VERTA-3010 16 PORT SFP/SFP+ TRANSCEIVER SWITCH MODULE Verta-3010 16 Port SFP/SFP+ Transceiver Switch with <ul style="list-style-type: none">• 16 port Small Form-Factor Pluggable (SFP/SFP+) transceiver switch matrix that plugs into the Verta Matrix Switch Foundation chassis• Each port accepts SFP and SFP+ transceivers with signal data rates of 10Mb/s to 10Gb/s.	\$ 9970
650-994-00	VERTA-3020 16 PORT OPTICAL POWER SWITCH MODULE Verta-3020 16 Port Optical Power Switch Module with <ul style="list-style-type: none">• 16 port (16 unidirectional input lanes, 16 unidirectional output lanes) switch matrix that plugs into the Verta Matrix Switch Foundation chassis with capability to set optical power level on output lanes and measure optical power on input lanes• Each port contains transceivers that convert 1GBps to 10GBps optical input signals to electrical signals and back to optical output signals• Support 50/125 Multimode Fiber media (850nm wavelength)• Each port accepts a duplex LC type optical cable connector or two simplex LC connectors	\$ 72840
651-592-00	VERTA-5010 16 CHANNEL OPTICAL POWER MANAGEMENT MODULE Verta-5010 16 Channel Optical Power Management Module with <ul style="list-style-type: none">• 16 channel (8 unidirectional input lanes, 8 unidirectional output lanes) optical power management instrument that plugs into the Verta Matrix Switch Foundation chassis• Continuously measure optical power and attenuate optical power on all lanes• Capability to attenuate optical power level on output channels and measure optical power on input channels• Each port accepts a duplex LC type optical cable connector or two simplex LC connectors• Support 50/125 Multimode Fiber media (850nm wavelength)	\$ 78530



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
678-899-80	VERTA-P3020 SWITCH MATRIX AND OPTICAL POWER MANAGEMENT PXIE INSTRUMENT	\$ 61340
	<p>Verta-P3020 is an 8x8 Optical Matrix Switch and Power Management Instrument with</p> <ul style="list-style-type: none"> • Switching connects ATE bus test instruments to UUT ports • 4 SFP/SFP+ Ports support optical or copper • 4 Optical Parametric Ports for 850nm optical multi-mode fiber connections • 2 Verta-to-Verta daisy chain ports • Switching can be Simplex, Duplex, or Multicast <ul style="list-style-type: none"> • Supports speeds of 1G to 10G • Supports multiple bus protocols • Adjustable output power levels compensate for ATE path loss, assuring repeatable functional test results • Provides Optical Power Measurement • Includes full featured C/C# Application Programming Interface with documentation supporting initialization, setup, and operation modes. • GUI web interface for easy setup and diagnostic troubleshooting 	
659-242-00	IEC POWER CORD, 2M	\$ 290
652-235-02	TIOS -05 HSSUB INSTRUMENT TO VERTA CABLE KIT	\$ 5700
651-285-35	XBEAM V2 TO LC, 32 POS, 7M OPTICAL FIBER CABLE, J15	\$ 29610
651-285-36	XBEAM V2 TO LC, 32 POS, 7M OPTICAL FIBER CABLE, J16	\$ 29610
651-286-01	TIOS FVT ITA FIXTURE, XBEAM V2 64 POS OPTICAL FIBER	\$ 39510
651-285-12	XBEAM V2 TO LC, 32 POSITION, 7M OPTICAL FIBER CABLE, J13	\$ 29610
651-285-13	XBEAM V2 TO LC, 32 POSITION, 7M OPTICAL FIBER CABLE, J14	\$ 29610
652-235-03	TIOS -05 FVT ITA FIXTURE	\$ 78830
658-124-01	TIOS FIBEROPTIC CLEANING KIT	\$ 2590
663-970-00	CABLE, VERTA-3010 QUAD SFP TO QUADRAX 36 IN LENGTH	\$ 6300
663-970-03	CABLE, VERTA-3010 SFP D38999 HERCULES SHORTING PLUG	\$ 8060
663-971-00	CABLE, VERTA-3010 EXPANDED BEAM FIBER OPTIC TO DUPLEX LC 59 IN LENGTH	\$ 14840
663-971-03	CABLE, VERTA-3010 EXPANDED BEAM FIBER OPTIC D38999 HERCULES SHORTING PLUG	\$ 12240
663-972-00	CABLE, VERTA-5010 EXPANDED BEAM FIBER OPTIC TO DUPLEX LC 59 IN LENGTH	\$ 14970
663-972-03	CABLE, VERTA-5010 EXPANDED BEAM FIBER OPTIC D38999 HERCULES SHORTING PLUG	\$ 12000



FUNCTIONAL TEST INSTRUMENTATION AND SUB-SYSTEM PRICE CATALOG NORTH AMERICA

PART #	DESCRIPTION	LIST PRICE
651-967-00	SFP AND LC CABLES FOR ECASS MEK KIT	\$ 3040